



36DX471F350AC2A Information

Heisener.com

Part Number 36DX471F350AC2A

Manufacturer Vishay Sprague

Catagory Capacitors

Category Capacitors

Aluminum Electrolytic Capacitors

Description CAP ALUM 470UF 350V SCREW

Package Radial, Can - Screw Terminals

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com

Request a Quote

Certified Quality

For Reference Only

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









36DX471F350AC2A Specifications

Manufacturer Part Number 36DX471F350AC2A Manufacturer Vishay Sprague Category Capacitors Package Radial, Can - Screw Terminals Series 36DX Capacitance 470μF Tolerance -10%, +50% Voltage - Rated 350V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 1000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing 0.500" (12.70mm) Size / Dimension 1.453" Dia (36.90mm) Height - Seated (Max) 4.252" (108.00mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	•	
Category Capacitors Package Radial, Can - Screw Terminals Series 36DX Capacitance 470μF Tolerance -10%, +50% Voltage - Rated 350V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 1000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing 0.500" (12.70mm) Size / Dimension 1.453" Dia (36.90mm) Height - Seated (Max) 4.252" (108.00mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Manufacturer Part Number	36DX471F350AC2A
Package Radial, Can - Screw Terminals Series 36DX Capacitance 470µF Tolerance -10%, +50% Voltage - Rated 350V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 1000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Lead Spacing 0.500" (12.70mm) Size / Dimension 1.453" Dia (36.90mm) Height - Seated (Max) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radia (Can - Screw Terminals	Manufacturer	Vishay Sprague
PackageRadial, Can - Screw TerminalsSeries36DXCapacitance470μFTolerance-10%, +50%Voltage - Rated350VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Ripple Current - High Frequency-Impedance-Lead Spacing0.500" (12.70mm)Size / Dimension1.453" Dia (36.90mm)Height - Seated (Max)4.252" (108.00mm)Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals	Category	Capacitors
Series 36DX Capacitance 470μF Tolerance -10%, +50% Voltage - Rated 350V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 1000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing 0.500" (12.70mm) Size / Dimension 1.453" Dia (36.90mm) Height - Seated (Max) 4.252" (108.00mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals		Aluminum Electrolytic Capacitors
Capacitance 470μF Tolerance -10%, +50% Voltage - Rated 350V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 1000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing 0.500" (12.70mm) Size / Dimension 1.453" Dia (36.90mm) Height - Seated (Max) 4.252" (108.00mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Package	Radial, Can - Screw Terminals
Tolerance -10%, +50% Voltage - Rated 350V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 1000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing 0.500" (12.70mm) Size / Dimension 1.453" Dia (36.90mm) Height - Seated (Max) 4.252" (108.00mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Raistance) - Ripple Current - Frequency - Chassis Mount Radial, Can - Screw Terminals	Series	36DX
Voltage - Rated350VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Ripple Current - High Frequency-Impedance-Lead Spacing0.500" (12.70mm)Size / Dimension1.453" Dia (36.90mm)Height - Seated (Max)4.252" (108.00mm)Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals	Capacitance	470μF
ESR (Equivalent Series Resistance) Lifetime @ Temp. 1000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency -Ripple Current - High Frequency Impedance Lead Spacing 5.2 / Dimension 1.453" Dia (36.90mm) Height - Seated (Max) Surface Mount Land Size Mounting Type Chassis Mount Package / Case Rio00 Hrs @ 85°C -000 Hrs @ 85°C -000 Hrs @ 85°C -000 Following -0100 Hrs @ 85°C -0100 Hrs @ 85°C	Tolerance	-10%, +50%
Lifetime @ Temp. Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency -Ripple Current - High Frequency Impedance Lead Spacing Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Package / Case 1000 Hrs @ 85°C -40°C ~ 85°C -40°C ~ 85°C -40°C ~ 85°C -600000000000000000000000000000000000	Voltage - Rated	350V
Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency - Impedance Lead Spacing 0.500" (12.70mm) Size / Dimension 1.453" Dia (36.90mm) Height - Seated (Max) Surface Mount Land Size Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	ESR (Equivalent Series Resistance)	-
Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing 0.500" (12.70mm) Size / Dimension 1.453" Dia (36.90mm) Height - Seated (Max) 4.252" (108.00mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Lifetime @ Temp.	1000 Hrs @ 85°C
Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing 0.500" (12.70mm) Size / Dimension 1.453" Dia (36.90mm) Height - Seated (Max) 4.252" (108.00mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Operating Temperature	-40°C ~ 85°C
Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing 0.500" (12.70mm) Size / Dimension 1.453" Dia (36.90mm) Height - Seated (Max) 4.252" (108.00mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Polarization	Polar
Ripple Current - High Frequency Impedance - Lead Spacing 0.500" (12.70mm) Size / Dimension 1.453" Dia (36.90mm) Height - Seated (Max) 4.252" (108.00mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Applications	General Purpose
Impedance-Lead Spacing0.500" (12.70mm)Size / Dimension1.453" Dia (36.90mm)Height - Seated (Max)4.252" (108.00mm)Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals	Ripple Current - Low Frequency	-
Lead Spacing0.500" (12.70mm)Size / Dimension1.453" Dia (36.90mm)Height - Seated (Max)4.252" (108.00mm)Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals	Ripple Current - High Frequency	-
Size / Dimension 1.453" Dia (36.90mm) Height - Seated (Max) 4.252" (108.00mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Impedance	-
Height - Seated (Max) Surface Mount Land Size Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Lead Spacing	0.500" (12.70mm)
Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Size / Dimension	1.453" Dia (36.90mm)
Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Height - Seated (Max)	4.252" (108.00mm)
Package / Case Radial, Can - Screw Terminals	Surface Mount Land Size	-
	Mounting Type	Chassis Mount
Report errors?	Package / Case	Radial, Can - Screw Terminals
		Report errors?

36DX471F350AC2A Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

36DX471F350AC2A Payment Methods



















36DX471F350AC2A Shipping Methods













If you have any question about 36DX471F350AC2A, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com