



36DX861F450BF2B Information

Heisener.com

Part Number 36DX861F450BF2B
Manufacturer Vishay Sprague
Category Capacitors

Aluminum Electrolytic Capacitors

DescriptionCAP ALUM 860UF 450V SCREWPackageRadial, Can - Screw Terminals

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









36DX861F450BF2B Specifications

Manufacturer Part Number 36DX861F450BF2B Manufacturer Vishay Sprague Category Capacitors Package Radial, Can - Screw Terminals Series 36DX Capacitance 860µF Tolerance -10%, +50% Voltage - Rated 450V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 1000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing 0.875" (22.22mm) Size / Dimension 2.079" Dia (52.80mm) Height - Seated (Max) 5.752" (146.10mm)	•	
Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can - Screw Terminals Series 36DX Capacitance 860µF Tolerance -10%, +50% Voltage - Rated 450V ESR (Equivalent Series Resistance) Lifetime @ Temp. 1000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing 0.875" (22.22mm) Size / Dimension Capacitors Adminum Electrolytic Electrons Adminum Electrolytic E	Manufacturer Part Number	36DX861F450BF2B
PackageRadial, Can - Screw TerminalsSeries36DXCapacitance860μFTolerance-10%, +50%Voltage - Rated450VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Ripple Current - High Frequency-Impedance-Lead Spacing0.875" (22.22mm)Size / Dimension2.079" Dia (52.80mm)	Manufacturer	Vishay Sprague
PackageRadial, Can - Screw TerminalsSeries36DXCapacitance860µFTolerance-10%, +50%Voltage - Rated450VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Ripple Current - High Frequency-Impedance-Lead Spacing0.875" (22.22mm)Size / Dimension2.079" Dia (52.80mm)	Category	Capacitors
Series36DXCapacitance860μFTolerance-10%, +50%Voltage - Rated450VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Ripple Current - High Frequency-Impedance-Lead Spacing0.875" (22.22mm)Size / Dimension2.079" Dia (52.80mm)		Aluminum Electrolytic Capacitors
Capacitance 860µF Tolerance -10%, +50% Voltage - Rated 450V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 1000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing 0.875" (22.22mm) Size / Dimension 2.079" Dia (52.80mm)	Package	Radial, Can - Screw Terminals
Tolerance -10%, +50% Voltage - Rated 450V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 1000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing 0.875" (22.22mm) Size / Dimension 2.079" Dia (52.80mm)	Series	36DX
Voltage - Rated 450V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 1000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing 0.875" (22.22mm) Size / Dimension 2.079" Dia (52.80mm)	Capacitance	860μF
ESR (Equivalent Series Resistance) Lifetime @ Temp. 1000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing 0.875" (22.22mm) Size / Dimension - 1000 Hrs @ 85°C -40°C ~ 85°C -40°	Tolerance	-10%, +50%
Lifetime @ Temp. Operating Temperature -40°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing Size / Dimension 1000 Hrs @ 85°C -40°C ~ 85°C Polar Polar -40°C ~ 85°C Polar -40°C ~ 85°C Polar -40°C ~ 85°C -	Voltage - Rated	450V
Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance Lead Spacing 0.875" (22.22mm) Size / Dimension 2.079" Dia (52.80mm)	ESR (Equivalent Series Resistance)	-
Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing 0.875" (22.22mm) Size / Dimension 2.079" Dia (52.80mm)	Lifetime @ Temp.	1000 Hrs @ 85°C
Applications Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing 0.875" (22.22mm) Size / Dimension General Purpose - 0.875" (22.22mm) 2.079" Dia (52.80mm)	Operating Temperature	-40°C ~ 85°C
Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing 0.875" (22.22mm) Size / Dimension 2.079" Dia (52.80mm)	Polarization	Polar
Ripple Current - High Frequency - Impedance - Lead Spacing 0.875" (22.22mm) Size / Dimension 2.079" Dia (52.80mm)	Applications	General Purpose
Impedance - Lead Spacing 0.875" (22.22mm) Size / Dimension 2.079" Dia (52.80mm)	Ripple Current - Low Frequency	-
Lead Spacing 0.875" (22.22mm) Size / Dimension 2.079" Dia (52.80mm)	Ripple Current - High Frequency	-
Size / Dimension 2.079" Dia (52.80mm)	Impedance	-
	Lead Spacing	0.875" (22.22mm)
Height - Seated (Max) 5.752" (146.10mm)	Size / Dimension	2.079" Dia (52.80mm)
6	Height - Seated (Max)	5.752" (146.10mm)
Surface Mount Land Size -	Surface Mount Land Size	-
Mounting Type Chassis Mount	Mounting Type	Chassis Mount
Package / Case Radial, Can - Screw Terminals	Package / Case	Radial, Can - Screw Terminals
Report errors?		Report errors?

36DX861F450BF2B Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

36DX861F450BF2B Payment Methods



















36DX861F450BF2B Shipping Methods













If you have any question about 36DX861F450BF2B, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com