



### 36DX931F450CC2B Information

Heisener.com

Part Number 36DX931F450CC2B
Manufacturer Vishay Sprague
Category Capacitors

Aluminum Electrolytic Capacitors

**Description**CAP ALUM 930UF 450V SCREW**Package**Radial, Can - Screw Terminals

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

For Reference Only

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# 36DX931F450CC2B Specifications

Manufacturer Part Number         36DX931F450CC2B           Manufacturer         Vishay Sprague           Category         Capacitors           Package         Radial, Can - Screw Terminals           Series         36DX           Capacitance         930μF           Tolerance         -10%, +50%           Voltage - Rated         450V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         1000 Hrs @ 85°C           Operating Temperature         -40°C ~ 85°C           Polarization         General Purpose           Ripple Current - Low Frequency         -           Ripple Current - High Frequency         -           Impedance         -           Lead Spacing         1.126" (28.60mm)           Size / Dimension         2.579" Dia (65.50mm)           Height - Seated (Max)         4.252" (108.00mm)           Surface Mount Land Size         -           Mounting Type         Chassis Mount           Package / Case         Radial, Can - Screw Terminals	•	
Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can - Screw Terminals Series 36DX Capacitance 930µF Tolerance -10%, +50% Voltage - Rated 450V ESR (Equivalent Series Resistance) -Lifetime @ Temp. 1000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Applications Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing 1.126" (28.60mm) Size / Dimension Lieight - Seated (Max) Surface Mount Land Size Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Manufacturer Part Number	36DX931F450CC2B
PackageRadial, Can - Screw TerminalsSeries36DXCapacitance930µFTolerance-10%, +50%Voltage - Rated450VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Ripple Current - High Frequency-Impedance-Lead Spacing1.126" (28.60mm)Size / Dimension2.579" Dia (65.50mm)Height - Seated (Max)4.252" (108.00mm)Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals	Manufacturer	Vishay Sprague
PackageRadial, Can - Screw TerminalsSeries36DXCapacitance930µFTolerance-10%, +50%Voltage - Rated450VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Ripple Current - High Frequency-Impedance-Lead Spacing1.126" (28.60mm)Size / Dimension2.579" Dia (65.50mm)Height - Seated (Max)4.252" (108.00mm)Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals	Category	Capacitors
Series         36DX           Capacitance         930µF           Tolerance         -10%, +50%           Voltage - Rated         450V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         1000 Hrs @ 85°C           Operating Temperature         -40°C ~ 85°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         -           Ripple Current - High Frequency         -           Impedance         -           Lead Spacing         1.126" (28.60mm)           Size / Dimension         2.579" Dia (65.50mm)           Height - Seated (Max)         4.252" (108.00mm)           Surface Mount Land Size         -           Mounting Type         Chassis Mount           Package / Case         Radial, Can - Screw Terminals		Aluminum Electrolytic Capacitors
Capacitance         930μF           Tolerance         -10%, +50%           Voltage - Rated         450V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         1000 Hrs @ 85°C           Operating Temperature         -40°C ~ 85°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         -           Ripple Current - High Frequency         -           Lead Spacing         1.126" (28.60mm)           Size / Dimension         2.579" Dia (65.50mm)           Height - Seated (Max)         4.252" (108.00mm)           Surface Mount Land Size         -           Mounting Type         Chassis Mount           Package / Case         Radial, Can - Screw Terminals	Package	Radial, Can - Screw Terminals
Tolerance -10%, +50%  Voltage - Rated 450V  ESR (Equivalent Series Resistance) -1000 Hrs @ 85°C  Lifetime @ Temp. 1000 Hrs @ 85°C  Operating Temperature -40°C ~ 85°C  Polarization Polar  Applications General Purpose  Ripple Current - Low Frequency - Ripple Current - High Frequency -  Impedance -1126" (28.60mm)  Size / Dimension 2.579" Dia (65.50mm)  Height - Seated (Max) 4.252" (108.00mm)  Surface Mount Land Size -1  Mounting Type Chassis Mount  Package / Case Raistance) -1  Ead Spacing Chassis Mount  Radial, Can - Screw Terminals	Series	36DX
Voltage - Rated450VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Ripple Current - High Frequency-Impedance-Lead Spacing1.126" (28.60mm)Size / Dimension2.579" Dia (65.50mm)Height - Seated (Max)4.252" (108.00mm)Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals	Capacitance	930µF
ESR (Equivalent Series Resistance)  Lifetime @ Temp.  1000 Hrs @ 85°C  Operating Temperature  -40°C ~ 85°C  Polarization  Applications  General Purpose  Ripple Current - Low Frequency  -Ripple Current - High Frequency  Impedance  Lead Spacing  1.126" (28.60mm)  Size / Dimension  4.252" (108.00mm)  Surface Mount Land Size  Mounting Type  Chassis Mount  Package / Case  Radial, Can - Screw Terminals	Tolerance	-10%, +50%
Lifetime @ Temp.  Operating Temperature  -40°C ~ 85°C  Polarization  Polar  Applications  General Purpose  Ripple Current - Low Frequency  -Ripple Current - High Frequency  Impedance  Lead Spacing  Size / Dimension  Height - Seated (Max)  Surface Mount Land Size  Mounting Type  Package / Case  1000 Hrs @ 85°C  -40°C ~ 85°C  -40°C ~ 85°C  General Purpose  -  1.126° (28.60mm)  -  2.579° Dia (65.50mm)  4.252° (108.00mm)  Chassis Mount  Package / Case  Radial, Can - Screw Terminals	Voltage - Rated	450V
Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency - Impedance Lead Spacing 1.126" (28.60mm) Size / Dimension Leight - Seated (Max) Surface Mount Land Size Mounting Type Chassis Mount Package / Case Roll and Purpose Ceneral Purpose - Lead Sp. Case - Chassis Mount Radial, Can - Screw Terminals	ESR (Equivalent Series Resistance)	-
Polarization Polar  Applications General Purpose  Ripple Current - Low Frequency -  Ripple Current - High Frequency -  Impedance -  Lead Spacing 1.126" (28.60mm)  Size / Dimension 2.579" Dia (65.50mm)  Height - Seated (Max) 4.252" (108.00mm)  Surface Mount Land Size -  Mounting Type Chassis Mount  Package / Case Radial, Can - Screw Terminals	Lifetime @ Temp.	1000 Hrs @ 85°C
Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing Size / Dimension Leight - Seated (Max) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case General Purpose  - General Purpose -  Chassis Mount  - Chassis Mount Reight - Seated (Max) - Radial, Can - Screw Terminals	Operating Temperature	-40°C ~ 85°C
Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing 1.126" (28.60mm) Size / Dimension 2.579" Dia (65.50mm) Height - Seated (Max) 4.252" (108.00mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Polarization	Polar
Ripple Current - High Frequency Impedance - Lead Spacing 1.126" (28.60mm) Size / Dimension 2.579" Dia (65.50mm) Height - Seated (Max) 4.252" (108.00mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Applications	General Purpose
Impedance-Lead Spacing1.126" (28.60mm)Size / Dimension2.579" Dia (65.50mm)Height - Seated (Max)4.252" (108.00mm)Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals	Ripple Current - Low Frequency	-
Lead Spacing1.126" (28.60mm)Size / Dimension2.579" Dia (65.50mm)Height - Seated (Max)4.252" (108.00mm)Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals	Ripple Current - High Frequency	-
Size / Dimension 2.579" Dia (65.50mm)  Height - Seated (Max) 4.252" (108.00mm)  Surface Mount Land Size -  Mounting Type Chassis Mount  Package / Case Radial, Can - Screw Terminals	Impedance	-
Height - Seated (Max)  Surface Mount Land Size  Mounting Type  Chassis Mount  Package / Case  A.252" (108.00mm)  -  Chassis Mount  Radial, Can - Screw Terminals	Lead Spacing	1.126" (28.60mm)
Surface Mount Land Size -  Mounting Type Chassis Mount  Package / Case Radial, Can - Screw Terminals	Size / Dimension	2.579" Dia (65.50mm)
Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Height - Seated (Max)	4.252" (108.00mm)
Package / Case Radial, Can - Screw Terminals	Surface Mount Land Size	-
	Mounting Type	Chassis Mount
Report errors?	Package / Case	Radial, Can - Screw Terminals
		Report errors?

#### 36DX931F450CC2B Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## 36DX931F450CC2B Payment Methods



















# 36DX931F450CC2B Shipping Methods













If you have any question about 36DX931F450CC2B, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com