



36DY144F015DF2A Information

Heisener.com

For Reference Only

Part Number 36DY144F015DF2A
Manufacturer Vishay Sprague
Category Capacitors

Aluminum Electrolytic Capacitors

Description CAP ALUM 140000UF 15V SCREW

Package Radial, Can - Screw Terminals

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









36DY144F015DF2A Specifications

Manufacturer Part Number 36DY144F015DF2A Manufacturer Vishay Sprague Category Capacitors Package Radial, Can - Screw Terminals Series 36DY Capacitance 140000µF Tolerance -10%, +50% Voltage - Rated 15V ESR (Equivalent Series Resistance) - ESR (Equivalent Series Resistance) - Operating Temperature 2000 Hrs @ 85°C Operating Temperature 40°C ~ 85°C Polarization General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing 1.252" (31.80mm) Size / Dimension 3.079" Dia (78.20mm) Height - Seated (Max) 5.752" (146.10mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	*	
Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can - Screw Terminals Series 36DY Capacitance 140000µF Tolerance -10%, +50% Voltage - Rated 15V ESR (Equivalent Series Resistance) -Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing 1.252" (31.80mm) Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Manufacturer Part Number	36DY144F015DF2A
Aluminum Electrolytic Capacitors Package Radial, Can - Screw Terminals Series 36DY Capacitance 140000µF Tolerance -10%, +50% Voltage - Rated 15V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing 1.252" (31.80mm) Size / Dimension 3.079" Dia (78.20mm) Height - Seated (Max) 5.752" (146.10mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Manufacturer	Vishay Sprague
Package Radial, Can - Screw Terminals Series 36DY Capacitance 140000μF Tolerance -10%, +50% Voltage - Rated 15V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing 1.252" (31.80mm) Size / Dimension 3.079" Dia (78.20mm) Height - Seated (Max) 5.752" (146.10mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Category	Capacitors
Series 36DY Capacitance 140000µF Tolerance -10%, +50% Voltage - Rated 15V ESR (Equivalent Series Resistance) -10K @ 85°C Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance -1.252" (31.80mm) Size / Dimension 3.079" Dia (78.20mm) Height - Seated (Max) 5.752" (146.10mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Rated (Max) 8.360 Mrs. Serew Terminals		Aluminum Electrolytic Capacitors
Capacitance 140000µF Tolerance -10%, +50% Voltage - Rated 15V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing 1.252" (31.80mm) Size / Dimension 3.079" Dia (78.20mm) Height - Seated (Max) 5.752" (146.10mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Package	Radial, Can - Screw Terminals
Tolerance -10%, +50% Voltage - Rated 15V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing 1.252" (31.80mm) Size / Dimension 3.079" Dia (78.20mm) Height - Seated (Max) 5.752" (146.10mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Raid (Max) Radial, Can - Screw Terminals	Series	36DY
Voltage - Rated ESR (Equivalent Series Resistance) Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing 1.252" (31.80mm) Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Capacitance	140000μF
ESR (Equivalent Series Resistance) Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency -Ripple Current - High Frequency Impedance Lead Spacing 1.252" (31.80mm) Size / Dimension 3.079" Dia (78.20mm) Height - Seated (Max) 5.752" (146.10mm) Surface Mount Land Size Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Tolerance	-10%, +50%
Lifetime @ Temp. Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing 1.252" (31.80mm) Size / Dimension Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Voltage - Rated	15V
Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency - Impedance Lead Spacing 1.252" (31.80mm) Size / Dimension Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	ESR (Equivalent Series Resistance)	-
Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing 1.252" (31.80mm) Size / Dimension 3.079" Dia (78.20mm) Height - Seated (Max) 5.752" (146.10mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Lifetime @ Temp.	2000 Hrs @ 85°C
Applications Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing 1.252" (31.80mm) Size / Dimension 3.079" Dia (78.20mm) Height - Seated (Max) 5.752" (146.10mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Operating Temperature	-40°C ~ 85°C
Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing 1.252" (31.80mm) Size / Dimension 3.079" Dia (78.20mm) Height - Seated (Max) 5.752" (146.10mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Polarization	Polar
Ripple Current - High Frequency Impedance Lead Spacing 1.252" (31.80mm) Size / Dimension 3.079" Dia (78.20mm) Height - Seated (Max) 5.752" (146.10mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Applications	General Purpose
Impedance-Lead Spacing1.252" (31.80mm)Size / Dimension3.079" Dia (78.20mm)Height - Seated (Max)5.752" (146.10mm)Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals	Ripple Current - Low Frequency	-
Lead Spacing1.252" (31.80mm)Size / Dimension3.079" Dia (78.20mm)Height - Seated (Max)5.752" (146.10mm)Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals	Ripple Current - High Frequency	-
Size / Dimension 3.079" Dia (78.20mm) Height - Seated (Max) 5.752" (146.10mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Impedance	-
Height - Seated (Max) Surface Mount Land Size Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Lead Spacing	1.252" (31.80mm)
Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Size / Dimension	3.079" Dia (78.20mm)
Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Height - Seated (Max)	5.752" (146.10mm)
Package / Case Radial, Can - Screw Terminals	Surface Mount Land Size	-
	Mounting Type	Chassis Mount
Report errors?	Package / Case	Radial, Can - Screw Terminals
		Report errors?

36DY144F015DF2A Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

36DY144F015DF2A Payment Methods



















36DY144F015DF2A Shipping Methods













If you have any question about 36DY144F015DF2A, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com