



372HXP Information

Heisener.com

For Reference Only

Part Number 372HXP

Manufacturer Hammond Manufacturing

Category Transformers

Power Transformers

Description XFRMR LAMINATED 191VA CHAS MOUNT

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









372HXP Specifications

Manufacturer Part Number 372HXP Manufacturer Hammond Manufacturing Category Transformers Power Transformers Power Transformers Series 300 Type Laminated Core Voltage - Primary 100V, 110V, 120V, 200V, 220V, 240V Voltage - Secondary (Full Load) 600V, 6.3V, 5V Current - Output (Max) 230mA, 6A, 3A Primary Winding(s) Dual, Multiple Taps Secondary Winding(s) Triple Center Tap Yes Power - Max 191VA Mounting Type Chassis Mount Termination Style Wire Leads Size / Dimension 101.60mm L x 95.25mm W Height - Seated (Max) 115.90mm Voltage - Isolation 2000Vrms Weight 7.2 lbs (3.3kg)		
Category Transformers Power Transformers - Series 300 Type Laminated Core Voltage - Primary 100V, 110V, 120V, 200V, 220V, 240V Voltage - Secondary (Full Load) 600V, 6.3V, 5V Current - Output (Max) 230mA, 6A, 3A Primary Winding(s) Dual, Multiple Taps Secondary Winding(s) Triple Center Tap Yes Power - Max 191VA Mounting Type Chassis Mount Termination Style Wire Leads Size / Dimension 101.60mm L x 95.25mm W Height - Seated (Max) 115.90mm Voltage - Isolation 2000Vrms Weight 7.2 lbs (3.3kg)	Manufacturer Part Number	372HXP
Power Transformers	Manufacturer	Hammond Manufacturing
Package - Series 300 Type Laminated Core Voltage - Primary 100V, 110V, 120V, 200V, 220V, 240V Voltage - Secondary (Full Load) 600V, 6.3V, 5V Current - Output (Max) 230mA, 6A, 3A Primary Winding(s) Dual, Multiple Taps Secondary Winding(s) Triple Center Tap Yes Power - Max 191VA Mounting Type Chassis Mount Termination Style Wire Leads Size / Dimension 101.60mm L x 95.25mm W Height - Seated (Max) 115.90mm Voltage - Isolation 2000Vrms Weight 7.2 lbs (3.3kg)	Category	Transformers
Series 300 Type Laminated Core Voltage - Primary 100V, 110V, 120V, 200V, 220V, 240V Voltage - Secondary (Full Load) 600V, 6.3V, 5V Current - Output (Max) 230mA, 6A, 3A Primary Winding(s) Dual, Multiple Taps Secondary Winding(s) Triple Center Tap Yes Power - Max 191VA Mounting Type Chassis Mount Termination Style Wire Leads Size / Dimension 101.60mm L x 95.25mm W Height - Seated (Max) 115.90mm Voltage - Isolation 2000Vrms Weight 7.2 lbs (3.3kg)		Power Transformers
Type Voltage - Primary 100V, 110V, 120V, 200V, 220V, 240V Voltage - Secondary (Full Load) 600V, 6.3V, 5V Current - Output (Max) 230mA, 6A, 3A Primary Winding(s) Dual, Multiple Taps Secondary Winding(s) Triple Center Tap Yes Power - Max 191VA Mounting Type Chassis Mount Termination Style Size / Dimension 101.60mm L x 95.25mm W Height - Seated (Max) Voltage - Isolation 2000Vrms Weight 7.2 lbs (3.3kg)	Package	-
Voltage - Primary Voltage - Secondary (Full Load) 600V, 110V, 120V, 200V, 220V, 240V 600V, 6.3V, 5V Current - Output (Max) Primary Winding(s) Secondary Winding(s) Center Tap Yes Power - Max 191VA Mounting Type Chassis Mount Termination Style Size / Dimension Height - Seated (Max) Voltage - Isolation Weight 100V, 110V, 120V, 200V, 220V, 240V 600V, 6.3V, 5V 230mA, 6A, 3A Primary Winding(s) Triple Yes Chassis Mount Wire Leads 191VA 191VA Wire Leads 101.60mm L x 95.25mm W 115.90mm Voltage - Isolation 2000Vrms 7.2 lbs (3.3kg)	Series	300
Voltage - Secondary (Full Load) Current - Output (Max) Primary Winding(s) Secondary Winding(s) Center Tap Power - Max Mounting Type Chassis Mount Termination Style Size / Dimension Height - Seated (Max) Voltage - Isolation Weight 600V, 6.3V, 5V 230mA, 6A, 3A Dual, Multiple Taps Triple Yes Chassis Mount Yes United the seated (Max) 191VA Wire Leads 101.60mm L x 95.25mm W 115.90mm 2000Vrms 7.2 lbs (3.3kg)	Туре	Laminated Core
Current - Output (Max) Primary Winding(s) Secondary Winding(s) Center Tap Power - Max Mounting Type Chassis Mount Termination Style Size / Dimension Voltage - Isolation Weight 230mA, 6A, 3A Dual, Multiple Taps Poul, Multiple Taps Poul, Multiple Taps Yes Poul, Multiple Taps Yes Chassis Mount 191VA Wire Leads Wire Leads 101.60mm L x 95.25mm W 115.90mm 2000Vrms Voltage - Isolation Voltage - Isolation Via July July July July July July July July	Voltage - Primary	100V, 110V, 120V, 200V, 220V, 240V
Primary Winding(s) Secondary Winding(s) Triple Center Tap Yes Power - Max 191VA Mounting Type Chassis Mount Termination Style Size / Dimension Height - Seated (Max) Voltage - Isolation Weight Dual, Multiple Taps Triple Yes Yes 191VA Chassis Mount Unit Leads 101.60mm L x 95.25mm W 115.90mm Voltage - Isolation 2000Vrms 7.2 lbs (3.3kg)	Voltage - Secondary (Full Load)	600V, 6.3V, 5V
Secondary Winding(s) Center Tap Yes Power - Max 191VA Mounting Type Chassis Mount Termination Style Wire Leads Size / Dimension 101.60mm L x 95.25mm W Height - Seated (Max) Voltage - Isolation 2000Vrms Weight 7.2 lbs (3.3kg)	Current - Output (Max)	230mA, 6A, 3A
Center Tap Power - Max 191VA Mounting Type Chassis Mount Termination Style Wire Leads Size / Dimension 101.60mm L x 95.25mm W Height - Seated (Max) Voltage - Isolation Voltage - Isolation Yes 191VA Wire Leads 101.60mm L x 95.25mm W 115.90mm 7.2 lbs (3.3kg)	Primary Winding(s)	Dual, Multiple Taps
Power - Max Mounting Type Chassis Mount Termination Style Size / Dimension 101.60mm L x 95.25mm W Height - Seated (Max) Voltage - Isolation Voltage - Isolation Weight 191VA Wire Leads 101.60mm L x 95.25mm W 115.90mm 7.2 lbs (3.3kg)	Secondary Winding(s)	Triple
Mounting Type Chassis Mount Termination Style Wire Leads Size / Dimension 101.60mm L x 95.25mm W Height - Seated (Max) 115.90mm Voltage - Isolation 2000Vrms Weight 7.2 lbs (3.3kg)	Center Tap	Yes
Termination Style Wire Leads Size / Dimension 101.60mm L x 95.25mm W Height - Seated (Max) 115.90mm Voltage - Isolation 2000Vrms Weight 7.2 lbs (3.3kg)	Power - Max	191VA
Size / Dimension 101.60mm L x 95.25mm W Height - Seated (Max) 115.90mm Voltage - Isolation 2000Vrms Weight 7.2 lbs (3.3kg)	Mounting Type	Chassis Mount
Height - Seated (Max) Voltage - Isolation Veight 115.90mm 2000Vrms 7.2 lbs (3.3kg)	Termination Style	Wire Leads
Voltage - Isolation 2000Vrms Weight 7.2 lbs (3.3kg)	Size / Dimension	101.60mm L x 95.25mm W
Weight 7.2 lbs (3.3kg)	Height - Seated (Max)	115.90mm
	Voltage - Isolation	2000Vrms
Report errors?	Weight	7.2 lbs (3.3kg)
		Report errors?

372HXP Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

372HXP Payment Methods





















372HXP Shipping Methods













If you have any question about 372HXP, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com