

### **373CZ Information**

Heisener.com

Part Number 373CZ

Manufacturer Hammond Manufacturing

**Category** Transformers

**Power Transformers** 

**Description** XFRMR LAMINATED 159VA CHAS MOUNT

Package

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **373CZ Specifications**

Manufacturer Part Number         373CZ           Manufacturer         Hammond Manufacturing           Category         Transformers           Package         -           Series         300           Type         Laminated Core           Voltage - Primary         100V, 110V, 120V, 200V, 220V, 240V           Voltage - Secondary (Full Load)         650V, 6.3V, 5V           Current - Output (Max)         173mA, 5A, 3A           Primary Winding(s)         Dual, Multiple Taps           Secondary Winding(s)         Four           Center Tap         Yes           Power - Max         159 VA           Mounting Type         Chassis Mount           Termination Style         Wire Leads           Size / Dimension         79.38mm L x 63.50mm W           Height - Seated (Max)         103.12mm           Voltage - Isolation         2000Vrms           Weight         5.7 lbs (2.6kg)		
Category         Transformers           Power Transformers           Package         -           Series         300           Type         Laminated Core           Voltage - Primary         100V, 110V, 120V, 200V, 220V, 240V           Voltage - Secondary (Full Load)         650V, 6.3V, 5V           Current - Output (Max)         173mA, 5A, 3A           Primary Winding(s)         Dual, Multiple Taps           Secondary Winding(s)         Four           Center Tap         Yes           Power - Max         159 VA           Mounting Type         Chassis Mount           Termination Style         Wire Leads           Size / Dimension         79.38mm L x 63.50mm W           Height - Seated (Max)         103.12mm           Voltage - Isolation         2000Vrms           Weight         5.7 lbs (2.6kg)	Manufacturer Part Number	373CZ
Power Transformers           Package         -           Series         300           Type         Laminated Core           Voltage - Primary         100V, 110V, 120V, 200V, 220V, 240V           Voltage - Secondary (Full Load)         650V, 6.3V, 5V           Current - Output (Max)         173mA, 5A, 3A           Primary Winding(s)         Dual, Multiple Taps           Secondary Winding(s)         Four           Center Tap         Yes           Power - Max         159 VA           Mounting Type         Chassis Mount           Termination Style         Wire Leads           Size / Dimension         79.38mm L x 63.50mm W           Height - Seated (Max)         103.12mm           Voltage - Isolation         2000Vrms           Weight         5.7 lbs (2.6kg)	Manufacturer	Hammond Manufacturing
Package         -           Series         300           Type         Laminated Core           Voltage - Primary         100V, 110V, 120V, 200V, 220V, 240V           Voltage - Secondary (Full Load)         650V, 6.3V, 5V           Current - Output (Max)         173mA, 5A, 3A           Primary Winding(s)         Dual, Multiple Taps           Secondary Winding(s)         Four           Center Tap         Yes           Power - Max         159 VA           Mounting Type         Chassis Mount           Termination Style         Wire Leads           Size / Dimension         79.38mm L x 63.50mm W           Height - Seated (Max)         103.12mm           Voltage - Isolation         2000Vrms           Weight         5.7 lbs (2.6kg)	Category	Transformers
Series         300           Type         Laminated Core           Voltage - Primary         100V, 110V, 120V, 200V, 220V, 240V           Voltage - Secondary (Full Load)         650V, 6.3V, 5V           Current - Output (Max)         173mA, 5A, 3A           Primary Winding(s)         Dual, Multiple Taps           Secondary Winding(s)         Four           Center Tap         Yes           Power - Max         159 VA           Mounting Type         Chassis Mount           Termination Style         Wire Leads           Size / Dimension         79.38mm L x 63.50mm W           Height - Seated (Max)         103.12mm           Voltage - Isolation         2000Vrms           Weight         5.7 lbs (2.6kg)		Power Transformers
Type Laminated Core  Voltage - Primary 100V, 110V, 120V, 200V, 220V, 240V  Voltage - Secondary (Full Load) 650V, 6.3V, 5V  Current - Output (Max) 173mA, 5A, 3A  Primary Winding(s) Dual, Multiple Taps  Secondary Winding(s) Four  Center Tap Yes  Power - Max 159 VA  Mounting Type Chassis Mount  Termination Style Wire Leads  Size / Dimension 79.38mm L x 63.50mm W  Height - Seated (Max) 103.12mm  Voltage - Isolation 2000Vrms  Weight	Package	-
Voltage - Primary  Voltage - Secondary (Full Load)  650V, 6.3V, 5V  Current - Output (Max)  Primary Winding(s)  Secondary Winding(s)  Four  Center Tap  Yes  Power - Max  Mounting Type  Chassis Mount  Termination Style  Size / Dimension  Height - Seated (Max)  Winding - Isolation  Weight  100V, 110V, 120V, 200V, 220V, 240V  650V, 6.3V, 5V  173mA, 5A, 3A  Primary Winding(s)  Four  Yes  Four  Chassis Mount  Wire Leads  159 VA  Wire Leads  103.12mm  Voltage - Isolation  2000Vrms  5.7 lbs (2.6kg)	Series	300
Voltage - Secondary (Full Load) Current - Output (Max) 173mA, 5A, 3A Primary Winding(s) Dual, Multiple Taps Secondary Winding(s) Four Center Tap Yes Power - Max 159 VA Mounting Type Chassis Mount Termination Style Size / Dimension 79.38mm L x 63.50mm W Height - Seated (Max) Voltage - Isolation Voltage - Isolation 5.7 lbs (2.6kg)	Type	Laminated Core
Current - Output (Max)  Primary Winding(s)  Dual, Multiple Taps  Secondary Winding(s)  Four  Center Tap  Power - Max  Mounting Type  Chassis Mount  Termination Style  Size / Dimension  Four  Vire Leads  79.38mm L x 63.50mm W  Height - Seated (Max)  Voltage - Isolation  Weight  173mA, 5A, 3A  103.18mm  104. Multiple Taps  Four  Chassis Mount  Wire Leads  159 VA  103.12mm  2000Vrms  5.7 lbs (2.6kg)	Voltage - Primary	100V, 110V, 120V, 200V, 220V, 240V
Primary Winding(s)  Secondary Winding(s)  Four  Center Tap  Yes  Power - Max  159 VA  Mounting Type  Chassis Mount  Termination Style  Size / Dimension  Height - Seated (Max)  Voltage - Isolation  Weight  Dual, Multiple Taps  Four  Chassis Mount  159 VA  Wire Leads  159 VA  Wire Leads  103.12mm  Voltage - Isolation  2000Vrms  5.7 lbs (2.6kg)	Voltage - Secondary (Full Load)	650V, 6.3V, 5V
Secondary Winding(s)  Center Tap  Yes  Power - Max  159 VA  Mounting Type  Chassis Mount  Termination Style  Wire Leads  Size / Dimension  79.38mm L x 63.50mm W  Height - Seated (Max)  Voltage - Isolation  2000Vrms  Weight  5.7 lbs (2.6kg)	Current - Output (Max)	173mA, 5A, 3A
Center Tap  Power - Max  159 VA  Mounting Type  Chassis Mount  Termination Style  Wire Leads  Size / Dimension  79.38mm L x 63.50mm W  Height - Seated (Max)  103.12mm  Voltage - Isolation  2000Vrms  Weight  5.7 lbs (2.6kg)	Primary Winding(s)	Dual, Multiple Taps
Power - Max  Mounting Type  Chassis Mount  Termination Style  Wire Leads  Size / Dimension  79.38mm L x 63.50mm W  Height - Seated (Max)  103.12mm  Voltage - Isolation  2000Vrms  Weight  5.7 lbs (2.6kg)	Secondary Winding(s)	Four
Mounting Type Chassis Mount  Termination Style Wire Leads  Size / Dimension 79.38mm L x 63.50mm W  Height - Seated (Max) 103.12mm  Voltage - Isolation 2000Vrms  Weight 5.7 lbs (2.6kg)	Center Tap	Yes
Termination Style Wire Leads Size / Dimension 79.38mm L x 63.50mm W Height - Seated (Max) 103.12mm Voltage - Isolation 2000Vrms Weight 5.7 lbs (2.6kg)	Power - Max	159 VA
Size / Dimension79.38mm L x 63.50mm WHeight - Seated (Max)103.12mmVoltage - Isolation2000VrmsWeight5.7 lbs (2.6kg)	Mounting Type	Chassis Mount
Height - Seated (Max)  Voltage - Isolation  Weight  103.12mm  2000Vrms  5.7 lbs (2.6kg)	Termination Style	Wire Leads
Voltage - Isolation 2000Vrms Weight 5.7 lbs (2.6kg)	Size / Dimension	79.38mm L x 63.50mm W
Weight 5.7 lbs (2.6kg)	Height - Seated (Max)	103.12mm
	Voltage - Isolation	2000Vrms
Report errors?	Weight	5.7 lbs (2.6kg)
1		Report errors?

#### **373CZ Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **373CZ Payment Methods**



















# **373CZ Shipping Methods**













If you have any question about 373CZ, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com