



377NB3C2000T Information

Heisener.com

Part Number 377NB3C2000T

Manufacturer CTS-Frequency Controls

Category Crystals, Oscillators, Resonators

Oscillators

Description OSC VCXO 200.0000MHZ LVDS SMD

Package 6-SMD, No Lead

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









377NB3C2000T Specifications

Manufacturer Part Number 377NB3C2000T Manufacturer CTS-Frequency Controls Category Crystals, Oscillators, Resonators Package 6-SMD, No Lead Series 377 Type VCXO Frequency 200MHz Function Enable/Disable Output LVDS Voltage - Supply 2.5V Frequency Stability ±50ppm Operating Temperature -20°C ~ 70°C Current - Supply (Max) 55mA Ratings - Mounting Type Surface Mount Package / Case 6-SMD, No Lead Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm) Height - Seated (Max) 0.079" (2.00mm)	•	
Category Crystals, Oscillators, Resonators Package 6-SMD, No Lead Series 377 Type VCXO Frequency 200MHz Function Enable/Disable Output LVDS Voltage - Supply 2.5V Frequency Stability ±50ppm Operating Temperature -20°C ~ 70°C Current - Supply (Max) 55mA Ratings - Mounting Type Surface Mount Package / Case 6-SMD, No Lead Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm) Height - Seated (Max) 0.079" (2.00mm)	Manufacturer Part Number	377NB3C2000T
Package 6-SMD, No Lead Series 377 Type VCXO Frequency 200MHz Function Enable/Disable Output LVDS Voltage - Supply 2.5V Frequency Stability ±50ppm Operating Temperature -20°C ~ 70°C Current - Supply (Max) 55mA Ratings - Mounting Type Surface Mount Package / Case 6-SMD, No Lead Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm) Height - Seated (Max) 0.079" (2.00mm)	Manufacturer	CTS-Frequency Controls
Package 6-SMD, No Lead Series 377 Type VCXO Frequency 200MHz Function Enable/Disable Output LVDS Voltage - Supply 2.5V Frequency Stability ±50ppm Operating Temperature -20°C ~ 70°C Current - Supply (Max) 55mA Ratings - Mounting Type Surface Mount Package / Case 6-SMD, No Lead Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm) Height - Seated (Max) 0.079" (2.00mm)	Category	Crystals, Oscillators, Resonators
Series 377 Type VCXO Frequency 200MHz Function Enable/Disable Output LVDS Voltage - Supply 2.5V Frequency Stability ±50ppm Operating Temperature -20°C ~ 70°C Current - Supply (Max) 55mA Ratings - Mounting Type Surface Mount Package / Case 6-SMD, No Lead Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm) Height - Seated (Max) 0.079" (2.00mm)		Oscillators
Type VCXO Frequency 200MHz Function Enable/Disable Output LVDS Voltage - Supply 2.5V Frequency Stability ±50ppm Operating Temperature -20°C ~ 70°C Current - Supply (Max) 55mA Ratings - Mounting Type Surface Mount Package / Case 6-SMD, No Lead Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm) Height - Seated (Max) 0.079" (2.00mm)	Package	6-SMD, No Lead
Frequency 200MHz Function Enable/Disable Output LVDS Voltage - Supply 2.5V Frequency Stability ±50ppm Operating Temperature -20°C ~ 70°C Current - Supply (Max) 55mA Ratings - Mounting Type Surface Mount Package / Case 6-SMD, No Lead Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm) Height - Seated (Max) 0.079" (2.00mm)	Series	377
Function Cutput LVDS Voltage - Supply 2.5V Frequency Stability Operating Temperature -20°C ~ 70°C Current - Supply (Max) Ratings - Mounting Type Surface Mount Package / Case 6-SMD, No Lead Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm) Height - Seated (Max) Enable/Disable LVDS - LVDS - Sufface -20°C ~ 70°C -20°C ~ 70°C	Туре	VCXO
Output LVDS Voltage - Supply 2.5V Frequency Stability ±50ppm Operating Temperature -20°C ~ 70°C Current - Supply (Max) 55mA Ratings - Mounting Type Surface Mount Package / Case 6-SMD, No Lead Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm) Height - Seated (Max) 0.079" (2.00mm)	Frequency	200MHz
Voltage - Supply 2.5V Frequency Stability ±50ppm Operating Temperature -20°C ~ 70°C Current - Supply (Max) 55mA Ratings - Mounting Type Surface Mount Package / Case 6-SMD, No Lead Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm) Height - Seated (Max) 0.079" (2.00mm)	Function	Enable/Disable
Frequency Stability ±50ppm Operating Temperature -20°C ~ 70°C Current - Supply (Max) 55mA Ratings - Mounting Type Surface Mount Package / Case 6-SMD, No Lead Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm) Height - Seated (Max) 0.079" (2.00mm)	Output	LVDS
Operating Temperature -20°C ~ 70°C Current - Supply (Max) S5mA Ratings - Mounting Type Surface Mount Package / Case 6-SMD, No Lead Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm) Height - Seated (Max) 0.079" (2.00mm)	Voltage - Supply	2.5V
Current - Supply (Max) Ratings - Mounting Type Surface Mount Package / Case 6-SMD, No Lead Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm) Height - Seated (Max) 0.079" (2.00mm)	Frequency Stability	±50ppm
Ratings - Mounting Type Surface Mount Package / Case 6-SMD, No Lead Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm) Height - Seated (Max) 0.079" (2.00mm)	Operating Temperature	-20°C ~ 70°C
Mounting Type Surface Mount Package / Case 6-SMD, No Lead Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm) Height - Seated (Max) 0.079" (2.00mm)	Current - Supply (Max)	55mA
Package / Case 6-SMD, No Lead Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm) Height - Seated (Max) 0.079" (2.00mm)	Ratings	-
Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm) Height - Seated (Max) 0.079" (2.00mm)	Mounting Type	Surface Mount
Height - Seated (Max) 0.079" (2.00mm)	Package / Case	6-SMD, No Lead
•	Size / Dimension	0.276" L x 0.197" W (7.00mm x 5.00mm)
Report errors?	Height - Seated (Max)	0.079" (2.00mm)
		Report errors?

377NB3C2000T Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

377NB3C2000T Payment Methods



















377NB3C2000T Shipping Methods













If you have any question about 377NB3C2000T, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com