



380LQ272M100J452 Information

Heisener.com

380LQ272M100J452 Part Number

Manufacturer Cornell Dubilier Electronics (CDE)

Category Capacitors

Aluminum Electrolytic Capacitors

CAP ALUM 2700UF 20% 100V SNAP **Description**

Package Radial, Can - Snap-In

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









380LQ272M100J452 Specifications

Manufacturer Part Number 380LQ272M100J452 Manufacturer Cornell Dubilier Electronics (CDE) Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can - Snap-In Series 380LQ Capacitance 2700μF Tolerance ±20% Voltage - Rated 100V ESR (Equivalent Series Resistance) 123 mOhm @ 120Hz Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature 40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 3.66A @ 120Hz Ripple Current - High Frequency 4.21A @ 20kHz Impedance - Lead Spacing 0.394" (10.00mm) Size / Dimension 0.984" Dia (25.00mm) Height - Seated (Max) 1.850" (47.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Report errors?		
Category Capacitors Package Radial, Can - Snap-In Series 380LQ Capacitance 2700μF Tolerance ±20% Voltage - Rated 100V ESR (Equivalent Series Resistance) 123 mOhm @ 120Hz Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 3.66A @ 120Hz Ripple Current - High Frequency 4.21A @ 20kHz Impedance - Lead Spacing 0.394" (10.00mm) Size / Dimension 0.984" Dia (25.00mm) Height - Seated (Max) 1.850" (47.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Manufacturer Part Number	380LQ272M100J452
Package Radial, Can - Snap-In Series 380LQ Capacitance 2700μF Tolerance ±20% Voltage - Rated 100V ESR (Equivalent Series Resistance) 123 mOhm @ 120Hz Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 3.66A @ 120Hz Ripple Current - High Frequency 4.21A @ 20kHz Impedance - Lead Spacing 0.394" (10.00mm) Size / Dimension 0.984" Dia (25.00mm) Height - Seated (Max) 1.850" (47.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Manufacturer	Cornell Dubilier Electronics (CDE)
Package Radial, Can - Snap-In Series 380LQ Capacitance 2700μF Tolerance ±20% Voltage - Rated 100V ESR (Equivalent Series Resistance) 123 mOhm @ 120Hz Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 3.66A @ 120Hz Ripple Current - High Frequency 4.21A @ 20kHz Impedance - Lead Spacing 0.394" (10.00mm) Size / Dimension 0.984" Dia (25.00mm) Height - Seated (Max) 1.850" (47.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Category	Capacitors
Series 380LQ Capacitance 2700µF Tolerance ±20% Voltage - Rated 100V ESR (Equivalent Series Resistance) 123 mOhm @ 120Hz Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 3.66A @ 120Hz Ripple Current - High Frequency 4.21A @ 20kHz Impedance - Lead Spacing 0.394" (10.00mm) Size / Dimension 0.984" Dia (25.00mm) Height - Seated (Max) 1.850" (47.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In		Aluminum Electrolytic Capacitors
Capacitance 2700μF Tolerance ±20% Voltage - Rated 100V ESR (Equivalent Series Resistance) 123 mOhm @ 120Hz Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 3.66A @ 120Hz Ripple Current - High Frequency 4.21A @ 20kHz Impedance - Lead Spacing 0.394" (10.00mm) Size / Dimension 0.984" Dia (25.00mm) Height - Seated (Max) 1.850" (47.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Package	Radial, Can - Snap-In
Tolerance ±20% Voltage - Rated 100V ESR (Equivalent Series Resistance) 123 mOhm @ 120Hz Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 3.66A @ 120Hz Ripple Current - High Frequency 4.21A @ 20kHz Impedance - Lead Spacing 0.394" (10.00mm) Size / Dimension 0.984" Dia (25.00mm) Height - Seated (Max) 1.850" (47.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Series	380LQ
Voltage - Rated100VESR (Equivalent Series Resistance)123 mOhm @ 120HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency3.66A @ 120HzRipple Current - High Frequency4.21A @ 20kHzImpedance-Lead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Capacitance	2700μF
ESR (Equivalent Series Resistance) Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency 3.66A @ 120Hz Ripple Current - High Frequency 4.21A @ 20kHz Impedance - Lead Spacing 0.394" (10.00mm) Size / Dimension 0.984" Dia (25.00mm) Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Tolerance	±20%
Lifetime @ Temp. Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency 4.21A @ 20kHz Impedance Lead Spacing 0.394" (10.00mm) Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case 2000 Hrs @ 85°C -40°C ~ 80°C -40°C ~	Voltage - Rated	100V
Operating Temperature Polarization Polar Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Ripple Current - Low Frequency Ripple Cur	ESR (Equivalent Series Resistance)	123 mOhm @ 120Hz
Polarization Polar Applications General Purpose Ripple Current - Low Frequency 3.66A @ 120Hz Ripple Current - High Frequency 4.21A @ 20kHz Impedance - Lead Spacing 0.394" (10.00mm) Size / Dimension 0.984" Dia (25.00mm) Height - Seated (Max) 1.850" (47.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Lifetime @ Temp.	2000 Hrs @ 85°C
Applications Ripple Current - Low Frequency Ripple Current - High Frequency A.21A @ 20kHz Impedance Lead Spacing Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Package / Case General Purpose 3.66A @ 120Hz 4.21A @ 20kHz 1.21A @ 20kHz	Operating Temperature	-40°C ∼ 85°C
Ripple Current - Low Frequency Ripple Current - High Frequency 4.21A @ 20kHz Impedance - Lead Spacing 0.394" (10.00mm) Size / Dimension 0.984" Dia (25.00mm) Height - Seated (Max) 1.850" (47.00mm) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Polarization	Polar
Ripple Current - High Frequency Impedance Lead Spacing O.394" (10.00mm) Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case 4.21A @ 20kHz	Applications	General Purpose
Impedance - Lead Spacing 0.394" (10.00mm) Size / Dimension 0.984" Dia (25.00mm) Height - Seated (Max) 1.850" (47.00mm) Surface Mount Land Size - Through Hole Package / Case Radial, Can - Snap-In	Ripple Current - Low Frequency	3.66A @ 120Hz
Lead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Ripple Current - High Frequency	4.21A @ 20kHz
Size / Dimension 0.984" Dia (25.00mm) Height - Seated (Max) 1.850" (47.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Impedance	-
Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Lead Spacing	0.394" (10.00mm)
Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Size / Dimension	0.984" Dia (25.00mm)
Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Height - Seated (Max)	1.850" (47.00mm)
Package / Case Radial, Can - Snap-In	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can - Snap-In
TE TO TO THE STATE OF THE STATE		Report errors?

380LQ272M100J452 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

380LQ272M100J452 Payment Methods



















380LQ272M100J452 Shipping Methods













If you have any question about 380LQ272M100J452, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com