



# 380LQ391M400A022 Information



For Reference Only

**Part Number** 380LQ391M400A022

Manufacturer Cornell Dubilier Electronics (CDE)

**Category** Capacitors

**Aluminum Electrolytic Capacitors** 

**Description** CAP ALUM 390UF 20% 400V SNAP

Package Radial, Can - Snap-In

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









### 380LQ391M400A022 Specifications

Manufacturer Part Number         380LQ391M400A022           Manufacturer         Cornell Dubilier Electronics (CDE)           Category         Capacitors           Aluminum Electrolytic Capacitors           Package         Radial, Can - Snap-In           Series         380LQ           Capacitance         390µF           Tolerance         ±20%           Voltage - Rated         400V           ESR (Equivalent Series Resistance)         510 mOhm @ 120Hz           Lifetime @ Temp.         2000 Hrs @ 85°C           Operating Temperature         -25°C ~ 85°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         2.13A @ 120Hz           Ripple Current - High Frequency         2.98A @ 20kHz           Impedance         -           Lead Spacing         0.394" (10.00mm)           Size / Dimension         1.378" Dia (35.00mm)           Height - Seated (Max)         1.260" (32.00mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can - Snap-In		
Category         Capacitors           Package         Radial, Can - Snap-In           Series         380LQ           Capacitance         390µF           Tolerance         ±20%           Voltage - Rated         400V           ESR (Equivalent Series Resistance)         510 mOhm @ 120Hz           Lifetime @ Temp.         2000 Hrs @ 85°C           Operating Temperature         -25°C ~ 85°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         2.13A @ 120Hz           Ripple Current - High Frequency         2.98A @ 20kHz           Impedance         -           Lead Spacing         0.394" (10.00mm)           Size / Dimension         1.378" Dia (35.00mm)           Height - Seated (Max)         1.260" (32.00mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can - Snap-In	Manufacturer Part Number	380LQ391M400A022
Package         Radial, Can - Snap-In           Series         380LQ           Capacitance         390µF           Tolerance         ±20%           Voltage - Rated         400V           ESR (Equivalent Series Resistance)         510 mOhm @ 120Hz           Lifetime @ Temp.         2000 Hrs @ 85°C           Operating Temperature         -25°C ~ 85°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         2.13A @ 120Hz           Ripple Current - High Frequency         2.98A @ 20kHz           Impedance         -           Lead Spacing         0.394" (10.00mm)           Size / Dimension         1.378" Dia (35.00mm)           Height - Seated (Max)         1.260" (32.00mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can - Snap-In	Manufacturer	Cornell Dubilier Electronics (CDE)
Package         Radial, Can - Snap-In           Series         380LQ           Capacitance         390μF           Tolerance         ±20%           Voltage - Rated         400V           ESR (Equivalent Series Resistance)         510 mOhm @ 120Hz           Lifetime @ Temp.         2000 Hrs @ 85°C           Operating Temperature         -25°C ~ 85°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         2.13A @ 120Hz           Ripple Current - High Frequency         2.98A @ 20kHz           Impedance         -           Lead Spacing         0.394" (10.00mm)           Size / Dimension         1.378" Dia (35.00mm)           Height - Seated (Max)         1.260" (32.00mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can - Snap-In	Category	Capacitors
Series         380LQ           Capacitance         390μF           Tolerance         ±20%           Voltage - Rated         400V           ESR (Equivalent Series Resistance)         510 mOhm @ 120Hz           Lifetime @ Temp.         2000 Hrs @ 85°C           Operating Temperature         -25°C ~ 85°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         2.13A @ 120Hz           Ripple Current - High Frequency         2.98A @ 20kHz           Impedance         -           Lead Spacing         0.394" (10.00mm)           Size / Dimension         1.378" Dia (35.00mm)           Height - Seated (Max)         1.260" (32.00mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can - Snap-In		Aluminum Electrolytic Capacitors
Capacitance       390µF         Tolerance       ±20%         Voltage - Rated       400V         ESR (Equivalent Series Resistance)       510 mOhm @ 120Hz         Lifetime @ Temp.       2000 Hrs @ 85°C         Operating Temperature       -25°C ~ 85°C         Polarization       Polar         Applications       General Purpose         Ripple Current - Low Frequency       2.13A @ 120Hz         Ripple Current - High Frequency       2.98A @ 20kHz         Impedance       -         Lead Spacing       0.394" (10.00mm)         Size / Dimension       1.378" Dia (35.00mm)         Height - Seated (Max)       1.260" (32.00mm)         Surface Mount Land Size       -         Mounting Type       Through Hole         Package / Case       Radial, Can - Snap-In	Package	Radial, Can - Snap-In
Tolerance ±20%  Voltage - Rated 400V  ESR (Equivalent Series Resistance) 510 mOhm @ 120Hz  Lifetime @ Temp. 2000 Hrs @ 85°C  Operating Temperature -25°C ~ 85°C  Polarization Polar  Applications General Purpose  Ripple Current - Low Frequency 2.13A @ 120Hz  Ripple Current - High Frequency 2.98A @ 20kHz  Impedance -  Lead Spacing 0.394" (10.00mm)  Size / Dimension 1.378" Dia (35.00mm)  Height - Seated (Max) 1.260" (32.00mm)  Surface Mount Land Size -  Mounting Type Through Hole  Package / Case Radial, Can - Snap-In	Series	380LQ
Voltage - Rated  ESR (Equivalent Series Resistance)  Lifetime @ Temp.  2000 Hrs @ 85°C  Operating Temperature  -25°C ~ 85°C  Polarization  Applications  General Purpose  Ripple Current - Low Frequency  Ripple Current - High Frequency  2.98A @ 20kHz  Impedance  Lead Spacing  0.394" (10.00mm)  Size / Dimension  Height - Seated (Max)  Surface Mount Land Size  Mounting Type  Through Hole  Package / Case  Faso C  2000 Hrs @ 85°C  600 Hrs @ 85°C  2000 Hrs @ 85°C  2010 Hrs @ 85°C  2020 Hrs @ 85°C  2020 Hrs @ 85°C  2020 Hrs @ 85°C  2021 Polar  2022 Polar  2023 Polar  2024 Polar  2024 Polar  2024 Polar  2025 Polar  2026 Polar  2026 Polar  2026 Polar  2027 Polar  2028	Capacitance	390μF
ESR (Equivalent Series Resistance)  Lifetime @ Temp.  2000 Hrs @ 85°C  Operating Temperature  -25°C ~ 85°C  Polarization  Applications  General Purpose  Ripple Current - Low Frequency  2.13A @ 120Hz  Ripple Current - High Frequency  2.98A @ 20kHz  Impedance  -  Lead Spacing  0.394" (10.00mm)  Size / Dimension  1.378" Dia (35.00mm)  Height - Seated (Max)  Surface Mount Land Size  Mounting Type  Through Hole  Package / Case  Radial, Can - Snap-In	Tolerance	±20%
Lifetime @ Temp.  Operating Temperature  -25°C ~ 85°C  Polarization  Polar  Applications  General Purpose  Ripple Current - Low Frequency  Ripple Current - High Frequency  2.98A @ 20kHz  Impedance  Lead Spacing  0.394" (10.00mm)  Size / Dimension  1.378" Dia (35.00mm)  Height - Seated (Max)  Surface Mount Land Size  Mounting Type  Through Hole  Package / Case  Radial, Can - Snap-In	Voltage - Rated	400V
Operating Temperature -25°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 2.13A @ 120Hz Ripple Current - High Frequency 2.98A @ 20kHz Impedance - Lead Spacing 0.394" (10.00mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 1.260" (32.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	ESR (Equivalent Series Resistance)	510 mOhm @ 120Hz
Polarization Polar  Applications General Purpose  Ripple Current - Low Frequency 2.13A @ 120Hz  Ripple Current - High Frequency 2.98A @ 20kHz  Impedance -  Lead Spacing 0.394" (10.00mm)  Size / Dimension 1.378" Dia (35.00mm)  Height - Seated (Max) 1.260" (32.00mm)  Surface Mount Land Size -  Mounting Type Through Hole  Package / Case Radial, Can - Snap-In	Lifetime @ Temp.	2000 Hrs @ 85°C
Applications  Ripple Current - Low Frequency  Ripple Current - High Frequency  Ripple Current - High Frequency  2.98A @ 20kHz  Impedance  Lead Spacing  0.394" (10.00mm)  Size / Dimension  1.378" Dia (35.00mm)  Height - Seated (Max)  1.260" (32.00mm)  Surface Mount Land Size  Mounting Type  Through Hole  Package / Case  Radial, Can - Snap-In	Operating Temperature	-25°C ~ 85°C
Ripple Current - Low Frequency  Ripple Current - High Frequency  2.98A @ 20kHz  Impedance  - Lead Spacing  0.394" (10.00mm)  Size / Dimension  1.378" Dia (35.00mm)  Height - Seated (Max)  1.260" (32.00mm)  Surface Mount Land Size  Mounting Type  Through Hole  Package / Case  Radial, Can - Snap-In	Polarization	Polar
Ripple Current - High Frequency  Impedance  Lead Spacing  0.394" (10.00mm)  Size / Dimension  1.378" Dia (35.00mm)  Height - Seated (Max)  1.260" (32.00mm)  Surface Mount Land Size  Mounting Type  Through Hole  Package / Case  Radial, Can - Snap-In	Applications	General Purpose
Impedance - Lead Spacing 0.394" (10.00mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 1.260" (32.00mm) Surface Mount Land Size - Through Hole Package / Case Radial, Can - Snap-In	Ripple Current - Low Frequency	2.13A @ 120Hz
Lead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Ripple Current - High Frequency	2.98A @ 20kHz
Size / Dimension 1.378" Dia (35.00mm)  Height - Seated (Max) 1.260" (32.00mm)  Surface Mount Land Size -  Mounting Type Through Hole  Package / Case Radial, Can - Snap-In	Impedance	-
Height - Seated (Max)  Surface Mount Land Size  Mounting Type  Through Hole  Package / Case  Radial, Can - Snap-In	Lead Spacing	0.394" (10.00mm)
Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Size / Dimension	1.378" Dia (35.00mm)
Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Height - Seated (Max)	1.260" (32.00mm)
Package / Case Radial, Can - Snap-In	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can - Snap-In
		Report errors?

### 380LQ391M400A022 Guarantees



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### 380LQ391M400A022 Payment Methods



















## 380LQ391M400A022 Shipping Methods













If you have any question about 380LQ391M400A022, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com