



380LQ471M450A042 Information



For Reference Only

Part Number 380LQ471M450A042

Manufacturer Cornell Dubilier Electronics (CDE)

Category Capacitors

Aluminum Electrolytic Capacitors

Description CAP ALUM 470UF 20% 450V SNAP

Package Radial, Can - Snap-In

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









380LQ471M450A042 Specifications

Manufacturer Part Number 380LQ471M450A042 Manufacturer Cornell Dubilier Electronics (CDE) Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can - Snap-In Series 380LQ Capacitance 470µF Tolerance ±20% Voltage - Rated 450V ESR (Equivalent Series Resistance) 423 mOhm @ 120Hz Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -25°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 2.53A @ 120Hz Ripple Current - High Frequency 3.54A @ 20kHz Impedance - Lead Spacing 0.394" (10.00mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 1.654" (42.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In		
Category Capacitors Package Radial, Can - Snap-In Series 380LQ Capacitance 470µF Tolerance ±20% Voltage - Rated 450 V ESR (Equivalent Series Resistance) 423 mOhm @ 120Hz Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -25°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 2.53A @ 120Hz Ripple Current - High Frequency 3.54A @ 20kHz Impedance - Lead Spacing 0.394" (10.00mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 1.654" (42.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Manufacturer Part Number	380LQ471M450A042
Package Radial, Can - Snap-In Series 380LQ Capacitance 470µF Tolerance ±20% Voltage - Rated 450V ESR (Equivalent Series Resistance) 423 mOhm @ 120Hz Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -25°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 2.53A @ 120Hz Ripple Current - High Frequency 3.54A @ 20kHz Impedance - Lead Spacing 0.394" (10.00mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 1.654" (42.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Manufacturer	Cornell Dubilier Electronics (CDE)
Package Radial, Can - Snap-In Series 380LQ Capacitance 470μF Tolerance ±20% Voltage - Rated 450V ESR (Equivalent Series Resistance) 423 mOhm @ 120Hz Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -25°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 2.53A @ 120Hz Ripple Current - High Frequency 3.54A @ 20kHz Impedance - Lead Spacing 0.394" (10.00mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 1.654" (42.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Category	Capacitors
Series 380LQ Capacitance 470μF Tolerance ±20% Voltage - Rated 450V ESR (Equivalent Series Resistance) 423 mOhm @ 120Hz Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -25°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 2.53A @ 120Hz Ripple Current - High Frequency 3.54A @ 20kHz Impedance - Lead Spacing 0.394" (10.00mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 1.654" (42.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In		Aluminum Electrolytic Capacitors
Capacitance 470µF Tolerance ±20% Voltage - Rated 450V ESR (Equivalent Series Resistance) 423 mOhm @ 120Hz Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -25°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 2.53A @ 120Hz Ripple Current - High Frequency 3.54A @ 20kHz Impedance - Lead Spacing 0.394" (10.00mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 1.654" (42.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Package	Radial, Can - Snap-In
Tolerance ±20% Voltage - Rated 450V ESR (Equivalent Series Resistance) 423 mOhm @ 120Hz Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -25°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 2.53A @ 120Hz Ripple Current - High Frequency 3.54A @ 20kHz Impedance - Lead Spacing 0.394" (10.00mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 1.654" (42.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Series	380LQ
Voltage - Rated ESR (Equivalent Series Resistance) Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -25°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency 3.54A @ 20kHz Impedance - Lead Spacing 0.394" (10.00mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case 423 mOhm @ 120Hz 424 mohm @ 120Hz 425 mohm @ 120Hz 425 mohm @ 120Hz 425 mohm @ 120Hz 426 mohm @ 120Hz 427 mohm @ 120Hz 427 mohm @ 120Hz 427 mohm @ 120Hz 428 mohm @ 120Hz 429 mohm @ 120Hz 420 mohm @ 120 mohm @ 120Hz 420 mohm @ 120 mohm @ 1	Capacitance	470μF
ESR (Equivalent Series Resistance) Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -25°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency 2.53A @ 120Hz Ripple Current - High Frequency 3.54A @ 20kHz Impedance - Lead Spacing 0.394" (10.00mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Tolerance	±20%
Lifetime @ Temp. Operating Temperature -25°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency 3.54A @ 20kHz Impedance Lead Spacing Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Package / Case 2000 Hrs @ 85°C -25°C ~ 85°C General Purpose General Purpose 1.378 @ 120Hz 3.54A @ 20kHz 1.378" Dia (35.00mm) 1.378" Dia (35.00mm) Through Hole Radial, Can - Snap-In	Voltage - Rated	450V
Operating Temperature -25°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 2.53A @ 120Hz Ripple Current - High Frequency 3.54A @ 20kHz Impedance - Lead Spacing 0.394" (10.00mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 1.654" (42.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	ESR (Equivalent Series Resistance)	423 mOhm @ 120Hz
Polarization Polar Applications General Purpose Ripple Current - Low Frequency 2.53A @ 120Hz Ripple Current - High Frequency 3.54A @ 20kHz Impedance - Lead Spacing 0.394" (10.00mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 1.654" (42.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Lifetime @ Temp.	2000 Hrs @ 85°C
Applications General Purpose Ripple Current - Low Frequency 2.53A @ 120Hz Ripple Current - High Frequency 3.54A @ 20kHz Impedance - Lead Spacing 0.394" (10.00mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 1.654" (42.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Operating Temperature	-25°C ~ 85°C
Ripple Current - Low Frequency Ripple Current - High Frequency 3.54A @ 20kHz Impedance - Lead Spacing 0.394" (10.00mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 1.654" (42.00mm) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Polarization	Polar
Ripple Current - High Frequency Impedance Lead Spacing 0.394" (10.00mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 1.654" (42.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Applications	General Purpose
Impedance-Lead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.654" (42.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Ripple Current - Low Frequency	2.53A @ 120Hz
Lead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.654" (42.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Ripple Current - High Frequency	3.54A @ 20kHz
Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 1.654" (42.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Impedance	-
Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Lead Spacing	0.394" (10.00mm)
Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Size / Dimension	1.378" Dia (35.00mm)
Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Height - Seated (Max)	1.654" (42.00mm)
Package / Case Radial, Can - Snap-In	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can - Snap-In
		Report errors?

380LQ471M450A042 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

380LQ471M450A042 Payment Methods





















380LQ471M450A042 Shipping Methods













If you have any question about 380LQ471M450A042, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com