

380LX122M160J052

380LX122M160J052 Information



Part Number	380LX122M160J052
Manufacturer	Cornell Dubilier Electronics (CDE)
Category	Capacitors Aluminum Electrolytic Capacitors
Description	CAP ALUM 1200UF 20% 160V SNAP
Package	Radial, Can - Snap-In
	For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

For Reference Only

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



380LX122M160J052 Specifications

Manufacturer Part Number380LX122M160J052ManufacturerCornell Dubilier Electronics (CDE)CategoryCapacitorsCategoryAluminum Electrolytic CapacitorsPackageRadial, Can - Snap-InPackage380LXCapacitance1200µFTolerance±20%Voltage - Rated160VESR (Equivalent Series Resistance)210 mOhmLifetime @ Temp.3000 Hrs @ 85°COperating Temperature+40°C ~ 85°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - High Frequency-Limende men-Limende men-Ripple Current - High Frequency-Limende men-Limende men-Capacitance-Capacitance-Manué Marcel Marce
CategoryCapacitorsCategoryAluminum Electrolytic CapacitorsPackageRadial, Can - Snap-InPackage380LXCapacitance1200µFTolerance±20%Voltage - Rated160VESR (Equivalent Series Resistance)210 mOhmLifetime @ Temp.3000 Hrs @ 85°COperating Temperature+40°C ~ 85°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - Low Frequency3.25A @ 120HzRipple Current - High Frequency-
Aluminum Electrolytic CapacitorsPackageAdial, Can - Snap-InSeries380LXCapacitance1200µFTolerance±20%Voltage - Rated160VESR (Equivalent Series Resistance)210 mOhmLifetime @ Temp.3000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationFolarApplicationsGeneral PurposeRipple Current - Low Frequency3.25A @ 120HzRipple Current - High Frequency-
PackageRadial, Can - Snap-InSeries380LXCapacitance1200µFTolerance±20%Voltage - Rated160VESR (Equivalent Series Resistance)210 mOhmLifetime @ Temp.3000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationFolarApplicationsGeneral PurposeRipple Current - Low Frequency3.25A @ 120HzRipple Current - High Frequency-
Series380LXCapacitance1200µFTolerance±20%Voltage - Rated160VESR (Equivalent Series Resistance)210 mOhmLifetime @ Temp.3000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - Low Frequency.Ripple Current - High Frequency-
Capacitance1200μFTolerance±20%Voltage - Rated160VESR (Equivalent Series Resistance)210 mOhmLifetime @ Temp.3000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency3.25A @ 120HzRipple Current - High Frequency-
Tolerance±20%Voltage - Rated160VESR (Equivalent Series Resistance)210 mOhmLifetime @ Temp.3000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency3.25A @ 120HzRipple Current - High Frequency-
Voltage - Rated160VESR (Equivalent Series Resistance)210 mOhmLifetime @ Temp.3000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency3.25A @ 120HzRipple Current - High Frequency-
ESR (Equivalent Series Resistance)210 mOhmLifetime @ Temp.3000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency3.25A @ 120HzRipple Current - High Frequency-
Lifetime @ Temp.3000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency3.25A @ 120HzRipple Current - High Frequency-
Operating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency3.25A @ 120HzRipple Current - High Frequency-
PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency3.25A @ 120HzRipple Current - High Frequency-
ApplicationsGeneral PurposeRipple Current - Low Frequency3.25A @ 120HzRipple Current - High Frequency-
Ripple Current - Low Frequency3.25A @ 120HzRipple Current - High Frequency-
Ripple Current - High Frequency -
Immediance
Impedance -
Lead Spacing 0.394" (10.00mm)
Size / Dimension 0.984" Dia (25.00mm)
Height - Seated (Max) 2.047" (52.00mm)
Surface Mount Land Size -
Mounting Type Through Hole
Package / Case Radial, Can - Snap-In
Report er

380LX122M160J052 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

380LX122M160J052 Payment Methods





If you have any question about 380LX122M160J052, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com