

# 381LX331M200H022

## 381LX331M200H022 Information

www.sener.com	Part Number	381LX331M200H022
	Manufacturer	Cornell Dubilier Electronics (CDE)
	Category	Capacitors Aluminum Electrolytic Capacitors
	Description	CAP ALUM 330UF 20% 200V SNAP
	Package	Radial, Can - Snap-In
		For the pricing/inventory/lead time, please contact
For Reference Only		us Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

For Reference Only

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



# 381LX331M200H022 Specifications

Manufacturer Part Number811.X331M200H022ManufacturerCornell Dubilier Electronics (CDE)CategoryCapacitorsPackageAluminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeries30µFCopacitance30µFTolerance200VVoltage - Rated200VESR (Equivalent Series Resistance)-Operating Temperature9000 Hrs © 105°COperating Temperature90arApplicationsCanceral PurposeRipple Current - High Frequency1.2A @ 120HzImpedance-Lead Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Munting Type1.2A @ 13.00mn)Package / CaseMunting TypePackage / CaseSatial, Can - Snap-In		
CategoryCapacitorsAluninum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeries381LXCapacitance330µFTolerance±20%Voltage - Rated00VESR (Equivalent Series Resistance)0Derating Temperature3000 Hrs @ 105°CPolarization6000 Hrs @ 105°CPolarization6000 Hrs @ 105°CApplications6000 Hrs @ 105°CRipple Current - Low Frequency1.2A @ 120HzRipple Current - High Frequency0.304" (1.00mm)Mindenge0.304" (1.00mm)Size / Dimension0.866" Dia (22.00mm)Hight - Seated (Max)1.2G" (32.00mm)Mounting TypeThrough Hole	Manufacturer Part Number	381LX331M200H022
Aluminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeries381LXCapacitance330µFTolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)-Lifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationGeneral PurposeRipple Current - Low Frequency1.2A @ 120HzRipple Current - High Frequency.3994" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Size / Dimension1.260" (32.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	Manufacturer	Cornell Dubilier Electronics (CDE)
PackageRadial, Can - Snap-InSeries381LXCapacitance330µFTolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)-Lifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - High Frequency1.2A @ 120HzImpedance-Lead Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	Category	Capacitors
Series381LXCapacitance330µFTolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)-Lifetime @ Temp.3000 Hrs @ 105°COperating Temperature40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.2A @ 120HzImpedance-Lead Spacing0.394" (10.00mm)Size / Dimension0.366° Dia (22.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeThrough Hole		Aluminum Electrolytic Capacitors
Capacitance330μFTolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)-Lifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.2A @ 120HzImpedance-Lead Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	Package	Radial, Can - Snap-In
Tolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)-Lifetime @ Temp.3000 Hrs @ 105°COperating Temperature40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - High Frequency1.2A @ 120HzImpedance-Lead Spacing0.394" (10.00mm)Size / Dimension1.260" Size (Dumm)Height - Seated (Max)1.260" (32.00mm)Mounting TypeThrough Hole	Series	381LX
Voltage - Rated200VESR (Equivalent Series Resistance)-Lifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.2A @ 120HzImpedance-Lead Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	Capacitance	330µF
ESR (Equivalent Series Resistance)-Lifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.2A @ 120HzRipple Current - High Frequency0.394" (10.00mm)Impedance-Lead Spacing0.366° Dia (22.00mm)Size / Dimension1.260" (32.00mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeThrough Hole	Tolerance	±20%
Lifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.2A @ 120HzRipple Current - High Frequency1.7A @ 20kHzImpedance-Lead Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	Voltage - Rated	200V
Operating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.2A @ 120HzRipple Current - High Frequency1.7A @ 20kHzImpedance-Lead Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)1.2G0" (32.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	ESR (Equivalent Series Resistance)	-
PolarizationPolarPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.2A @ 120HzRipple Current - High Frequency1.7A @ 20kHzImpedance-Lead Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	Lifetime @ Temp.	3000 Hrs @ 105°C
ApplicationsGeneral PurposeRipple Current - Low Frequency1.2A @ 120HzRipple Current - High Frequency1.7A @ 20kHzImpedance-Lead Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	Operating Temperature	$-40^{\circ}C \sim 105^{\circ}C$
Ripple Current - Low Frequency1.2A @ 120HzRipple Current - High Frequency1.7A @ 20kHzImpedance-Lead Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	Polarization	Polar
Ripple Current - High Frequency1.7A @ 20kHzImpedance-Lead Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	Applications	General Purpose
Impedance-Lead Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	Ripple Current - Low Frequency	1.2A @ 120Hz
Lead Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	Ripple Current - High Frequency	1.7A @ 20kHz
Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	Impedance	-
Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	Lead Spacing	0.394" (10.00mm)
Surface Mount Land Size-Mounting TypeThrough Hole	Size / Dimension	0.866" Dia (22.00mm)
Mounting Type Through Hole	Height - Seated (Max)	1.260" (32.00mm)
	Surface Mount Land Size	-
Package / Case Radial, Can - Snap-In	Mounting Type	Through Hole
	Package / Case	Radial, Can - Snap-In
Report er		Report errors?

### 381LX331M200H022 Guarantees



**Quality Guarantees** 

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

#### 381LX331M200H022 Payment Methods



If you have any question about 381LX331M200H022, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com