



### 381LX472M080K052 Information



For Reference Only

**Part Number** 381LX472M080K052

Manufacturer Cornell Dubilier Electronics (CDE)

**Category** Capacitors

**Aluminum Electrolytic Capacitors** 

**Description** CAP ALUM 4700UF 20% 80V SNAP

Package Radial, Can - Snap-In

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# 381LX472M080K052 Specifications

ManufacturerCornell Dubilier Electronics (CDE)CategoryCapacitorsPackageRadial, Can - Snap-InSeries381LXCapacitance4700μFTolerance±20%Voltage - Rated80VESR (Equivalent Series Resistance)-Lifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency3.3A @ 120HzRipple Current - High Frequency3.8A @ 20kHzImpedance-Lead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	-	
Category         Capacitors           Aluminum Electrolytic Capacitors           Package         Radial, Can - Snap-In           Series         381LX           Capacitance         4700μF           Tolerance         ±20%           Voltage - Rated         80V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         3000 Hrs @ 105°C           Operating Temperature         -40°C ~ 105°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         3.3A @ 120Hz           Ripple Current - High Frequency         3.8A @ 20kHz           Impedance         -           Lead Spacing         0.394" (10.00mm)           Size / Dimension         1.181" Dia (30.00mm)           Height - Seated (Max)         2.047" (52.00mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can - Snap-In	Manufacturer Part Number	381LX472M080K052
Aluminum Electrolytic Capacitors	Manufacturer	Cornell Dubilier Electronics (CDE)
Package       Radial, Can - Snap-In         Series       381LX         Capacitance       4700μF         Tolerance       ±20%         Voltage - Rated       80V         ESR (Equivalent Series Resistance)       -         Lifetime @ Temp.       3000 Hrs @ 105°C         Operating Temperature       -40°C ~ 105°C         Polarization       Polar         Applications       General Purpose         Ripple Current - Low Frequency       3.3A @ 120Hz         Ripple Current - High Frequency       3.8A @ 20kHz         Impedance       -         Lead Spacing       0.394" (10.00mm)         Size / Dimension       1.181" Dia (30.00mm)         Height - Seated (Max)       2.047" (52.00mm)         Surface Mount Land Size       -         Mounting Type       Through Hole         Package / Case       Radial, Can - Snap-In	Category	Capacitors
Series       381LX         Capacitance       4700µF         Tolerance       ±20%         Voltage - Rated       80V         ESR (Equivalent Series Resistance)       -         Lifetime @ Temp.       3000 Hrs @ 105°C         Operating Temperature       -40°C ~ 105°C         Polarization       Polar         Applications       General Purpose         Ripple Current - Low Frequency       3.3A @ 120Hz         Ripple Current - High Frequency       3.8A @ 20kHz         Impedance       -         Lead Spacing       0.394" (10.00mm)         Size / Dimension       1.181" Dia (30.00mm)         Height - Seated (Max)       2.047" (52.00mm)         Surface Mount Land Size       -         Mounting Type       Through Hole         Package / Case       Radial, Can - Snap-In		Aluminum Electrolytic Capacitors
Capacitance       4700μF         Tolerance       ±20%         Voltage - Rated       80V         ESR (Equivalent Series Resistance)       -         Lifetime @ Temp.       3000 Hrs @ 105°C         Operating Temperature       -40°C ~ 105°C         Polarization       Polar         Applications       General Purpose         Ripple Current - Low Frequency       3.3A @ 120Hz         Ripple Current - High Frequency       3.8A @ 20kHz         Impedance       -         Lead Spacing       0.394" (10.00mm)         Size / Dimension       1.181" Dia (30.00mm)         Height - Seated (Max)       2.047" (52.00mm)         Surface Mount Land Size       -         Mounting Type       Through Hole         Package / Case       Radial, Can - Snap-In	Package	Radial, Can - Snap-In
Tolerance ±20%  Voltage - Rated 80V  ESR (Equivalent Series Resistance) - Lifetime @ Temp. 3000 Hrs @ 105°C  Operating Temperature -40°C ~ 105°C  Polarization Polar  Applications General Purpose  Ripple Current - Low Frequency 3.3A @ 120Hz  Ripple Current - High Frequency 3.8A @ 20kHz  Impedance - Lead Spacing 0.394" (10.00mm)  Size / Dimension 1.181" Dia (30.00mm)  Height - Seated (Max) 2.047" (52.00mm)  Surface Mount Land Size -  Mounting Type Through Hole  Package / Case Radial, Can - Snap-In	Series	381LX
Voltage - Rated  ESR (Equivalent Series Resistance)  Lifetime @ Temp.  Operating Temperature  -40°C ~ 105°C  Polarization  Applications  General Purpose  Ripple Current - Low Frequency  Ripple Current - High Frequency  Impedance  Lead Spacing  O.394" (10.00mm)  Size / Dimension  Height - Seated (Max)  Surface Mount Land Size  Mounting Type  Through Hole  Package / Case  R3000 Hrs @ 105°C  -40°C ~ 105°C  Polar  -40°C ~ 105°C  -40°C ~ 105°	Capacitance	4700μF
ESR (Equivalent Series Resistance)  Lifetime @ Temp.  3000 Hrs @ 105°C  -40°C ~ 105°C  Polarization  Polar  Applications  General Purpose  Ripple Current - Low Frequency  3.3A @ 120Hz  Ripple Current - High Frequency  3.8A @ 20kHz  Impedance  -  Lead Spacing  0.394" (10.00mm)  Size / Dimension  1.181" Dia (30.00mm)  Height - Seated (Max)  2.047" (52.00mm)  Surface Mount Land Size  Mounting Type  Through Hole  Package / Case  Radial, Can - Snap-In	Tolerance	±20%
Lifetime @ Temp.  Operating Temperature  -40°C ~ 105°C  Polarization  Polar  Applications  General Purpose  Ripple Current - Low Frequency  3.3A @ 120Hz  Ripple Current - High Frequency  3.8A @ 20kHz  Impedance  -  Lead Spacing  0.394" (10.00mm)  Size / Dimension  1.181" Dia (30.00mm)  Height - Seated (Max)  Surface Mount Land Size  Mounting Type  Through Hole  Package / Case  Radial, Can - Snap-In	Voltage - Rated	80V
Operating Temperature  -40°C ~ 105°C  Polarization  Applications  General Purpose  Ripple Current - Low Frequency  3.3A @ 120Hz  Ripple Current - High Frequency  3.8A @ 20kHz  Impedance  Lead Spacing  0.394" (10.00mm)  Size / Dimension  1.181" Dia (30.00mm)  Height - Seated (Max)  2.047" (52.00mm)  Surface Mount Land Size  Mounting Type  Through Hole  Package / Case  Radial, Can - Snap-In	ESR (Equivalent Series Resistance)	-
Polarization Polar Applications General Purpose Ripple Current - Low Frequency 3.3A @ 120Hz Ripple Current - High Frequency 3.8A @ 20kHz Impedance - Lead Spacing 0.394" (10.00mm) Size / Dimension 1.181" Dia (30.00mm) Height - Seated (Max) 2.047" (52.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Lifetime @ Temp.	3000 Hrs @ 105°C
Applications General Purpose Ripple Current - Low Frequency 3.3A @ 120Hz Ripple Current - High Frequency 3.8A @ 20kHz Impedance - Lead Spacing 0.394" (10.00mm) Size / Dimension 1.181" Dia (30.00mm) Height - Seated (Max) 2.047" (52.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Operating Temperature	-40°C ~ 105°C
Ripple Current - Low Frequency  Ripple Current - High Frequency  3.8A @ 20kHz  Impedance  - Lead Spacing  0.394" (10.00mm)  Size / Dimension  1.181" Dia (30.00mm)  Height - Seated (Max)  2.047" (52.00mm)  Surface Mount Land Size  Mounting Type  Through Hole  Package / Case  Radial, Can - Snap-In	Polarization	Polar
Ripple Current - High Frequency  Impedance  Lead Spacing  O.394" (10.00mm)  Size / Dimension  1.181" Dia (30.00mm)  Height - Seated (Max)  Surface Mount Land Size  Mounting Type  Through Hole  Package / Case  Radial, Can - Snap-In	Applications	General Purpose
Impedance - Lead Spacing 0.394" (10.00mm) Size / Dimension 1.181" Dia (30.00mm) Height - Seated (Max) 2.047" (52.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Ripple Current - Low Frequency	3.3A @ 120Hz
Lead Spacing 0.394" (10.00mm) Size / Dimension 1.181" Dia (30.00mm) Height - Seated (Max) 2.047" (52.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Ripple Current - High Frequency	3.8A @ 20kHz
Size / Dimension 1.181" Dia (30.00mm)  Height - Seated (Max) 2.047" (52.00mm)  Surface Mount Land Size -  Mounting Type Through Hole  Package / Case Radial, Can - Snap-In	Impedance	-
Height - Seated (Max)  Surface Mount Land Size  Mounting Type  Through Hole  Package / Case  Radial, Can - Snap-In	Lead Spacing	0.394" (10.00mm)
Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Size / Dimension	1.181" Dia (30.00mm)
Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Height - Seated (Max)	2.047" (52.00mm)
Package / Case Radial, Can - Snap-In	Surface Mount Land Size	-
•	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can - Snap-In
		Report errors?

### **381LX472M080K052 Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## 381LX472M080K052 Payment Methods

































If you have any question about 381LX472M080K052, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com