



382LX104M016A082 Information



For Reference Only

Part Number 382LX104M016A082

Manufacturer Cornell Dubilier Electronics (CDE)

Category Capacitors

Aluminum Electrolytic Capacitors

Description CAP ALUM 100000UF 20% 16V SNAP

Package Radial, Can - Snap-In - 4 Lead

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









382LX104M016A082 Specifications

Manufacturer Part Number382LX104M016A082ManufacturerCornell Dubilier Electronics (CDE)CategoryCapacitorsPackageRadial, Can - Snap-In - 4 LeadSeries382LXCapacitance100000µFTolerance±20%Voltage - Rated16VESR (Equivalent Series Resistance)-Lifetime @ Temp.3000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Ripple Current - High Frequency-Impedance-Lead Spacing-Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)3.228" (82.00mm)Surface Mount Land Size-		
Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can - Snap-In - 4 Lead Series 382LX Capacitance 100000µF Tolerance ±20% Voltage - Rated ESR (Equivalent Series Resistance) Lifetime @ Temp. 3000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing - Size / Dimension Height - Seated (Max) Surface Mount Land Size Radial, Can - Snap-In - 4 Lead 382LX Radial, Can - Snap-In - 4 Lead 382LX Radial, Can - Snap-In - 4 Lead 382LX Redial, Can - Snap-In - 4 Lead 382LX Redial, Can - Snap-In - 4 Lead 382LX 640000µF ±20% For a So C 16V ESR (Equivalent Series Resistance) -40°C ~ 85°C Polar -40°C ~ 85°C -40°C	Manufacturer Part Number	382LX104M016A082
PackageRadial, Can - Snap-In - 4 LeadSeries382LXCapacitance100000μFTolerance±20%Voltage - Rated16VESR (Equivalent Series Resistance)-Lifetime @ Temp.3000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Ripple Current - High Frequency-Impedance-Lead Spacing-Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)3.228" (82.00mm)Surface Mount Land Size-	Manufacturer	Cornell Dubilier Electronics (CDE)
Package Radial, Can - Snap-In - 4 Lead Series 382LX Capacitance 100000μF Tolerance ±20% Voltage - Rated 16V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 3000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing - Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 3.228" (82.00mm) Surface Mount Land Size -	Category	Capacitors
Series 382LX Capacitance 100000µF Tolerance ±20% Voltage - Rated 16V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 3000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing - Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 3.228" (82.00mm) Surface Mount Land Size -		Aluminum Electrolytic Capacitors
Capacitance100000µFTolerance±20%Voltage - Rated16VESR (Equivalent Series Resistance)-Lifetime @ Temp.3000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Ripple Current - High Frequency-Impedance-Lead Spacing-Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)3.228" (82.00mm)Surface Mount Land Size-	Package	Radial, Can - Snap-In - 4 Lead
Tolerance ±20% Voltage - Rated 16V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 3000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing - Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 3.228" (82.00mm) Surface Mount Land Size -	Series	382LX
Voltage - Rated ESR (Equivalent Series Resistance) Lifetime @ Temp. Operating Temperature -40°C ~ 85°C Polarization Applications Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing Size / Dimension Height - Seated (Max) Surface Mount Land Size - 16V 6V 6V - 1300 Hrs @ 85°C -40°C ~ 85°C Polar -40°C ~ 85°C -40	Capacitance	100000μF
ESR (Equivalent Series Resistance) Lifetime @ Temp. 3000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing Size / Dimension Height - Seated (Max) Surface Mount Land Size -40°C ~ 85°C Polar General Purpose - - - - - - - - - 3000 Hrs @ 85°C -40°C ~ 85°C -40	Tolerance	±20%
Lifetime @ Temp. 3000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing - Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 3.228" (82.00mm) Surface Mount Land Size -	Voltage - Rated	16V
Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency Impedance Lead Spacing - Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) Surface Mount Land Size	ESR (Equivalent Series Resistance)	-
Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing - Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 3.228" (82.00mm) Surface Mount Land Size -	Lifetime @ Temp.	3000 Hrs @ 85°C
Applications Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing - Size / Dimension Height - Seated (Max) Surface Mount Land Size General Purpose - 1.378" Dia (35.00mm) 3.228" (82.00mm) - - - - - - - - - - - - -	Operating Temperature	-40°C ~ 85°C
Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing - Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 3.228" (82.00mm) Surface Mount Land Size -	Polarization	Polar
Ripple Current - High Frequency Impedance Lead Spacing - Size / Dimension Light - Seated (Max) Surface Mount Land Size	Applications	General Purpose
Impedance-Lead Spacing-Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)3.228" (82.00mm)Surface Mount Land Size-	Ripple Current - Low Frequency	-
Lead Spacing-Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)3.228" (82.00mm)Surface Mount Land Size-	Ripple Current - High Frequency	-
Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)3.228" (82.00mm)Surface Mount Land Size-	Impedance	-
Height - Seated (Max) Surface Mount Land Size 3.228" (82.00mm) -	Lead Spacing	-
Surface Mount Land Size -	Size / Dimension	1.378" Dia (35.00mm)
	Height - Seated (Max)	3.228" (82.00mm)
	Surface Mount Land Size	-
Mounting Type Through Hole	Mounting Type	Through Hole
Package / Case Radial, Can - Snap-In - 4 Lead	Package / Case	Radial, Can - Snap-In - 4 Lead
Report errors?		Report errors?

382LX104M016A082 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

382LX104M016A082 Payment Methods



















382LX104M016A082 Shipping Methods













If you have any question about 382LX104M016A082, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com