



### 382LX273M050A062 Information



For Reference Only

**Part Number** 382LX273M050A062

Manufacturer Cornell Dubilier Electronics (CDE)

**Category** Capacitors

**Aluminum Electrolytic Capacitors** 

**Description** CAP ALUM 27000UF 20% 50V SNAP

Package Radial, Can - Snap-In - 4 Lead

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## 382LX273M050A062 Specifications

Manufacturer Part Number         382LX273M050A062           Manufacturer         Cornell Dubilier Electronics (CDE)           Category         Capacitors           Package         Radial, Can - Snap- In - 4 Lead           Series         382LX           Capacitance         27000µF           Tolerance         ±20%           Voltage - Rated         50V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         3000 Hrs @ 85°C           Operating Temperature         40°C ~ 85°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         -           Ripple Current - High Frequency         -           Lead Spacing         1.378" Dia (35.00mm)           Size / Dimension         1.378" Dia (35.00mm)           Height - Seated (Max)         2.559" (65.00mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can - Snap-In - 4 Lead		
Category         Capacitors           Package         Radial, Can - Snap-In - 4 Lead           Series         382LX           Capacitance         27000µF           Tolerance         ±20%           Voltage - Rated         50V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         3000 Hrs @ 85°C           Operating Temperature         -40°C ~ 85°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         -           Ripple Current - High Frequency         -           Impedance         -           Lead Spacing         -           Size / Dimension         1.378" Dia (35.00mm)           Height - Seated (Max)         2.559" (65.00mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can - Snap-In - 4 Lead	Manufacturer Part Number	382LX273M050A062
PackageAluminum Electrolytic CapacitorsPackageRadial, Can - Snap-In - 4 LeadSeries382LXCapacitance27000μFTolerance±20%Voltage - Rated50VESR (Equivalent Series Resistance)-Lifetime @ Temp.3000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Ripple Current - High Frequency-Impedance-Lead Spacing-Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)2.559" (65.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 4 Lead	Manufacturer	Cornell Dubilier Electronics (CDE)
Package         Radial, Can - Snap-In - 4 Lead           Series         382LX           Capacitance         27000µF           Tolerance         ±20%           Voltage - Rated         50V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         3000 Hrs @ 85°C           Operating Temperature         -40°C ~ 85°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         -           Ripple Current - High Frequency         -           Impedance         -           Lead Spacing         -           Size / Dimension         1.378" Dia (35.00mm)           Height - Seated (Max)         2.559" (65.00mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can - Snap-In - 4 Lead	Category	Capacitors
Series         382LX           Capacitance         27000µF           Tolerance         ±20%           Voltage - Rated         50V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         3000 Hrs @ 85°C           Operating Temperature         -40°C ~ 85°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         -           Ripple Current - High Frequency         -           Impedance         -           Lead Spacing         -           Size / Dimension         1.378" Dia (35.00mm)           Height - Seated (Max)         2.559" (65.00mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can - Snap-In - 4 Lead		Aluminum Electrolytic Capacitors
Capacitance         27000µF           Tolerance         ±20%           Voltage - Rated         50V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         3000 Hrs @ 85°C           Operating Temperature         -40°C ~ 85°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         -           Ripple Current - High Frequency         -           Impedance         -           Lead Spacing         -           Size / Dimension         1.378" Dia (35.00mm)           Height - Seated (Max)         2.559" (65.00mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can - Snap-In - 4 Lead	Package	Radial, Can - Snap-In - 4 Lead
Tolerance±20%Voltage - Rated50VESR (Equivalent Series Resistance)-Lifetime @ Temp.3000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Ripple Current - High Frequency-Impedance-Lead Spacing-Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)2.559" (65.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 4 Lead	Series	382LX
Voltage - Rated50VESR (Equivalent Series Resistance)-Lifetime @ Temp.3000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Ripple Current - High Frequency-Impedance-Lead Spacing-Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)2.559" (65.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 4 Lead	Capacitance	27000μF
ESR (Equivalent Series Resistance)  Lifetime @ Temp.  Operating Temperature  -40°C ~ 85°C  Polarization  Applications  General Purpose  Ripple Current - Low Frequency  -Ripple Current - High Frequency  Impedance  Lead Spacing  Size / Dimension  Height - Seated (Max)  Surface Mount Land Size  Mounting Type  Package / Case  - A0°C ~ 85°C  General Purpose  -40°C ~ 85°C  -40°C ~ 85	Tolerance	±20%
Lifetime @ Temp.3000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Ripple Current - High Frequency-Impedance-Lead Spacing-Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)2.559" (65.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 4 Lead	Voltage - Rated	50V
Operating Temperature -40°C ~ 85°C  Polarization Polar  Applications General Purpose  Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing - Size / Dimension 1.378" Dia (35.00mm)  Height - Seated (Max) 2.559" (65.00mm)  Surface Mount Land Size - Mounting Type Through Hole  Package / Case Radial, Can - Snap-In - 4 Lead	ESR (Equivalent Series Resistance)	-
Polarization Polar  Applications General Purpose  Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing - Size / Dimension 1.378" Dia (35.00mm)  Height - Seated (Max) 2.559" (65.00mm)  Surface Mount Land Size - Mounting Type Through Hole  Package / Case Radial, Can - Snap-In - 4 Lead	Lifetime @ Temp.	3000 Hrs @ 85°C
Applications  Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing - Size / Dimension - Height - Seated (Max) Surface Mount Land Size - Mounting Type Package / Case  General Purpose -  1.378" Dia (35.00mm) - 2.559" (65.00mm) - Through Hole Radial, Can - Snap-In - 4 Lead	Operating Temperature	-40°C ~ 85°C
Ripple Current - Low Frequency	Polarization	Polar
Ripple Current - High Frequency Impedance - Lead Spacing - Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 2.559" (65.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 4 Lead	Applications	General Purpose
Impedance-Lead Spacing-Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)2.559" (65.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 4 Lead	Ripple Current - Low Frequency	-
Lead Spacing - Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 2.559" (65.00mm) Surface Mount Land Size - Through Hole Package / Case Radial, Can - Snap-In - 4 Lead	Ripple Current - High Frequency	-
Size / Dimension 1.378" Dia (35.00mm)  Height - Seated (Max) 2.559" (65.00mm)  Surface Mount Land Size -  Mounting Type Through Hole  Package / Case Radial, Can - Snap-In - 4 Lead	Impedance	-
Height - Seated (Max)  Surface Mount Land Size  Mounting Type  Through Hole  Package / Case  Radial, Can - Snap-In - 4 Lead	Lead Spacing	-
Surface Mount Land Size -  Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 4 Lead	Size / Dimension	1.378" Dia (35.00mm)
Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 4 Lead	Height - Seated (Max)	2.559" (65.00mm)
Package / Case Radial, Can - Snap-In - 4 Lead	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can - Snap-In - 4 Lead
		Report errors?

#### **382LX273M050A062 Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### 382LX273M050A062 Payment Methods



















## 382LX273M050A062 Shipping Methods













If you have any question about 382LX273M050A062, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com