



#### 382LX472M250B082V Information



For Reference Only

382LX472M250B082V Manufacturer Cornell Dubilier Electronics (CDE)

Category Capacitors

Part Number

**Aluminum Electrolytic Capacitors** 

**Description** CAP ALUM 4700UF 20% 250V SNAP

Radial, Can - Snap-In - 5 Lead **Package** 

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## 382LX472M250B082V Specifications

Manufacturer Part Number382LX472M250B082VManufacturerCornell Dubilier Electronics (CDE)CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, Can - Snap-In - 5 LeadSeries382LXCapacitance4700μFTolerance±20%Voltage - Rated250VESR (Equivalent Series Resistance)-Lifetime @ Temp.3000 Hrs @ 85°C
Category  Capacitors  Aluminum Electrolytic Capacitors  Package  Radial, Can - Snap-In - 5 Lead  Series  382LX  Capacitance  4700µF  Tolerance  ±20%  Voltage - Rated  250V  ESR (Equivalent Series Resistance)  -
Aluminum Electrolytic CapacitorsPackageRadial, Can - Snap-In - 5 LeadSeries382LXCapacitance4700μFTolerance±20%Voltage - Rated250VESR (Equivalent Series Resistance)-
PackageRadial, Can - Snap-In - 5 LeadSeries382LXCapacitance4700μFTolerance±20%Voltage - Rated250VESR (Equivalent Series Resistance)-
Series $382LX$ Capacitance $4700\mu F$ Tolerance $\pm 20\%$ Voltage - Rated $250V$ ESR (Equivalent Series Resistance)-
Capacitance $4700 \mu F$ Tolerance $\pm 20 \%$ Voltage - Rated $250 V$ ESR (Equivalent Series Resistance)-
Tolerance $\pm 20\%$ Voltage - Rated $250V$ ESR (Equivalent Series Resistance) -
Voltage - Rated 250V ESR (Equivalent Series Resistance) -
ESR (Equivalent Series Resistance) -
Lifetime @ Temp. 3000 Hrs @ 85°C
Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$
Polarization Polar
Applications General Purpose
Ripple Current - Low Frequency 9.65A @ 120Hz
Ripple Current - High Frequency 13.51A @ 20kHz
Impedance -
Lead Spacing -
Size / Dimension 1.969" Dia (50.00mm)
Height - Seated (Max) 3.228" (82.00mm)
Surface Mount Land Size -
Mounting Type Through Hole
Package / Case Radial, Can - Snap-In - 5 Lead
Report errors

#### 382LX472M250B082V Guarantees



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### 382LX472M250B082V Payment Methods



















### 382LX472M250B082V Shipping Methods













If you have any question about 382LX472M250B082V, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com