



39018R2C8.25 Information

Mai Cate Heisener.com

Part Number39018R2C8.25ManufacturerLittelfuse Inc.CategoryCircuit Protection

Electrical, Specialty Fuses

Description FUSE CARTRIDGE 390A 8.25KVAC

Package Cartridge, Non-Standard

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









39018R2C8.25 Specifications

Manufacturer Part Number 39018R2C8.25 Manufacturer Littelfuse Inc. Category Circuit Protection Electrical, Specialty Fuses Package Cartridge, Non-Standard Series POWR-GARD? Fuse Type Cartridge Current Rating 390A Voltage Rating - AC 8250V (8.25kV) Voltage Rating - DC - Response Time - Applications Motor Protection Features Indicating Class R Approvals - Operating Temperature - Breaking Capacity @ Rated Voltage 80kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 15.875" L x 3.000" W x 6.380" H (403.23mm x 76.20mm x 162.05mm)		
CategoryCircuit Protection Electrical, Specialty FusesPackageCartridge, Non-StandardSeriesPOWR-GARD?Fuse TypeCartridgeCurrent Rating390AVoltage Rating - AC8250V (8.25kV)Voltage Rating - DC-Response Time-ApplicationsMotor ProtectionFeaturesIndicatingClassRApprovals-Operating Temperature-Breaking Capacity @ Rated Voltage80kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension15.875" L x 3.000" W x 6.380" H (403.23mm x 76.20mm x 162.05mm)	Manufacturer Part Number	39018R2C8.25
PackageElectrical, Specialty FusesPackageCartridge, Non-StandardSeriesPOWR-GARD?Fuse TypeCartridgeCurrent Rating390AVoltage Rating - AC8250V (8.25kV)Voltage Rating - DC-Response Time-ApplicationsMotor ProtectionFeaturesIndicatingClassRApprovals-Operating Temperature-Breaking Capacity @ Rated Voltage80kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension15.875" L x 3.000" W x 6.380" H (403.23mm x 76.20mm x 162.05mm)	Manufacturer	Littelfuse Inc.
Package Cartridge, Non-Standard Series POWR-GARD? Fuse Type Cartridge Current Rating 390A Voltage Rating - AC 8250V (8.25kV) Voltage Rating - DC - Response Time - Applications Motor Protection Features Indicating Class R Approvals - Operating Temperature - Breaking Capacity @ Rated Voltage 80kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 15.875" L x 3.000" W x 6.380" H (403.23mm x 76.20mm x 162.05mm)	Category	Circuit Protection
SeriesPOWR-GARD?Fuse TypeCartridgeCurrent Rating390AVoltage Rating - AC8250V (8.25kV)Voltage Rating - DC-Response Time-ApplicationsMotor ProtectionFeaturesIndicatingClassRApprovals-Operating Temperature-Breaking Capacity @ Rated Voltage80kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension15.875" L x 3.000" W x 6.380" H (403.23mm x 76.20mm x 162.05mm)		Electrical, Specialty Fuses
Fuse TypeCartridgeCurrent Rating390AVoltage Rating - AC8250V (8.25kV)Voltage Rating - DC-Response Time-ApplicationsMotor ProtectionFeaturesIndicatingClassRApprovals-Operating Temperature-Breaking Capacity @ Rated Voltage80kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension15.875" L x 3.000" W x 6.380" H (403.23mm x 76.20mm x 162.05mm)	Package	Cartridge, Non-Standard
Current Rating 390A Voltage Rating - AC 8250V (8.25kV) Voltage Rating - DC - Response Time - Applications Motor Protection Features Indicating Class R Approvals - Operating Temperature - Breaking Capacity @ Rated Voltage 80kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 15.875" L x 3.000" W x 6.380" H (403.23mm x 76.20mm x 162.05mm)	Series	POWR-GARD?
Voltage Rating - AC Voltage Rating - DC Response Time Applications Motor Protection Features Indicating Class R Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 8250V (8.25kV) 8250V (8.25kV)	Fuse Type	Cartridge
Voltage Rating - DC Response Time - Applications Motor Protection Features Indicating Class R Approvals - Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension - Cass - Cass Cartridge, Non-Standard Size / Dimension - Size / Dimension - Cass - Cass Cass Cass Cass Cass Cass	Current Rating	390A
Response Time	Voltage Rating - AC	8250V (8.25kV)
Applications Motor Protection Features Indicating Class R Approvals - Operating Temperature - Breaking Capacity @ Rated Voltage 80kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 15.875" L x 3.000" W x 6.380" H (403.23mm x 76.20mm x 162.05mm)	Voltage Rating - DC	-
Features Indicating Class R Approvals - Operating Temperature - Breaking Capacity @ Rated Voltage 80kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 15.875" L x 3.000" W x 6.380" H (403.23mm x 76.20mm x 162.05mm)	Response Time	-
Class R Approvals - Operating Temperature - Breaking Capacity @ Rated Voltage 80kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 15.875" L x 3.000" W x 6.380" H (403.23mm x 76.20mm x 162.05mm)	Applications	Motor Protection
Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 15.875" L x 3.000" W x 6.380" H (403.23mm x 76.20mm x 162.05mm)	Features	Indicating
Operating Temperature Breaking Capacity @ Rated Voltage 80kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 15.875" L x 3.000" W x 6.380" H (403.23mm x 76.20mm x 162.05mm)	Class	R
Breaking Capacity @ Rated Voltage 80kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 15.875" L x 3.000" W x 6.380" H (403.23mm x 76.20mm x 162.05mm)	Approvals	-
Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 15.875" L x 3.000" W x 6.380" H (403.23mm x 76.20mm x 162.05mm)	Operating Temperature	-
Package / Case Cartridge, Non-Standard Size / Dimension 15.875" L x 3.000" W x 6.380" H (403.23mm x 76.20mm x 162.05mm)	Breaking Capacity @ Rated Voltage	80kA
Size / Dimension 15.875" L x 3.000" W x 6.380" H (403.23mm x 76.20mm x 162.05mm)	Mounting Type	Holder
· · ·	Package / Case	Cartridge, Non-Standard
Report errors?	Size / Dimension	15.875" L x 3.000" W x 6.380" H (403.23mm x 76.20mm x 162.05mm)
		Report errors?

39018R2C8.25 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

39018R2C8.25 Payment Methods



















39018R2C8.25 Shipping Methods













If you have any question about 39018R2C8.25, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com