

395-012-541-204

395-012-541-204 Information



Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



395-012-541-204 Specifications

ManufacturerEDAC Inc.Cardecors, InterconnectsCard Edge Connectors - Edgeboard ConnectorsPackage-Series395Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row6Number of Positions/Bay/Row12Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleContact MaterialCoppen, Nickel, Tin AlloyContact Finish Thickness-Contact Finish Thickness-Contact TypeIndeContact Type-Contact Specifies-Contact Type-Contact Finish Thickness-Contact Type-Fauge FeatureBlackFunge Feature-Operating Temperature-CorborSince - 105°C	-		
CategoryConnectors, InterconnectsCard Edge Connectors - Edgeboard ConnectorsPackage-Series395Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row6Number of Positions/Bay/Row062° (1.57mm)Card Thickness0.062° (1.57mm)Number of Rows2Pitch0.100° (2.54mm)Features-Mounting TypeThrough HoleContact MaterialCoper, Nickel, Tin AlloyContact Finish Thickness-Contact Finish Thickness-Contact Type-Contact TypeBackFauge FeatureFush Mount, Top Opening, Unthreaded, 0.156° (3.96mm) DiaOperating Temperature-65°C ~ 105°C	Manufacturer Part Number	395-012-541-204	
AndCard Edge Connectors - Edgeboard ConnectorsPackage-Series395Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row6Ouer of Positions/Bay/Row12Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleContact MaterialCooper, Nickel, Tin AlloyContact Finish Thickness-Contact Finish Thickness-Contact Type-Contact Type-Contact Type-Contact Type-Contact Type-Contact Type-Contact Type-Contact Type-Contact Type-Contact Type-ColorBlackFinage FeatureFush Mount, Top Opening, Unthreaded, 0.156" (3.96mm) DiaOperating Temperature-65°C ~ 105°C	Manufacturer	EDAC Inc.	
Package-Series395Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row6Number of Positions12Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleContact MaterialCopper, Nickel, Tin AlloyContact Finish Thickness-Contact Finish Thickness-Contact Type-Contact Type-Contact Type-Contact Type-ColorBlackFinage Feature-65°C ~ 105°C	Category	Connectors, Interconnects	
Series395Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row6Number of Positions/Bay/Row12Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleContact Finish ThicknessGoldContact Finish Thickness-Contact Finish Thickness-Contact Type-Contact Type-Contact Type-Seature-Contact Type-Contact Type-Contact Type-Seature-ColorBlackFange Feature-Operating Temperature-5°C ~ 105°C		Card Edge Connectors - Edgeboard Connectors	
Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row6Number of Positions12Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleContact MaterialCoper, Nickel, Tin AlloyContact FinishGoldContact Finish Thickness-Contact TypeBackFlange FeatureFush Mount, Top Opening, Unthreaded, 0.156" (3.96mm) DiaOperating Temperature-65°C ~ 105°C	Package	-	
GenderFemaleNumber of Positions/Bay/Row6Number of Positions12Card Thickness0.062° (1.57 mm)Number of Rows2Pitch0.100° (2.54 mm)Features-Mounting TypeMirough HoleContact MaterialCoper, Nickel, Tin AlloyContact FinishGoldContact Finish Thickness-Contact Finish Thickness-Contact Finish ThicknessBackColorBackFinage FeatureFush Mount, Top Opening, Unthreaded, 0.156° (3.96 mm) DiaOpenting Temperature-Contact String Temperature-Contact Stri	Series	395	
Number of Positions/Bay/Row6Number of Positions12Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting Type0.100" (2.54mm)TerminationWire WrapContact MaterialCopper, Nickel, Tin AlloyContact Finish Thickness-Contact Finish Thickness-Contact Spee-ColorBlackFlange FeatureFlush Mount, Top Opening, Unthreaded, 0.156" (3.96mm) DiaOperating Temperature-65°C ~ 105°C	Card Type	Non Specified - Dual Edge	
Number of Positions 12 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.100" (2.54mm) Features - Mounting Type Through Hole Contact Material Copper, Nickel, Tin Alloy Contact Finish Gold Contact Finish Thickness - Contact Type - Color Black Flange Feature Flush Mount, Top Opening, Unthreaded, 0.156" (3.96mm) Dia Operating Temperature -65°C ~ 105°C	Gender	Female	
Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting Type-TerminationWire WrapContact MaterialCopper, Nickel, Tin AlloyContact Finish Thickness-Contact Type-ColorBlackFlange Feature-Operating Temperature-6°C ~ 105°C	Number of Positions/Bay/Row	6	
Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationWire WrapContact MaterialCopper, Nickel, Tin AlloyContact FinishGoldContact Finish Thickness-Contact Type-ColorBlackFlange Feature-65°C ~ 105°C	Number of Positions	12	
Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationWire WrapContact MaterialCopper, Nickel, Tin AlloyContact Finish ThicknessGoldContact Finish Thickness-Contact Type-ColorBlackFlange FeatureFush Mount, Top Opening, Unthreaded, 0.156" (3.96mm) DiaOperating Temperature-65°C ~ 105°C	Card Thickness	0.062" (1.57mm)	
Features-Mounting TypeThrough HoleTerminationWire WrapContact MaterialCopper, Nickel, Tin AlloyContact FinishGoldContact Finish Thickness-Contact Type-ColorBlackFlange FeatureFlush Mount, Top Opening, Unthreaded, 0.156" (3.96mm) DiaOperating Temperature-65°C ~ 105°C	Number of Rows	2	
Mounting TypeThrough HoleTerminationWire WrapContact MaterialCopper, Nickel, Tin AlloyContact FinishGoldContact Finish Thickness-Contact Type-ColorBlackFlange FeatureFlush Mount, Top Opening, Unthreaded, 0.156" (3.96mm) DiaOperating Temperature-65°C ~ 105°C	Pitch	0.100" (2.54mm)	
TerminationWire WrapContact MaterialCopper, Nickel, Tin AlloyContact FinishGoldContact Finish Thickness-Contact Type-ColorBlackFlange FeatureFlush Mount, Top Opening, Unthreaded, 0.156" (3.96mm) DiaOperating Temperature-65°C ~ 105°C	Features	-	
Contact MaterialCopper, Nickel, Tin AlloyContact FinishGoldContact Finish Thickness-Contact Type-ColorBlackFlange FeatureFlush Mount, Top Opening, Unthreaded, 0.156" (3.96mm) DiaOperating Temperature-65°C ~ 105°C	Mounting Type	Through Hole	
Contact FinishGoldContact Finish Thickness-Contact Type-ColorBlackFlange FeatureFlush Mount, Top Opening, Unthreaded, 0.156" (3.96mm) DiaOperating Temperature-65°C ~ 105°C	Termination	Wire Wrap	
Contact Finish Thickness-Contact Type-ColorBlackFlange FeatureFlush Mount, Top Opening, Unthreaded, 0.156" (3.96mm) DiaOperating Temperature-65°C ~ 105°C	Contact Material	Copper, Nickel, Tin Alloy	
Contact Type-ColorBlackFlange FeatureFlush Mount, Top Opening, Unthreaded, 0.156" (3.96mm) DiaOperating Temperature-65°C ~ 105°C	Contact Finish	Gold	
ColorBlackFlange FeatureFlush Mount, Top Opening, Unthreaded, 0.156" (3.96mm) DiaOperating Temperature-65°C ~ 105°C	Contact Finish Thickness	-	
Flange FeatureFlush Mount, Top Opening, Unthreaded, 0.156" (3.96mm) DiaOperating Temperature-65°C ~ 105°C	Contact Type	-	
Operating Temperature $-65^{\circ}C \sim 105^{\circ}C$	Color	Black	
	Flange Feature	Flush Mount, Top Opening, Unthreaded, 0.156" (3.96mm) Dia	
Paport arrors?	Operating Temperature	-65°C ~ 105°C	
Report errors:			Report errors?

395-012-541-204 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

If you have any question about 395-012-541-204, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com