



39D157F100FP6 Information

Heisener.com

For Reference Only

39D157F100FP6 Part Number Manufacturer Vishay Sprague Category Capacitors

Aluminum Electrolytic Capacitors CAP ALUM 150UF 100V AXIAL

Description

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









39D157F100FP6 Specifications

Manufacturer Part Number 39D157F100FP6 Manufacturer Vishay Sprague Category Capacitors Package Axial, Can Series 39D Capacitance 150µF Tolerance -10%, +50% Voltage - Rated 100V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 500 Hrs @ 85°C Operating Temperature -20°C ~ 85°C Polarization General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing - Size / Dimension 0.634" Dia x 2.642" L (16.10mm x 67.10mm) Height - Seated (Max) - Surface Mount Land Size - Mounting Type Through Hole Package / Case Axial, Can Report errors?	•	
Category Capacitors Package Axial, Can Series 39D Capacitance 150μF Tolerance -10%, +50% Voltage - Rated 100V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 500 Hrs @ 85°C Operating Temperature -20°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing - Size / Dimension 0.634" Dia x 2.642" L (16.10mm x 67.10mm) Height - Seated (Max) - Surface Mount Land Size - Mounting Type Through Hole Package / Case Axial, Can	Manufacturer Part Number	39D157F100FP6
Package Axial, Can Series 39D Capacitance 150µF Tolerance -10%, +50% Voltage - Rated 100V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 500 Hrs @ 85°C Operating Temperature -20°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing - Size / Dimension 0.634" Dia x 2.642" L (16.10mm x 67.10mm) Height - Seated (Max) - Surface Mount Land Size - Mounting Type Through Hole Package / Case Axial, Can	Manufacturer	Vishay Sprague
Package Axial, Can Series 39D Capacitance 150μF Tolerance -10%, +50% Voltage - Rated 100V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 500 Hrs @ 85°C Operating Temperature -20°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing - Size / Dimension 0.634" Dia x 2.642" L (16.10mm x 67.10mm) Height - Seated (Max) - Surface Mount Land Size - Mounting Type Through Hole Package / Case Axial, Can	Category	Capacitors
Series 39D Capacitance 150µF Tolerance -10%, +50% Voltage - Rated 100V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 500 Hrs @ 85°C Operating Temperature -20°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing - Size / Dimension 0.634" Dia x 2.642" L (16.10mm x 67.10mm) Height - Seated (Max) - Surface Mount Land Size - Mounting Type Through Hole Package / Case Axial, Can		Aluminum Electrolytic Capacitors
Capacitance 150μF Tolerance -10%, +50% Voltage - Rated 100V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 500 Hrs @ 85°C Operating Temperature -20°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing - Size / Dimension 0.634" Dia x 2.642" L (16.10mm x 67.10mm) Height - Seated (Max) - Surface Mount Land Size - Mounting Type Through Hole Package / Case Axial, Can	Package	Axial, Can
Tolerance -10%, +50% Voltage - Rated 100V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 500 Hrs @ 85°C Operating Temperature -20°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing - Size / Dimension 0.634" Dia x 2.642" L (16.10mm x 67.10mm) Height - Seated (Max) - Surface Mount Land Size - Mounting Type Through Hole Package / Case Associated (Max) - Through Hole Package / Case	Series	39D
Voltage - Rated100VESR (Equivalent Series Resistance)-Lifetime @ Temp.500 Hrs @ 85°COperating Temperature-20°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Ripple Current - High Frequency-Impedance-Lead Spacing-Size / Dimension0.634" Dia x 2.642" L (16.10mm x 67.10mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseAxial, Can	Capacitance	150μF
ESR (Equivalent Series Resistance) Lifetime @ Temp. 500 Hrs @ 85°C Operating Temperature -20°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency Impedance Lead Spacing Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case - 500 Hrs @ 85°C -20°C ~ 85°C -20°C	Tolerance	-10%, +50%
Lifetime @ Temp. 500 Hrs @ 85°C Operating Temperature -20°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing - Size / Dimension 0.634" Dia x 2.642" L (16.10mm x 67.10mm) Height - Seated (Max) - Surface Mount Land Size - Mounting Type Through Hole Package / Case Associated Ass	Voltage - Rated	100V
Operating Temperature-20°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Ripple Current - High Frequency-Impedance-Lead Spacing-Size / Dimension0.634" Dia x 2.642" L (16.10mm x 67.10mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseAxial, Can	ESR (Equivalent Series Resistance)	-
Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing - Size / Dimension 0.634" Dia x 2.642" L (16.10mm x 67.10mm) Height - Seated (Max) - Surface Mount Land Size - Mounting Type Through Hole Package / Case Axial, Can	Lifetime @ Temp.	500 Hrs @ 85°C
Applications Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing - Size / Dimension - Height - Seated (Max) - Surface Mount Land Size - Mounting Type - Package / Case - General Purpose - Through Hole - Axial, Can	Operating Temperature	-20°C ~ 85°C
Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing - Size / Dimension 0.634" Dia x 2.642" L (16.10mm x 67.10mm) Height - Seated (Max) - Surface Mount Land Size - Mounting Type Through Hole Package / Case Axial, Can	Polarization	Polar
Ripple Current - High Frequency Impedance Lead Spacing - Size / Dimension Height - Seated (Max) - Surface Mount Land Size Mounting Type Through Hole Package / Case - Axial, Can	Applications	General Purpose
Impedance - Lead Spacing - Size / Dimension 0.634" Dia x 2.642" L (16.10mm x 67.10mm) Height - Seated (Max) - Surface Mount Land Size - Mounting Type Through Hole Package / Case Axial, Can	Ripple Current - Low Frequency	-
Lead Spacing - Size / Dimension 0.634" Dia x 2.642" L (16.10mm x 67.10mm) Height - Seated (Max) - Surface Mount Land Size - Mounting Type Through Hole Package / Case Axial, Can	Ripple Current - High Frequency	-
Size / Dimension 0.634" Dia x 2.642" L (16.10mm x 67.10mm) Height - Seated (Max) - Surface Mount Land Size - Mounting Type Through Hole Package / Case Axial, Can	Impedance	-
Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Axial, Can	Lead Spacing	-
Surface Mount Land Size - Mounting Type Through Hole Package / Case Axial, Can	Size / Dimension	0.634" Dia x 2.642" L (16.10mm x 67.10mm)
Mounting Type Through Hole Package / Case Axial, Can	Height - Seated (Max)	-
Package / Case Axial, Can	Surface Mount Land Size	-
-	Mounting Type	Through Hole
Report errors?	Package / Case	Axial, Can
		Report errors?

39D157F100FP6 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

39D157F100FP6 Payment Methods



















39D157F100FP6 Shipping Methods













If you have any question about 39D157F100FP6, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com