



39D177F300JS6 Information

(A) Heisener.com

Part Number39D177F300JS6ManufacturerVishay SpragueCategoryCapacitors

Aluminum Electrolytic Capacitors

Description CAP ALUM 170UF 300V AXIAL

Package Axial, Can

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









39D177F300JS6 Specifications

Manufacturer Part Number 39D177F300JS6 Manufacturer Vishay Sprague Category Capacitors Package Axial, Can Series 39D Capacitance 170μF Tolerance -10%, +50% Voltage - Rated 300V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 500 Hrs @ 85°C Operating Temperature -20°C ~ 85°C Polarization General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing - Size / Dimension 1.012" Dia x 3.142" L (25.70mm x 79.80mm) Height - Seated (Max) - Surface Mount Land Size - Mounting Type Through Hole Package / Case Axial, Can Report errors?	*	
Category Capacitors Package Axial, Can Series 39D Capacitance 170μF Tolerance -10%, +50% Voltage - Rated 300V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 500 Hrs @ 85°C Operating Temperature -20°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing - Size / Dimension 1.012" Dia x 3.142" L (25.70mm x 79.80mm) Height - Seated (Max) - Surface Mount Land Size - Mounting Type Through Hole Package / Case Axial, Can	Manufacturer Part Number	39D177F300JS6
Aluminum Electrolytic Capacitors Package Axial, Can Series 39D Capacitance 170µF Tolerance -10%, +50% Voltage - Rated 300V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 500 Hrs @ 85°C Operating Temperature -20°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing - Size / Dimension 1.012" Dia x 3.142" L (25.70mm x 79.80mm) Height - Seated (Max) - Surface Mount Land Size - Mounting Type Through Hole Package / Case Axial, Can	Manufacturer	Vishay Sprague
Package Axial, Can Series 39D Capacitance 170μF Tolerance -10%, +50% Voltage - Rated 300V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 500 Hrs @ 85°C Operating Temperature -20°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Lead Spacing - Size / Dimension 1.012" Dia x 3.142" L (25.70mm x 79.80mm) Height - Seated (Max) - Surface Mount Land Size - Mounting Type Through Hole Package / Case Axial, Can	Category	Capacitors
Series 39D Capacitance 170µF Tolerance -10%, +50% Voltage - Rated 300V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 500 Hrs @ 85°C Operating Temperature -20°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Lead Spacing - Size / Dimension 1.012" Dia x 3.142" L (25.70mm x 79.80mm) Height - Seated (Max) - Surface Mount Land Size - Mounting Type Through Hole Package / Case Axial, Can		Aluminum Electrolytic Capacitors
Capacitance 170μF Tolerance -10%, +50% Voltage - Rated 300V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 500 Hrs @ 85°C Operating Temperature -20°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing - Size / Dimension 1.012" Dia x 3.142" L (25.70mm x 79.80mm) Height - Seated (Max) - Surface Mount Land Size - Mounting Type Through Hole Package / Case Axial, Can	Package	Axial, Can
Tolerance -10%, +50% Voltage - Rated 300V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 500 Hrs @ 85°C Operating Temperature -20°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing - Size / Dimension 1.012" Dia x 3.142" L (25.70mm x 79.80mm) Height - Seated (Max) - Surface Mount Land Size - Mounting Type Through Hole Package / Case Axial, Can	Series	39D
Voltage - Rated300VESR (Equivalent Series Resistance)-Lifetime @ Temp.500 Hrs @ 85°COperating Temperature-20°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Ripple Current - High Frequency-Impedance-Lead Spacing-Size / Dimension1.012" Dia x 3.142" L (25.70mm x 79.80mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseAxial, Can	Capacitance	170μF
ESR (Equivalent Series Resistance) Lifetime @ Temp. 500 Hrs @ 85°C Operating Temperature -20°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency Impedance Lead Spacing Size / Dimension 1.012" Dia x 3.142" L (25.70mm x 79.80mm) Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Axial, Can	Tolerance	-10%, +50%
Lifetime @ Temp. 500 Hrs @ 85°C Operating Temperature -20°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing - Size / Dimension 1.012" Dia x 3.142" L (25.70mm x 79.80mm) Height - Seated (Max) - Surface Mount Land Size - Mounting Type Through Hole Package / Case Asoc Assoc A	Voltage - Rated	300V
Operating Temperature-20°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Ripple Current - High Frequency-Impedance-Lead Spacing-Size / Dimension1.012" Dia x 3.142" L (25.70mm x 79.80mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseAxial, Can	ESR (Equivalent Series Resistance)	-
Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing - Size / Dimension 1.012" Dia x 3.142" L (25.70mm x 79.80mm) Height - Seated (Max) - Surface Mount Land Size - Mounting Type Through Hole Package / Case Axial, Can	Lifetime @ Temp.	500 Hrs @ 85°C
Applications Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing - Size / Dimension - Height - Seated (Max) Surface Mount Land Size - Mounting Type Package / Case General Purpose - General Purpose - 1.012" Dia x 3.142" L (25.70mm x 79.80mm) - Through Hole Package / Case Axial, Can	Operating Temperature	-20°C ~ 85°C
Ripple Current - Low Frequency	Polarization	Polar
Ripple Current - High Frequency Impedance Lead Spacing - Size / Dimension 1.012" Dia x 3.142" L (25.70mm x 79.80mm) Height - Seated (Max) - Surface Mount Land Size - Mounting Type Through Hole Package / Case Axial, Can	Applications	General Purpose
Impedance - Lead Spacing - Size / Dimension 1.012" Dia x 3.142" L (25.70mm x 79.80mm) Height - Seated (Max) - Surface Mount Land Size - Mounting Type Through Hole Package / Case Axial, Can	Ripple Current - Low Frequency	-
Lead Spacing - Size / Dimension 1.012" Dia x 3.142" L (25.70mm x 79.80mm) Height - Seated (Max) - Surface Mount Land Size - Mounting Type Through Hole Package / Case Axial, Can	Ripple Current - High Frequency	-
Size / Dimension 1.012" Dia x 3.142" L (25.70mm x 79.80mm) Height - Seated (Max) - Surface Mount Land Size - Mounting Type Through Hole Package / Case Axial, Can	Impedance	-
Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Axial, Can	Lead Spacing	-
Surface Mount Land Size - Mounting Type Through Hole Package / Case Axial, Can	Size / Dimension	1.012" Dia x 3.142" L (25.70mm x 79.80mm)
Mounting Type Through Hole Package / Case Axial, Can	Height - Seated (Max)	-
Package / Case Axial, Can	Surface Mount Land Size	-
•	Mounting Type	Through Hole
Report errors?	Package / Case	Axial, Can
		Report errors?

39D177F300JS6 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

39D177F300JS6 Payment Methods



















39D177F300JS6 Shipping Methods













If you have any question about 39D177F300JS6, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com