



#### 39D307F250JT6 Information

Heisener.com

Part Number 39D307F250JT6
Manufacturer Vishay Sprague
Category Capacitors

Capacitors
Aluminum Electrolytic Capacitors

**Description** CAP ALUM 300UF 250V AXIAL

Package Axial, Can

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com

Request a Quote



# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# 39D307F250JT6 Specifications

Manufacturer Part Number         39D307F250TT6           Manufacturer         Vishay Sprague           Category         Capacitors           Aluminum Electrolytic Capacitors           Package         Axial, Can           Series         39D           Capacitance         300µF           Tolerance         -10%, +50%           Voltage - Rated         250V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         500 Hrs @ 85°C           Operating Temperature         -20°C ~ 85°C           Polarization         General Purpose           Ripple Current - Low Frequency         -           Ripple Current - High Frequency         -           Impedance         -           Lead Spacing         -           Size / Dimension         1.012" Dia x 3.642" L (25.70mm x 92.50mm)           Height - Seated (Max)         -           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Axial, Can           Report errors?	•	
Category Capacitors Aluminum Electrolytic Capacitors  Package Axial, Can Series 39D Capacitance 300µF Tolerance -10%, +50% Voltage - Rated 250V ESR (Equivalent Series Resistance) Lifetime @ Temp. 500 Hrs @ 85°C Operating Temperature -20°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing Size / Dimension 1.012" Dia x 3.642" L (25.70mm x 92.50mm) Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case  Axial, Can	Manufacturer Part Number	39D307F250JT6
Aluminum Electrolytic Capacitors  Package Axial, Can  Series 39D  Capacitance 300µF  Tolerance -10%, +50%  Voltage - Rated 250V  ESR (Equivalent Series Resistance) - Lifetime @ Temp. 500 Hrs @ 85°C  Operating Temperature -20°C ~ 85°C  Polarization Polar  Applications General Purpose  Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing - Size / Dimension 1.012" Dia x 3.642" L (25.70mm x 92.50mm)  Height - Seated (Max) - Surface Mount Land Size - Mounting Type Through Hole  Package / Case Axial, Can	Manufacturer	Vishay Sprague
Package         Axial, Can           Series         39D           Capacitance         300μF           Tolerance         -10%, +50%           Voltage - Rated         250V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         500 Hrs @ 85°C           Operating Temperature         -20°C ~ 85°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         -           Ripple Current - High Frequency         -           Lead Spacing         -           Size / Dimension         1.012" Dia x 3.642" L (25.70mm x 92.50mm)           Height - Seated (Max)         -           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Axial, Can	Category	Capacitors
Series         39D           Capacitance         300µF           Tolerance         -10%, +50%           Voltage - Rated         250V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         500 Hrs @ 85°C           Operating Temperature         -20°C ~ 85°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         -           Ripple Current - High Frequency         -           Impedance         -           Lead Spacing         -           Size / Dimension         1.012" Dia x 3.642" L (25.70mm x 92.50mm)           Height - Seated (Max)         -           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Axial, Can		Aluminum Electrolytic Capacitors
Capacitance300μFTolerance-10%, +50%Voltage - Rated250VESR (Equivalent Series Resistance)-Lifetime @ Temp.500 Hrs @ 85°COperating Temperature-20°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Ripple Current - High Frequency-Impedance-Lead Spacing-Size / Dimension1.012" Dia x 3.642" L (25.70mm x 92.50mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseAxial, Can	Package	Axial, Can
Tolerance -10%, +50%  Voltage - Rated 250V  ESR (Equivalent Series Resistance) - Lifetime @ Temp. 500 Hrs @ 85°C  Operating Temperature -20°C ~ 85°C  Polarization Polar  Applications General Purpose  Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing - Size / Dimension 1.012" Dia x 3.642" L (25.70mm x 92.50mm)  Height - Seated (Max) - Surface Mount Land Size - Mounting Type Through Hole  Package / Case Axial, Can	Series	39D
Voltage - Rated 250V  ESR (Equivalent Series Resistance) -  Lifetime @ Temp. 500 Hrs @ 85°C  Operating Temperature -20°C ~ 85°C  Polarization Polar  Applications General Purpose  Ripple Current - Low Frequency -  Ripple Current - High Frequency -  Impedance -  Lead Spacing -  Size / Dimension 1.012" Dia x 3.642" L (25.70mm x 92.50mm)  Height - Seated (Max) -  Surface Mount Land Size -  Mounting Type Through Hole  Package / Case Axial, Can	Capacitance	300μF
ESR (Equivalent Series Resistance)  Lifetime @ Temp.  500 Hrs @ 85°C  Operating Temperature  -20°C ~ 85°C  Polarization  Applications  General Purpose  Ripple Current - Low Frequency  - Ripple Current - High Frequency  Impedance  Lead Spacing  Size / Dimension  1.012" Dia x 3.642" L (25.70mm x 92.50mm)  Height - Seated (Max)  Surface Mount Land Size  Mounting Type  Through Hole  Package / Case  Axial, Can	Tolerance	-10%, +50%
Lifetime @ Temp. 500 Hrs @ 85°C  Operating Temperature -20°C ~ 85°C  Polarization Polar  Applications General Purpose  Ripple Current - Low Frequency -  Ripple Current - High Frequency -  Impedance -  Lead Spacing -  Size / Dimension 1.012" Dia x 3.642" L (25.70mm x 92.50mm)  Height - Seated (Max) -  Surface Mount Land Size -  Mounting Type Through Hole  Package / Case Associated As	Voltage - Rated	250V
Operating Temperature Polarization Polar Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing - Size / Dimension Liol2" Dia x 3.642" L (25.70mm x 92.50mm)  Height - Seated (Max) Surface Mount Land Size  Mounting Type Through Hole Package / Case Axial, Can	ESR (Equivalent Series Resistance)	-
Polarization Polar  Applications General Purpose  Ripple Current - Low Frequency -  Ripple Current - High Frequency -  Impedance -  Lead Spacing -  Size / Dimension 1.012" Dia x 3.642" L (25.70mm x 92.50mm)  Height - Seated (Max) -  Surface Mount Land Size -  Mounting Type Through Hole  Package / Case Axial, Can	Lifetime @ Temp.	500 Hrs @ 85°C
Applications  Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing - Size / Dimension - Height - Seated (Max) - Surface Mount Land Size - Mounting Type Package / Case - General Purpose -  Lead Purpose -  Lead Spacing -  Through Hole Package / Case -  Axial, Can	Operating Temperature	-20°C ~ 85°C
Ripple Current - Low Frequency Ripple Current - High Frequency - Impedance - Lead Spacing - Size / Dimension - Height - Seated (Max) - Surface Mount Land Size - Mounting Type Through Hole Package / Case - Axial, Can	Polarization	Polar
Ripple Current - High Frequency Impedance Lead Spacing - Size / Dimension 1.012" Dia x 3.642" L (25.70mm x 92.50mm)  Height - Seated (Max) - Surface Mount Land Size - Mounting Type Through Hole Package / Case Axial, Can	Applications	General Purpose
Impedance - Lead Spacing - Size / Dimension 1.012" Dia x 3.642" L (25.70mm x 92.50mm) Height - Seated (Max) - Surface Mount Land Size - Mounting Type Through Hole Package / Case Axial, Can	Ripple Current - Low Frequency	-
Lead Spacing - Size / Dimension 1.012" Dia x 3.642" L (25.70mm x 92.50mm) Height - Seated (Max) - Surface Mount Land Size - Mounting Type Through Hole Package / Case Axial, Can	Ripple Current - High Frequency	-
Size / Dimension 1.012" Dia x 3.642" L (25.70mm x 92.50mm)  Height - Seated (Max) -  Surface Mount Land Size -  Mounting Type Through Hole  Package / Case Axial, Can	Impedance	-
Height - Seated (Max)  Surface Mount Land Size  Mounting Type  Through Hole  Package / Case  Axial, Can	Lead Spacing	-
Surface Mount Land Size -  Mounting Type Through Hole Package / Case Axial, Can	Size / Dimension	1.012" Dia x 3.642" L (25.70mm x 92.50mm)
Mounting Type Through Hole Package / Case Axial, Can	Height - Seated (Max)	-
Package / Case Axial, Can	Surface Mount Land Size	-
-	Mounting Type	Through Hole
Report errors?	Package / Case	Axial, Can
		Report errors?

#### 39D307F250JT6 Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### 39D307F250JT6 Payment Methods



















## 39D307F250JT6 Shipping Methods













If you have any question about 39D307F250JT6, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com