

3CIF21 Information



For Reference Only

Part Number 3CIF21 Manufacturer Eaton

Category Circuit Protection

Electrical, Specialty Fuses

Description FUSE CARTRIDGE 3A 600VAC/250VDC

Package Cylindrical, Blade Terminal (Bolt)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









3CIF21 Specifications

Manufacturer Part Number3CIF21ManufacturerEatonCategoryCircuit ProtectionBeckageCylindrical, Specialty FusesPackageCylindrical, Blade Terminal (Bolt)Series-Fuse TypeCartridgeCurrent Rating3AVoltage Rating - AC600VVoltage Rating - DC250VResponse TimeFastApplicationsElectrical, IndustrialFeatures-Class-ApprovalsCE, CSAOperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension0.543" Dia x 1.398" L (13.80mm x 35.50mm)		
Category Circuit Protection Electrical, Specialty Fuses Package Cylindrical, Blade Terminal (Bolt) Series - Fuse Type Cartridge Current Rating 3A Voltage Rating - AC 600V Voltage Rating - DC Esponse Time Fast Applications Electrical, Industrial Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Circuit Protection Electrical, Specialty Fuses Cartridge Captridge Captridg	Manufacturer Part Number	3CIF21
Electrical, Specialty Fuses Package Cylindrical, Blade Terminal (Bolt) Series - Fuse Type Cartridge Current Rating 3A Voltage Rating - AC Voltage Rating - DC Esponse Time Fast Applications Electrical, Industrial Features - Class - Approvals Cyer CE, CSA Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Electrical, Industrial Features - CE, CSA Cyer CE, CSA C	Manufacturer	Eaton
PackageCylindrical, Blade Terminal (Bolt)Series-Fuse TypeCartridgeCurrent Rating3AVoltage Rating - AC600VVoltage Rating - DC250VResponse TimeFastApplicationsElectrical, IndustrialFeatures-Class-ApprovalsCE, CSAOperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension0.543" Dia x 1.398" L (13.80mm x 35.50mm)	Category	Circuit Protection
Series-Fuse TypeCartridgeCurrent Rating3AVoltage Rating - AC600VVoltage Rating - DC250VResponse TimeFastApplicationsElectrical, IndustrialFeatures-Class-ApprovalsCE, CSAOperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension0.543" Dia x 1.398" L (13.80mm x 35.50mm)		Electrical, Specialty Fuses
Fuse TypeCartridgeCurrent Rating3AVoltage Rating - AC600VVoltage Rating - DC250VResponse TimeFastApplicationsElectrical, IndustrialFeatures-Class-ApprovalsCE, CSAOperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension0.543" Dia x 1.398" L (13.80mm x 35.50mm)	Package	Cylindrical, Blade Terminal (Bolt)
Current Rating Voltage Rating - AC 600V Voltage Rating - DC 250V Response Time Fast Applications Electrical, Industrial Features - Class - Approvals CE, CSA Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Size / Dimension 3A 600V 60	Series	-
Voltage Rating - AC Voltage Rating - DC 250V Response Time Fast Applications Electrical, Industrial Features - Class - Approvals CE, CSA Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Size / Dimension 600V 250V CE, CSA Fast Clectrical, Industrial - CE, CSA - CE, CSA CE, CSA CUBA CE, CSA CUBA CE, CSA CUBA	Fuse Type	Cartridge
Voltage Rating - DC Response Time Fast Applications Electrical, Industrial Features - Class - Approvals CE, CSA Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 250V 250V 260V 260V 260V 260V 260V 260V 260V 270V 270V 280V	Current Rating	3A
Response Time Applications Electrical, Industrial Features - Class - Approvals Operating Temperature - Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Fast Electrical, Industrial - CE, CSA - OPERATOR OPER	Voltage Rating - AC	600V
Applications Electrical, Industrial Features - Class - Approvals CE, CSA Operating Temperature - Breaking Capacity @ Rated Voltage 200kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.543" Dia x 1.398" L (13.80mm x 35.50mm)	Voltage Rating - DC	250V
Features - Class - CSA Approvals CE, CSA Operating Temperature - Breaking Capacity @ Rated Voltage 200kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.543" Dia x 1.398" L (13.80mm x 35.50mm)	Response Time	Fast
Class - CE, CSA Operating Temperature - Sereking Capacity @ Rated Voltage 200kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.543" Dia x 1.398" L (13.80mm x 35.50mm)	Applications	Electrical, Industrial
Approvals CE, CSA Operating Temperature - Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension CE, CSA CUSA CE, CSA CUSA CE, CSA CUSA CONNA CONNA CONNA CONNA CE, CSA CUSA CONNA C	Features	-
Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.543" Dia x 1.398" L (13.80mm x 35.50mm)	Class	-
Breaking Capacity @ Rated Voltage 200kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.543" Dia x 1.398" L (13.80mm x 35.50mm)	Approvals	CE, CSA
Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.543" Dia x 1.398" L (13.80mm x 35.50mm)	Operating Temperature	-
Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.543" Dia x 1.398" L (13.80mm x 35.50mm)	Breaking Capacity @ Rated Voltage	200kA
Size / Dimension 0.543" Dia x 1.398" L (13.80mm x 35.50mm)	Mounting Type	Bolt Mount
	Package / Case	Cylindrical, Blade Terminal (Bolt)
Report errors?	Size / Dimension	0.543" Dia x 1.398" L (13.80mm x 35.50mm)
*		Report errors?

3CIF21 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

3CIF21 Payment Methods



















3CIF21 Shipping Methods













If you have any question about 3CIF21, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com