



3D2ZBH08481 Information



For Reference Only

Part Number 3D2ZBH08481
Manufacturer APEM Inc.
Category Switches

Navigation Switches, Joystick

Description SWITCH JOYSTICK 10A 250V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









3D2ZBH08481 Specifications

Category Switches Navigation Switches, Joystick Package - Series 1000HE Type Joystick, 2 - Axis Actuator Type Joystick Switch Function 8-Way Directional Functions, Extra - Output Digital (Mechanical Switch) Voltage - Supply - Current Rating 10A (AC) Voltage Rating - AC 250V Voltage Rating - DC - Contact Material Silver (Ag) Contact Finish - Mounting Type Panel Mount Termination Style Solder Lug Operating Temperature -20°C ~ 50°C Panel Cutout Dimensions Circular - 22.00mm Dia		
Category Switches Navigation Switches, Joystick Package - Series 1000HE Type Joystick, 2 - Axis Actuator Type Joystick Switch Function 8-Way Directional Functions, Extra - Output Digital (Mechanical Switch) Voltage - Supply - Current Rating 10A (AC) Voltage Rating - AC 250V Voltage Rating - DC - Contact Material Silver (Ag) Contact Finish - Mounting Type Panel Mount Termination Style Solder Lug Operating Temperature -20°C ~ 50°C Panel Cutout Dimensions Circular - 22.00mm Dia Ingress Protection IP67 - Dust Tight, Waterproof Features -	Manufacturer Part Number	3D2ZBH08481
Navigation Switches, Joystick Package - Series 1000HE Type Joystick, 2 - Axis Actuator Type Joystick Switch Function 8-Way Directional Functions, Extra - Output Digital (Mechanical Switch) Voltage - Supply - Current Rating 10A (AC) Voltage Rating - AC Voltage Rating - DC - Contact Material Silver (Ag) Contact Finish - Mounting Type Panel Mount Termination Style Operating Temperature -20°C ~ 50°C Panel Cutout Dimensions Ingress Protection P67 - Dust Tight, Waterproof Features	Manufacturer	APEM Inc.
Package - Series 1000HE Type Joystick, 2 - Axis Actuator Type Joystick Switch Function 8-Way Directional Functions, Extra - Output Digital (Mechanical Switch) Voltage - Supply - Current Rating 10A (AC) Voltage Rating - AC 250V Voltage Rating - DC - Contact Material Silver (Ag) Contact Finish - Mounting Type Panel Mount Termination Style Solder Lug Operating Temperature -20°C ~ 50°C Panel Cutout Dimensions Circular - 22.00mm Dia Ingress Protection IP67 - Dust Tight, Waterproof Features -	Category	Switches
Series 1000HE Type Joystick, 2 - Axis Actuator Type Joystick Switch Function 8-Way Directional Functions, Extra - Output Digital (Mechanical Switch) Voltage - Supply - Current Rating 10A (AC) Voltage Rating - AC 250V Voltage Rating - DC - Contact Material Silver (Ag) Contact Finish - Mounting Type Panel Mount Termination Style Solder Lug Operating Temperature -20°C ~ 50°C Panel Cutout Dimensions Circular - 22.00mm Dia Ingress Protection IP67 - Dust Tight, Waterproof Features -		Navigation Switches, Joystick
Type Joystick, 2 - Axis Actuator Type Joystick Switch Function 8-Way Directional Functions, Extra - Output Digital (Mechanical Switch) Voltage - Supply - Current Rating 10A (AC) Voltage Rating - AC 250V Voltage Rating - DC - Contact Material Silver (Ag) Contact Finish - Mounting Type Panel Mount Termination Style Solder Lug Operating Temperature -20°C ~ 50°C Panel Cutout Dimensions Circular - 22.00mm Dia Ingress Protection IP67 - Dust Tight, Waterproof Features -	Package	-
Actuator Type Switch Function 8-Way Directional Functions, Extra - Output Digital (Mechanical Switch) Voltage - Supply - Current Rating 10A (AC) Voltage Rating - AC 250V Voltage Rating - DC - Contact Material Silver (Ag) Contact Finish - Mounting Type Panel Mount Termination Style Operating Temperature Panel Cutout Dimensions Circular - 22.00mm Dia Ingress Protection Features Jigital (Mechanical Switch) - Silver (AC) Digital (Mechanical Switch) - Silver (AC) Panel Mount Silver (AC) - Contact Material Silver (Ag) - Contact Finish - Circular - 22.00mm Dia Ingress Protection IP67 - Dust Tight, Waterproof Features	Series	1000HE
Switch Function Functions, Extra Output Digital (Mechanical Switch) Voltage - Supply - Current Rating 10A (AC) Voltage Rating - AC 250V Voltage Rating - DC Contact Material Silver (Ag) Contact Finish - Mounting Type Panel Mount Termination Style Operating Temperature Panel Cutout Dimensions Ingress Protection Features - Seway Directional S-Way Directional - Bayay Directional - Sulter (Mechanical Switch) - Digital (Mechanical Switch) - Digital (Mechanical Switch) - Panel (MaC) - Silver (Ag) - Silver (Ag) - Cortact Material Silver (Ag) - Cortact Finish - Circular - 22.00mm Dia IP67 - Dust Tight, Waterproof Features -	Туре	Joystick, 2 - Axis
Functions, Extra Output Digital (Mechanical Switch) Voltage - Supply - Current Rating 10A (AC) Voltage Rating - AC 250V Voltage Rating - DC - Contact Material Silver (Ag) Contact Finish - Mounting Type Panel Mount Termination Style Operating Temperature -20°C ~ 50°C Panel Cutout Dimensions Ingress Protection Panel Mount Ingress Protection Panel Cutout Tight, Waterproof Features - Digital (Mechanical Switch) - Current Rating	Actuator Type	Joystick
Output Digital (Mechanical Switch) Voltage - Supply - Current Rating 10A (AC) Voltage Rating - AC 250V Voltage Rating - DC - Contact Material Silver (Ag) Contact Finish - Mounting Type Panel Mount Termination Style Solder Lug Operating Temperature -20°C ~ 50°C Panel Cutout Dimensions Circular - 22.00mm Dia Ingress Protection IP67 - Dust Tight, Waterproof Features -	Switch Function	8-Way Directional
Voltage - Supply Current Rating 10A (AC) Voltage Rating - AC 250V Voltage Rating - DC - Contact Material Silver (Ag) Contact Finish - Mounting Type Panel Mount Termination Style Operating Temperature Panel Cutout Dimensions Circular - 22.00mm Dia Ingress Protection Features - 10A (AC) 250V Panel Cutout Dimensions Circular - 22.00mm Dia IP67 - Dust Tight, Waterproof Features - 10A (AC) 250V	Functions, Extra	-
Current Rating Voltage Rating - AC Voltage Rating - DC - Contact Material Contact Finish - Mounting Type Panel Mount Termination Style Operating Temperature Operating Temperature Panel Cutout Dimensions Ingress Protection Features 10A (AC) 250V - Panel Cutout Dimensions 10A (AC) - 250V - 250V - 260V - 260V - 270°C ~ 50°C - 270°C ~ 50	Output	Digital (Mechanical Switch)
Voltage Rating - AC Voltage Rating - DC Contact Material Silver (Ag) Contact Finish - Mounting Type Panel Mount Termination Style Operating Temperature Operating Temperature Panel Cutout Dimensions Circular - 22.00mm Dia Ingress Protection IP67 - Dust Tight, Waterproof Features	Voltage - Supply	-
Voltage Rating - DC Contact Material Silver (Ag) Contact Finish Mounting Type Panel Mount Termination Style Operating Temperature -20°C ~ 50°C Panel Cutout Dimensions Circular - 22.00mm Dia Ingress Protection IP67 - Dust Tight, Waterproof Features -	Current Rating	10A (AC)
Contact Material Contact Finish Mounting Type Panel Mount Termination Style Operating Temperature Operating Temperature -20°C ~ 50°C Panel Cutout Dimensions Circular - 22.00mm Dia Ingress Protection IP67 - Dust Tight, Waterproof Features -	Voltage Rating - AC	250V
Contact Finish Mounting Type Panel Mount Termination Style Solder Lug Operating Temperature -20°C ~ 50°C Panel Cutout Dimensions Circular - 22.00mm Dia Ingress Protection IP67 - Dust Tight, Waterproof Features -	Voltage Rating - DC	-
Mounting Type Panel Mount Termination Style Solder Lug Operating Temperature -20°C ~50°C Panel Cutout Dimensions Circular - 22.00mm Dia Ingress Protection IP67 - Dust Tight, Waterproof Features -	Contact Material	Silver (Ag)
Termination Style Operating Temperature -20°C ~ 50°C Panel Cutout Dimensions Circular - 22.00mm Dia Ingress Protection IP67 - Dust Tight, Waterproof Features -	Contact Finish	-
Operating Temperature -20°C ~ 50°C Panel Cutout Dimensions Circular - 22.00mm Dia Ingress Protection IP67 - Dust Tight, Waterproof Features -	Mounting Type	Panel Mount
Panel Cutout Dimensions Circular - 22.00mm Dia Ingress Protection IP67 - Dust Tight, Waterproof Features -	Termination Style	Solder Lug
Ingress Protection IP67 - Dust Tight, Waterproof Features -	Operating Temperature	-20°C ~ 50°C
Features -	Panel Cutout Dimensions	Circular - 22.00mm Dia
	Ingress Protection	IP67 - Dust Tight, Waterproof
Report errors?	Features	-
		Report errors?

3D2ZBH08481 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

3D2ZBH08481 Payment Methods


































If you have any question about 3D2ZBH08481, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com