

3FL16-350

3FL16-350 Information



Part Number	3FL16-350	
Manufacturer	Tamura	
Category	Transformers Power Transformers	
Description	XFRMR LAMINATED 6VA THRU HOLE	
Package	-	
	For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com E-mail: salesdept@heisener.com	



Request a Quote

For Reference Only

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



3FL16-350 Specifications

Manufacturer Part Number3FL16-350ManufacturerTamuraCategoryTransformersPackage-PackageSFLSeriesSFLTypeLaminated CoreVoltage - Primary115V, 230VVoltage - Secondary (Full Load)Paralel 700mA, Series 350mACurrent - Output (Max)DualSecondary Winding(s)DualPower - Max6VAMounting TypeSolPower - MaxFrinaryPower - MaxCurent - Output (Max)Power - MaxStare Secondary (Partice)Power - MaxStare Secondar		
CategoryTransformersPower TransformersPackage-Series3FLTypeLaminated CoreVoltage - Primary115V, 230VVoltage - Secondary (Full Load)Parallel 8V, Series 16VCurrent - Output (Max)Parallel 700mA, Series 350mAPrimary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max6 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension47.60mm L x 39.60mm WHeight - Seated (Max)21.60mm	Manufacturer Part Number	3FL16-350
Power TransformersPackage-Series3FLTypeLaminated CoreVoltage - Primary115V, 230VVoltage - Secondary (Full Load)Parallel 8V, Series 16VCurrent - Output (Max)Parallel 700mA, Series 350mAPrimary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max6 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension47.60mm L x 39.60mm WHeight - Seated (Max)21.60mm	Manufacturer	Tamura
Package-Series3FLTypeLaminated CoreVoltage - Primary115V, 230VVoltage - Secondary (Full Load)Parallel 8V, Series 16VCurrent - Output (Max)Parallel 700mA, Series 350mAPrimary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max6 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension47.60mm L x 39.60mm WHeight - Seated (Max)21.60mm	Category	Transformers
Series3FLTypeLaminated CoreVoltage - Primary115V, 230VVoltage - Secondary (Full Load)Parallel 8V, Series 16VCurrent - Output (Max)Parallel 700mA, Series 350mAPrimary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max6 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension47.60mm L x 39.60mm WHeight - Seated (Max)21.60mm		Power Transformers
TypeLaminated CoreVoltage - Primary115V, 230VVoltage - Secondary (Full Load)Parallel 8V, Series 16VCurrent - Output (Max)Parallel 700mA, Series 350mAPrimary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max6 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension47.60mm L x 39.60mm WHeight - Seated (Max)21.60mm	Package	-
NVoltage - Primary115V, 230VVoltage - Secondary (Full Load)Parallel 8V, Series 16VCurrent - Output (Max)Parallel 700mA, Series 350mAPrimary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max6 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension47.60mm L x 39.60mm WHeight - Seated (Max)21.60mm	Series	3FL
Voltage - Secondary (Full Load)Parallel 8V, Series 16VCurrent - Output (Max)Parallel 700mA, Series 350mAPrimary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max6 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension47.60mm L x 39.60mm WHeight - Seated (Max)21.60mm	Туре	Laminated Core
Current - Output (Max)Parallel 700mA, Series 350mAPrimary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max6 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension47.60mm L x 39.60mm WHeight - Seated (Max)21.60mm	Voltage - Primary	115V, 230V
Primary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max6 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension47.60mm L x 39.60mm WHeight - Seated (Max)21.60mm	Voltage - Secondary (Full Load)	Parallel 8V, Series 16V
Secondary Winding(s)DualCenter TapNoPower - Max6 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension47.60mm L x 39.60mm WHeight - Seated (Max)21.60mm	Current - Output (Max)	Parallel 700mA, Series 350mA
Center TapNoPower - Max6 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension47.60mm L x 39.60mm WHeight - Seated (Max)21.60mm	Primary Winding(s)	Dual
Power - Max6 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension47.60mm L x 39.60mm WHeight - Seated (Max)21.60mm	Secondary Winding(s)	Dual
Mounting TypeThrough HoleTermination StylePC PinSize / Dimension47.60mm L x 39.60mm WHeight - Seated (Max)21.60mm	Center Tap	No
Termination StylePC PinSize / Dimension47.60mm L x 39.60mm WHeight - Seated (Max)21.60mm	Power - Max	6 VA
Size / Dimension47.60mm L x 39.60mm WHeight - Seated (Max)21.60mm	Mounting Type	Through Hole
Height - Seated (Max) 21.60mm	Termination Style	PC Pin
-	Size / Dimension	47.60mm L x 39.60mm W
	Height - Seated (Max)	21.60mm
Voltage - Isolation 1500Vrms	Voltage - Isolation	1500Vrms
Weight -	Weight	-
Report error		Report errors?

3FL16-350 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.



If you have any question about 3FL16-350, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com