

3KP200

3KP200 Information



Part Number	3KP200
Manufacturer	Littelfuse Inc.
Category	Circuit Protection TVS - Diodes
Description	TVS DIODE 200VWM 345.66VC AXIAL
Package	P600, Axial
	For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



3KP200 Specifications

Manufacturer Part Number3KP200ManufacturerLittelfuse Inc.CategoryCircuit ProtectionPackageTVS - DiodesPackageP600, AxialSeries3KPTypeZenerUnidirectional Channels1Bidirectional Channels-Voltage - Reverse Standoff (Typ)200VVoltage - Breakdown (Min)210.6VVoltage - Clamping (Max) @ Ipp345.66VCurrent - Peak Pulse (10/1000µs)9.1A	
CategoryCircuit ProtectionTVS - DiodesPackageP600, AxialSeriesSKPTypeZenerUnidirectional Channels1Bidirectional Channels-Voltage - Reverse Standoff (Typ)200VVoltage - Breakdown (Min)210.6VVoltage - Clamping (Max) @ Ipp345.66VCurrent - Peak Pulse (10/1000µs)9.1A	
TVS - DiodesPackageF000, AxialSeriesP600, AxialStripe3KPTypeZenerUnidirectional Channels1Bidirectional Channels-Voltage - Reverse Standoff (Typ)200VVoltage - Breakdown (Min)210.6VVoltage - Clamping (Max) @ Ipp345.66VCurrent - Peak Pulse (10/1000µs)9.1A	
PackageP600, AxialSeries3KPTypeZenerUnidirectional Channels1Bidirectional Channels-Voltage - Reverse Standoff (Typ)200VVoltage - Breakdown (Min)210.6VVoltage - Clamping (Max) @ Ipp345.66VCurrent - Peak Pulse (10/100µs)9.1A	
Series3KPTypeZenerUnidirectional Channels1Bidirectional Channels-Voltage - Reverse Standoff (Typ)200VVoltage - Breakdown (Min)210.6VVoltage - Clamping (Max) @ Ipp345.66VCurrent - Peak Pulse (10/100µs)9.1A	
TypeZenerUnidirectional Channels1Bidirectional Channels-Voltage - Reverse Standoff (Typ)200VVoltage - Breakdown (Min)210.6VVoltage - Clamping (Max) @ Ipp345.66VCurrent - Peak Pulse (10/100µs)9.1A	
MIUnidirectional Channels1Bidirectional Channels-Voltage - Reverse Standoff (Typ)200VVoltage - Breakdown (Min)210.6VVoltage - Clamping (Max) @ Ipp345.66VCurrent - Peak Pulse (10/1000µs)9.1A	
Bidirectional Channels-Voltage - Reverse Standoff (Typ)200VVoltage - Breakdown (Min)210.6VVoltage - Clamping (Max) @ Ipp345.66VCurrent - Peak Pulse (10/100µs)9.1A	
Voltage - Reverse Standoff (Typ)200VVoltage - Breakdown (Min)210.6VVoltage - Clamping (Max) @ Ipp345.66VCurrent - Peak Pulse (10/1000µs)9.1A	
Voltage - Breakdown (Min)210.6VVoltage - Clamping (Max) @ Ipp345.66VCurrent - Peak Pulse (10/1000µs)9.1A	
Voltage - Clamping (Max) @ Ipp 345.66V Current - Peak Pulse (10/1000µs) 9.1A	
Current - Peak Pulse (10/1000µs) 9.1A	
Power - Peak Pulse 3000W (3kW)	
Power Line Protection No	
Applications General Purpose	
Capacitance @ Frequency -	
Operating Temperature $-55^{\circ}C \sim 175^{\circ}C$ (TJ)	
Mounting Type Through Hole	
Package / Case P600, Axial	
Supplier Device Package P600	
Report	rrors?

3KP200 Guarantees



If you have any question about 3KP200, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com