



## 3SBC1626A2 Information

Heisener.com

Part Number 3SBC1626A2

Manufacturer TE Connectivity Aerospace, Defense and Marine

Category Relays

Signal Relays, Up to 2 Amps

**Description** RELAY GEN PURPOSE DPDT 2A 26.5V

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com





Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## 3SBC1626A2 Specifications

Manufacturer Part Number       3SBC1626A2         Manufacturer       TE Connectivity Aerospace, Defense and Marine         Category       Relays         Signal Relays, Up to 2 Amps         Package       -         Series       Military, MIL-R-39016/37, 3SBC, CII         Relay Type       General Purpose         Coil Type       Non Latching         Coil Current       19.62mA         Coil Voltage       26.5VDC         Contact Form       DPDT (2 Form C)         Contact Rating (Current)       2A         Switching Voltage       115VAC, 28VDC - Max         Turn On Voltage (Max)       13.5 VDC         Turn Off Voltage (Min)       1.5 VDC         Operate Time       4ms         Release Time       6ms         Features       Sealed - Hermetically         Mounting Type       Chassis Mount	-	
Relays Signal Relays, Up to 2 Amps  Package Series Military, MIL-R-39016/37, 3SBC, CII Relay Type General Purpose Coil Type Non Latching Coil Current 19.62mA Coil Voltage 26.5 VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 115 VAC, 28 VDC - Max Turn On Voltage (Max) 13.5 VDC Turn Off Voltage (Min) 1.5 VDC Operate Time 4ms Release Time 6ms Features Sealed - Hermetically	Manufacturer Part Number	3SBC1626A2
Package - Series Military, MIL-R-39016/37, 3SBC, CII Relay Type General Purpose Coil Type Non Latching Coil Current 19.62mA Coil Voltage 26.5VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 115VAC, 28VDC - Max Turn On Voltage (Max) 13.5 VDC Turn Off Voltage (Min) 1.5 VDC Operate Time 4ms Release Time 6ms Features Sealed - Hermetically	Manufacturer	TE Connectivity Aerospace, Defense and Marine
Package - Series Military, MIL-R-39016/37, 3SBC, CII Relay Type General Purpose Coil Type Non Latching Coil Current 19.62mA Coil Voltage 26.5VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 115VAC, 28VDC - Max Turn On Voltage (Max) 13.5 VDC Turn Off Voltage (Min) 1.5 VDC Operate Time 4ms Release Time 6ms Features Sealed - Hermetically	Category	Relays
Series Military, MIL-R-39016/37, 3SBC, CII Relay Type General Purpose Coil Type Non Latching Coil Current 19.62mA Coil Voltage 26.5VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 115VAC, 28VDC - Max Turn On Voltage (Max) 13.5 VDC Turn Off Voltage (Min) 1.5 VDC Operate Time 4ms Release Time 6ms Features Sealed - Hermetically		Signal Relays, Up to 2 Amps
Relay Type General Purpose  Coil Type Non Latching  Coil Current 19.62mA  Coil Voltage 26.5VDC  Contact Form DPDT (2 Form C)  Contact Rating (Current) 2A  Switching Voltage 115VAC, 28VDC - Max  Turn On Voltage (Max) 13.5 VDC  Turn Off Voltage (Min) 1.5 VDC  Operate Time 4ms  Release Time 6ms  Features Sealed - Hermetically	Package	-
Coil Type Non Latching Coil Current 19.62mA Coil Voltage 26.5VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 115VAC, 28VDC - Max Turn On Voltage (Max) 13.5 VDC Turn Off Voltage (Min) 1.5 VDC Operate Time 4ms Release Time 6ms Features Sealed - Hermetically	Series	Military, MIL-R-39016/37, 3SBC, CII
Coil Current 19.62mA Coil Voltage 26.5VDC  Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 115VAC, 28VDC - Max Turn On Voltage (Max) 13.5 VDC  Turn Off Voltage (Min) 1.5 VDC Operate Time 4ms Release Time 6ms Features Sealed - Hermetically	Relay Type	General Purpose
Coil Voltage26.5VDCContact FormDPDT (2 Form C)Contact Rating (Current)2ASwitching Voltage115VAC, 28VDC - MaxTurn On Voltage (Max)13.5 VDCTurn Off Voltage (Min)1.5 VDCOperate Time4msRelease Time6msFeaturesSealed - Hermetically	Coil Type	Non Latching
Contact Form DPDT (2 Form C)  Contact Rating (Current) 2A  Switching Voltage 115VAC, 28VDC - Max  Turn On Voltage (Max) 13.5 VDC  Turn Off Voltage (Min) 1.5 VDC  Operate Time 4ms  Release Time 6ms  Features Sealed - Hermetically	Coil Current	19.62mA
Contact Rating (Current)  Switching Voltage  115VAC, 28VDC - Max  Turn On Voltage (Max)  13.5 VDC  Turn Off Voltage (Min)  1.5 VDC  Operate Time  4ms  Release Time  6ms  Features  Sealed - Hermetically	Coil Voltage	26.5VDC
Switching Voltage 115VAC, 28VDC - Max  Turn On Voltage (Max) 13.5 VDC  Turn Off Voltage (Min) 1.5 VDC  Operate Time 4ms  Release Time 6ms  Features Sealed - Hermetically	Contact Form	DPDT (2 Form C)
Turn On Voltage (Max)  13.5 VDC  Turn Off Voltage (Min)  1.5 VDC  Operate Time  4ms  Release Time  6ms  Features  Sealed - Hermetically	Contact Rating (Current)	2A
Turn Off Voltage (Min)  Operate Time  4ms  Release Time  6ms  Features  Sealed - Hermetically	Switching Voltage	115VAC, 28VDC - Max
Operate Time4msRelease Time6msFeaturesSealed - Hermetically	Turn On Voltage (Max)	13.5 VDC
Release Time 6ms Features Sealed - Hermetically	Turn Off Voltage (Min)	1.5 VDC
Features Sealed - Hermetically	Operate Time	4ms
·	Release Time	6ms
Mounting Type Chassis Mount	Features	Sealed - Hermetically
Chaosis Would	Mounting Type	Chassis Mount
Termination Style Solder Hook	Termination Style	Solder Hook
Report errors?		Report errors?

## 3SBC1626A2 Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

# 3SBC1626A2 Payment Methods





















## 3SBC1626A2 Shipping Methods













If you have any question about 3SBC1626A2, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com