



3SBC1721A2 Information

Heisener.com

Part Number 3SBC1721A2

Manufacturer TE Connectivity Aerospace, Defense and Marine

Category

Signal Relays, Up to 2 Amps

RELAY GENERAL PURPOSE DPDT 2A **Description**

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









3SBC1721A2 Specifications

Manufacturer Part Number 3SBC1721A2 Manufacturer TE Connectivity Aerospace, Defense and Marine Category Relays Package - Series Military, MIL-R-39016/38, 3SBC, CII Relay Type General Purpose Coil Type Non Latching Coil Current - Coil Voltage - Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 115VAC, 28VDC - Max Turn On Voltage (Max) - Turn Off Voltage (Min) - Operate Time - Release Time - Features Sealed - Hermetically Mounting Type - Termination Style -		
CategoryRelaysPackage-SeriesMilitary, MIL-R-39016/38, 3SBC, CIIRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current-Coil Voltage-Contact FormDPDT (2 Form C)Contact Rating (Current)2ASwitching Voltage (Max)-Turn Of Voltage (Max)-Turn Off Voltage (Min)-Operate Time-Release Time-FeaturesSealed - HermeticallyMounting Type-Termination Style-	Manufacturer Part Number	3SBC1721A2
Package-SeriesMilitary, MIL-R-39016/38, 3SBC, CIIRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current-Coil Voltage-Contact FormDPDT (2 Form C)Contact Rating (Current)2ASwitching Voltage115VAC, 28VDC - MaxTurn On Voltage (Max)-Turn Off Voltage (Min)-Operate Time-Release Time-FeaturesSealed - HermeticallyMounting Type-Termination Style-	Manufacturer	TE Connectivity Aerospace, Defense and Marine
Package - Series Military, MIL-R-39016/38, 3SBC, CII Relay Type General Purpose Coil Type Non Latching Coil Current - Coil Voltage - Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 115VAC, 28VDC - Max Turn On Voltage (Max) - Turn Off Voltage (Min) - Operate Time - Release Time - Sealed - Hermetically Mounting Type - Termination Style - Contact Subscript Sub	Category	Relays
SeriesMilitary, MIL-R-39016/38, 3SBC, CIIRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current-Coil Voltage-Contact FormDPDT (2 Form C)Contact Rating (Current)2ASwitching Voltage115VAC, 28VDC - MaxTurn On Voltage (Max)-Turn Off Voltage (Min)-Operate Time-Release Time-FeaturesSealed - HermeticallyMounting Type-Termination Style-		Signal Relays, Up to 2 Amps
Relay TypeGeneral PurposeCoil TypeNon LatchingCoil Current-Coil Voltage-Contact FormDPDT (2 Form C)Contact Rating (Current)2ASwitching Voltage115VAC, 28VDC - MaxTurn On Voltage (Max)-Turn Off Voltage (Min)-Operate Time-Release Time-FeaturesSealed - HermeticallyMounting Type-Termination Style-	Package	-
Coil TypeNon LatchingCoil Current-Coil Voltage-Contact FormDPDT (2 Form C)Contact Rating (Current)2ASwitching Voltage115VAC, 28VDC - MaxTurn On Voltage (Max)-Turn Off Voltage (Min)-Operate Time-Release Time-FeaturesSealed - HermeticallyMounting Type-Termination Style-	Series	Military, MIL-R-39016/38, 3SBC, CII
Coil Current Coil Voltage - Contact Form DPDT (2 Form C) Contact Rating (Current) Switching Voltage 115VAC, 28VDC - Max Turn On Voltage (Max) - Turn Off Voltage (Min) Operate Time Release Time - Features Sealed - Hermetically Mounting Type - Termination Style -	Relay Type	General Purpose
Coil Voltage - DPDT (2 Form C) Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 115VAC, 28VDC - Max Turn On Voltage (Max) - Turn Off Voltage (Min) - Operate Time - Release Time - Features Sealed - Hermetically Mounting Type - Termination Style - Operate Time - Oper	Coil Type	Non Latching
Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 115VAC, 28VDC - Max Turn On Voltage (Max) - Turn Off Voltage (Min) - Operate Time - Release Time - Features Sealed - Hermetically Mounting Type - Termination Style -	Coil Current	-
Contact Rating (Current) Switching Voltage 115VAC, 28VDC - Max Turn On Voltage (Max) - Turn Off Voltage (Min) Operate Time Release Time Features Sealed - Hermetically Mounting Type - Termination Style 2A Switching (Current) - Saled - Max - Substitute of the state	Coil Voltage	-
Switching Voltage 115VAC, 28VDC - Max Turn On Voltage (Max) - Turn Off Voltage (Min) - Operate Time - Release Time - Features Sealed - Hermetically Mounting Type - Termination Style -	Contact Form	DPDT (2 Form C)
Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time Release Time Features Sealed - Hermetically Mounting Type - Termination Style - - - - - - - - - - - - -	Contact Rating (Current)	2A
Turn Off Voltage (Min) Operate Time Release Time - Features Sealed - Hermetically Mounting Type - Termination Style -	Switching Voltage	115VAC, 28VDC - Max
Operate Time - Release Time - Sealed - Hermetically Mounting Type - Termination Style - Sealed - Hermetically - Hermetically - Sealed - Hermetically - Hermetically - Sealed - Hermetically - Hermetic	Turn On Voltage (Max)	-
Release Time - Features Sealed - Hermetically Mounting Type - Termination Style -	Turn Off Voltage (Min)	-
Features Sealed - Hermetically Mounting Type - Termination Style -	Operate Time	-
Mounting Type - Termination Style -	Release Time	-
Termination Style -	Features	Sealed - Hermetically
·	Mounting Type	-
Report errors?	Termination Style	-
		Report errors?

3SBC1721A2 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

3SBC1721A2 Payment Methods





















3SBC1721A2 Shipping Methods













If you have any question about 3SBC1721A2, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com