



3SBC1778A2 Information

Heisener.com

Part Number 3SBC1778A2

Manufacturer TE Connectivity Aerospace, Defense and Marine

Category

Signal Relays, Up to 2 Amps

RELAY GEN PURPOSE DPDT 2A 18V **Description**

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









3SBC1778A2 Specifications

Manufacturer Part Number 3SBC1778A2 Manufacturer TE Connectivity Aerospace, Defense and Marine Category Relays Signal Relays, Up to 2 Amps Package - Series Military, MIL-R-39016/13, 3SBC, CII Relay Type General Purpose Coil Type Non Latching Coil Current 27.66mA Coil Voltage 18VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 115VAC, 28VDC - Max Turn On Voltage (Max) - Turn Off Voltage (Min) - Operate Time 4ms Release Time 4ms Features Sealed - Hermetically Mounting Type Chassis Mount Termination Style Solder Hook		
CategoryRelaysPackage-SeriesMilitary, MIL-R-39016/13, 3SBC, CIIRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current27.66mACoil Voltage18VDCContact FormDPDT (2 Form C)Contact Rating (Current)2ASwitching Voltage115VAC, 28VDC - MaxTurn On Voltage (Max)-Turn Off Voltage (Min)-Operate Time4msRelease Time4msFeaturesSealed - HermeticallyMounting TypeChassis MountTermination StyleSolder Hook	Manufacturer Part Number	3SBC1778A2
Package-SeriesMilitary, MIL-R-39016/13, 3SBC, CIIRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current27.66mACoil Voltage18VDCContact FormDPDT (2 Form C)Contact Rating (Current)2ASwitching Voltage115VAC, 28VDC - MaxTurn On Voltage (Max)-Turn Off Voltage (Min)-Operate Time4msRelease Time4msFeaturesSealed - HermeticallyMounting TypeChassis MountTermination StyleSolder Hook	Manufacturer	TE Connectivity Aerospace, Defense and Marine
Package-SeriesMilitary, MIL-R-39016/13, 3SBC, CIIRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current27.66mACoil Voltage18VDCContact FormDPDT (2 Form C)Contact Rating (Current)2ASwitching Voltage115VAC, 28VDC - MaxTurn On Voltage (Max)-Turn Off Voltage (Min)-Operate Time4msRelease Time4msFeaturesSealed - HermeticallyMounting TypeChassis MountTermination StyleSolder Hook	Category	Relays
SeriesMilitary, MIL-R-39016/13, 3SBC, CIIRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current27.66mACoil Voltage18VDCContact FormDPDT (2 Form C)Contact Rating (Current)2ASwitching Voltage115VAC, 28VDC - MaxTurn On Voltage (Max)-Turn Off Voltage (Min)-Operate Time4msRelease Time4msFeaturesSealed - HermeticallyMounting TypeChassis MountTermination StyleSolder Hook		Signal Relays, Up to 2 Amps
Relay TypeGeneral PurposeCoil TypeNon LatchingCoil Current27.66mACoil Voltage18VDCContact FormDPDT (2 Form C)Contact Rating (Current)2ASwitching Voltage115VAC, 28VDC - MaxTurn On Voltage (Max)-Turn Off Voltage (Min)-Operate Time4msRelease Time4msFeaturesSealed - HermeticallyMounting TypeChassis MountTermination StyleSolder Hook	Package	-
Coil Type Non Latching Coil Current 27.66mA Coil Voltage 18VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 115VAC, 28VDC - Max Turn On Voltage (Max) - Turn Off Voltage (Min) - Operate Time 4ms Release Time 4ms Features Sealed - Hermetically Mounting Type Chassis Mount Termination Style Solder Hook	Series	Military, MIL-R-39016/13, 3SBC, CII
Coil Current 27.66mA Coil Voltage 18VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 115VAC, 28VDC - Max Turn On Voltage (Max) - Turn Off Voltage (Min) - Operate Time 4ms Release Time 4ms Features Sealed - Hermetically Mounting Type Chassis Mount Termination Style Solder Hook	Relay Type	General Purpose
Coil Voltage 18VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 115VAC, 28VDC - Max Turn On Voltage (Max) - Turn Off Voltage (Min) - Operate Time 4ms Release Time 4ms Features Sealed - Hermetically Mounting Type Chassis Mount Termination Style Solder Hook	Coil Type	Non Latching
Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 115VAC, 28VDC - Max Turn On Voltage (Max) - Turn Off Voltage (Min) - Operate Time 4ms Release Time 4ms Release Time 5eatures Sealed - Hermetically Mounting Type Chassis Mount Termination Style Solder Hook	Coil Current	27.66mA
Contact Rating (Current) Switching Voltage 115VAC, 28VDC - Max Turn On Voltage (Max) - Turn Off Voltage (Min) Operate Time 4ms Release Time 4ms Features Sealed - Hermetically Mounting Type Chassis Mount Termination Style Solder Hook	Coil Voltage	18VDC
Switching Voltage 115VAC, 28VDC - Max Turn On Voltage (Max) - Turn Off Voltage (Min) - Operate Time 4ms Release Time 4ms Features Sealed - Hermetically Mounting Type Chassis Mount Termination Style Solder Hook	Contact Form	DPDT (2 Form C)
Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time 4ms Release Time 4ms Features Sealed - Hermetically Mounting Type Chassis Mount Termination Style Solder Hook	Contact Rating (Current)	2A
Turn Off Voltage (Min) Operate Time 4ms Release Time 4ms Features Sealed - Hermetically Mounting Type Chassis Mount Termination Style Solder Hook	Switching Voltage	115VAC, 28VDC - Max
Operate Time 4ms Release Time 4ms Features Sealed - Hermetically Mounting Type Chassis Mount Termination Style Solder Hook	Turn On Voltage (Max)	-
Release Time 4ms Features Sealed - Hermetically Mounting Type Chassis Mount Termination Style Solder Hook	Turn Off Voltage (Min)	-
Features Sealed - Hermetically Mounting Type Chassis Mount Termination Style Solder Hook	Operate Time	4ms
Mounting Type Chassis Mount Termination Style Solder Hook	Release Time	4ms
Termination Style Solder Hook	Features	Sealed - Hermetically
·	Mounting Type	Chassis Mount
	Termination Style	Solder Hook
Report errors?		Report errors?

3SBC1778A2 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

3SBC1778A2 Payment Methods





















3SBC1778A2 Shipping Methods













If you have any question about 3SBC1778A2, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com