



3SBC1787A2 Information

Heisener.com

Part Number 3SBC1787A2

Manufacturer TE Connectivity Aerospace, Defense and Marine

Category Relays

Signal Relays, Up to 2 Amps

Description RELAY GENERAL PURPOSE DPDT 2A 5V

Package

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com





Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









3SBC1787A2 Specifications

Manufacturer Part Number 3SBC1787A2 Manufacturer TE Connectivity Aerospace, Defense and Marine Category Relays Package - Series Military, MIL-R-39016/13, 3SBC, CII Relay Type General Purpose Coil Type Non Latching Coil Current 113.6mA Coil Voltage 5VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 115VAC, 28VDC - Max Turn On Voltage (Max) - Turn Off Voltage (Min) - Operate Time 4ms Release Time 4ms Features Sealed - Hermetically Mounting Type Through Hole Termination Style PC Pin		
CategoryRelaysPackage-SeriesMilitary, MIL-R-39016/13, 3SBC, CIIRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current113.6mACoil Voltage5VDCContact FormDPDT (2 Form C)Contact Rating (Current)2ASwitching Voltage115VAC, 28VDC - MaxTurn On Voltage (Max)-Turn Off Voltage (Min)-Operate Time4msRelease Time4msFeaturesSealed - HermeticallyMounting TypeThrough HoleTermination StylePC Pin	Manufacturer Part Number	3SBC1787A2
Package-SeriesMilitary, MIL-R-39016/13, 3SBC, CIIRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current113.6mACoil Voltage5VDCContact FormDPDT (2 Form C)Contact Rating (Current)2ASwitching Voltage115VAC, 28VDC - MaxTurn On Voltage (Max)-Turn Off Voltage (Min)-Operate Time4msRelease Time4msFeaturesSealed - HermeticallyMounting TypeThrough HoleTermination StylePC Pin	Manufacturer	TE Connectivity Aerospace, Defense and Marine
Package-SeriesMilitary, MIL-R-39016/13, 3SBC, CIIRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current113.6mACoil Voltage5VDCContact FormDPDT (2 Form C)Contact Rating (Current)2ASwitching Voltage115VAC, 28VDC - MaxTurn On Voltage (Max)-Turn Off Voltage (Min)-Operate Time4msRelease Time4msFeaturesSealed - HermeticallyMounting TypeThrough HoleTermination StylePC Pin	Category	Relays
SeriesMilitary, MIL-R-39016/13, 3SBC, CIIRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current113.6mACoil Voltage5VDCContact FormDPDT (2 Form C)Contact Rating (Current)2ASwitching Voltage115VAC, 28VDC - MaxTurn On Voltage (Max)-Turn Off Voltage (Min)-Operate Time4msRelease Time4msFeaturesSealed - HermeticallyMounting TypeThrough HoleTermination StylePC Pin		Signal Relays, Up to 2 Amps
Relay TypeGeneral PurposeCoil TypeNon LatchingCoil Current113.6mACoil Voltage5VDCContact FormDPDT (2 Form C)Contact Rating (Current)2ASwitching Voltage115VAC, 28VDC - MaxTurn On Voltage (Max)-Turn Off Voltage (Min)-Operate Time4msRelease Time4msFeaturesSealed - HermeticallyMounting TypeThrough HoleTermination StylePC Pin	Package	-
Coil Type Non Latching Coil Current 113.6mA Coil Voltage 5VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 115VAC, 28VDC - Max Turn On Voltage (Max) - Turn Off Voltage (Min) - Operate Time 4ms Release Time 4ms Features Sealed - Hermetically Mounting Type Through Hole Termination Style PC Pin	Series	Military, MIL-R-39016/13, 3SBC, CII
Coil Current113.6mACoil Voltage5VDCContact FormDPDT (2 Form C)Contact Rating (Current)2ASwitching Voltage115VAC, 28VDC - MaxTurn On Voltage (Max)-Turn Off Voltage (Min)-Operate Time4msRelease Time4msFeaturesSealed - HermeticallyMounting TypeThrough HoleTermination StylePC Pin	Relay Type	General Purpose
Coil Voltage 5VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 115VAC, 28VDC - Max Turn On Voltage (Max) - Turn Off Voltage (Min) - Operate Time 4ms Release Time 4ms Features Sealed - Hermetically Mounting Type Through Hole Termination Style PC Pin	Coil Type	Non Latching
Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 115VAC, 28VDC - Max Turn On Voltage (Max) - Turn Off Voltage (Min) - Operate Time 4ms Release Time 4ms Release Time 5eatures Sealed - Hermetically Mounting Type Through Hole Termination Style PC Pin	Coil Current	113.6mA
Contact Rating (Current) Switching Voltage 115VAC, 28VDC - Max Turn On Voltage (Max) - Turn Off Voltage (Min) Operate Time 4ms Release Time 4ms Features Sealed - Hermetically Mounting Type Through Hole Termination Style PC Pin	Coil Voltage	5VDC
Switching Voltage 115VAC, 28VDC - Max Turn On Voltage (Max) - Turn Off Voltage (Min) - Operate Time 4ms Release Time 4ms Features Sealed - Hermetically Mounting Type Through Hole Termination Style PC Pin	Contact Form	DPDT (2 Form C)
Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time 4ms Release Time 4ms Features Sealed - Hermetically Mounting Type Through Hole Termination Style PC Pin	Contact Rating (Current)	2A
Turn Off Voltage (Min) Operate Time 4ms Release Time 4ms Features Sealed - Hermetically Mounting Type Through Hole Termination Style PC Pin	Switching Voltage	115VAC, 28VDC - Max
Operate Time 4ms Release Time 4ms Features Sealed - Hermetically Mounting Type Through Hole Termination Style PC Pin	Turn On Voltage (Max)	-
Release Time 4ms Features Sealed - Hermetically Mounting Type Through Hole Termination Style PC Pin	Turn Off Voltage (Min)	-
Features Sealed - Hermetically Mounting Type Through Hole Termination Style PC Pin	Operate Time	4ms
Mounting Type Through Hole Termination Style PC Pin	Release Time	4ms
Termination Style PC Pin	Features	Sealed - Hermetically
,	Mounting Type	Through Hole
Report errors?	Termination Style	PC Pin
Report circles.		Report errors?

3SBC1787A2 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

3SBC1787A2 Payment Methods



















3SBC1787A2 Shipping Methods













If you have any question about 3SBC1787A2, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com