



3SBC2000A2 Information

Heisener.com

Part Number 3SBC2000A2

Manufacturer TE Connectivity Aerospace, Defense and Marine

Category Relays

Signal Relays, Up to 2 Amps

Description RELAY GENERAL PURPOSE DPDT 2A 6V

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









3SBC2000A2 Specifications

Manufacturer Part Number Manufacturer TE Connectivity Aerospace, Defense and Marine Category Relays Signal Relays, Up to 2 Amps Package - Series Military, MIL-R-39016/13, 3SBC, CII Relay Type General Purpose Coil Type Non Latching Coil Current 107.2mA Coil Voltage Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 115VAC, 28VDC - Max Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time 4ms	•	
Category Relays Signal Relays, Up to 2 Amps Package - Series Military, MIL-R-39016/13, 3SBC, CII Relay Type General Purpose Coil Type Non Latching Coil Current 107.2mA Coil Voltage 6VDC Contact Form DPDT (2 Form C) Contact Rating (Current) Switching Voltage 115VAC, 28VDC - Max Turn On Voltage (Max) Turn Off Voltage (Min) -	Manufacturer Part Number	3SBC2000A2
Signal Relays, Up to 2 Amps Package - Series Military, MIL-R-39016/13, 3SBC, CII Relay Type General Purpose Coil Type Non Latching Coil Current 107.2mA Coil Voltage 6VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 115VAC, 28VDC - Max Turn On Voltage (Max) Turn Off Voltage (Min) -	Manufacturer	TE Connectivity Aerospace, Defense and Marine
Package - Military, MIL-R-39016/13, 3SBC, CII Relay Type General Purpose Coil Type Non Latching Coil Current 107.2mA Coil Voltage 6VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 115VAC, 28VDC - Max Turn On Voltage (Max) Turn Off Voltage (Min) -	Category	Relays
Series Military, MIL-R-39016/13, 3SBC, CII Relay Type General Purpose Coil Type Non Latching Coil Current 107.2mA Coil Voltage 6VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 115VAC, 28VDC - Max Turn On Voltage (Max) - Turn Off Voltage (Min) -		Signal Relays, Up to 2 Amps
Relay Type General Purpose Coil Type Non Latching Coil Current 107.2mA Coil Voltage 6VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 115VAC, 28VDC - Max Turn On Voltage (Max) Turn Off Voltage (Min) -	Package	-
Coil Type Non Latching Coil Current 107.2mA Coil Voltage 6VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 115VAC, 28VDC - Max Turn On Voltage (Max) - Turn Off Voltage (Min) -	Series	Military, MIL-R-39016/13, 3SBC, CII
Coil Current 107.2mA Coil Voltage 6VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 115VAC, 28VDC - Max Turn On Voltage (Max) - Turn Off Voltage (Min) -	Relay Type	General Purpose
Coil Voltage 6VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 115VAC, 28VDC - Max Turn On Voltage (Max) - Turn Off Voltage (Min) -	Coil Type	Non Latching
Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 115VAC, 28VDC - Max Turn On Voltage (Max) - Turn Off Voltage (Min) -	Coil Current	107.2mA
Contact Rating (Current) Switching Voltage 115VAC, 28VDC - Max Turn On Voltage (Max) - Turn Off Voltage (Min) -	Coil Voltage	6VDC
Switching Voltage 115VAC, 28VDC - Max Turn On Voltage (Max) - Turn Off Voltage (Min) -	Contact Form	DPDT (2 Form C)
Turn On Voltage (Max) - Turn Off Voltage (Min) -	Contact Rating (Current)	2A
Turn Off Voltage (Min)	Switching Voltage	115VAC, 28VDC - Max
	Turn On Voltage (Max)	-
Operate Time 4ms	Turn Off Voltage (Min)	-
L "	Operate Time	4ms
Release Time 4ms	Release Time	4ms
Features Sealed - Hermetically	Features	Sealed - Hermetically
Mounting Type Through Hole	Mounting Type	Through Hole
Termination Style PC Pin	Termination Style	PC Pin
Report errors?		Report errors?

3SBC2000A2 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

3SBC2000A2 Payment Methods



















3SBC2000A2 Shipping Methods













If you have any question about 3SBC2000A2, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com