



3SBC2091A2 Information



For Reference Only

Part Number 3SBC2091A2

Manufacturer TE Connectivity Aerospace, Defense and Marine

Category Relays

Signal Relays, Up to 2 Amps

Description RELAY GEN PURPOSE DPDT 2A 26.5V

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









3SBC2091A2 Specifications

Manufacturer Part Number 3SBC2091A2 Manufacturer TE Connectivity Aerospace, Defense and Marine Category Relays Signal Relays, Up to 2 Amps Package - Series Military, MIL-R-39016/37, 3SBC, CII Relay Type General Purpose Coil Type Non Latching Coil Current 19.62mA Coil Voltage 26.5VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 28VDC - Nom Turn On Voltage (Max) 13.5 VDC Turn Off Voltage (Min) 1.5 VDC Operate Time 4ms Release Time 6ms Features Sealed - Hermetically Mounting Type Through Hole Termination Style PC Pin		
CategoryRelaysPackage-SeriesMilitary, MIL-R-39016/37, 3SBC, CIIRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current19.62mACoil Voltage26.5VDCContact FormDPDT (2 Form C)Contact Rating (Current)2ASwitching Voltage28VDC - NomTurn On Voltage (Max)13.5 VDCTurn Off Voltage (Min)1.5 VDCOperate Time4msRelease Time6msFeaturesSealed - HermeticallyMounting TypeThrough HoleTermination StylePC Pin	Manufacturer Part Number	3SBC2091A2
Package - Series Military, MIL-R-39016/37, 3SBC, CII Relay Type General Purpose Coil Type Non Latching Coil Current 19.62mA Coil Voltage 26.5VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 28VDC - Nom Turn On Voltage (Max) 13.5 VDC Turn Off Voltage (Min) 1.5 VDC Operate Time 4ms Release Time 6ms Features Sealed - Hermetically Mounting Type Through Hole Termination Style PC Pin	Manufacturer	TE Connectivity Aerospace, Defense and Marine
Package-SeriesMilitary, MIL-R-39016/37, 3SBC, CIIRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current19.62mACoil Voltage26.5VDCContact FormDPDT (2 Form C)Contact Rating (Current)2ASwitching Voltage28VDC - NomTurn On Voltage (Max)13.5 VDCTurn Off Voltage (Min)1.5 VDCOperate Time4msRelease Time6msFeaturesSealed - HermeticallyMounting TypeThrough HoleTermination StylePC Pin	Category	Relays
SeriesMilitary, MIL-R-39016/37, 3SBC, CIIRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current19.62mACoil Voltage26.5VDCContact FormDPDT (2 Form C)Contact Rating (Current)2ASwitching Voltage28VDC - NomTurn On Voltage (Max)13.5 VDCTurn Off Voltage (Min)1.5 VDCOperate Time4msRelease Time6msFeaturesSealed - HermeticallyMounting TypeThrough HoleTermination StylePC Pin		Signal Relays, Up to 2 Amps
Relay TypeGeneral PurposeCoil TypeNon LatchingCoil Current19.62mACoil Voltage26.5VDCContact FormDPDT (2 Form C)Contact Rating (Current)2ASwitching Voltage28VDC - NomTurn On Voltage (Max)13.5 VDCTurn Off Voltage (Min)1.5 VDCOperate Time4msRelease Time6msFeaturesSealed - HermeticallyMounting TypeThrough HoleTermination StylePC Pin	Package	-
Coil Type Non Latching Coil Current 19.62mA Coil Voltage 26.5VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 28VDC - Nom Turn On Voltage (Max) 13.5 VDC Turn Off Voltage (Min) 1.5 VDC Operate Time 4ms Release Time 6ms Features Sealed - Hermetically Mounting Type Through Hole Termination Style PC Pin	Series	Military, MIL-R-39016/37, 3SBC, CII
Coil Current19.62mACoil Voltage26.5VDCContact FormDPDT (2 Form C)Contact Rating (Current)2ASwitching Voltage28VDC - NomTurn On Voltage (Max)13.5 VDCTurn Off Voltage (Min)1.5 VDCOperate Time4msRelease Time6msFeaturesSealed - HermeticallyMounting TypeThrough HoleTermination StylePC Pin	Relay Type	General Purpose
Coil Voltage 26.5VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 28VDC - Nom Turn On Voltage (Max) 13.5 VDC Turn Off Voltage (Min) 1.5 VDC Operate Time 4ms Release Time 6ms Features Sealed - Hermetically Mounting Type Through Hole Termination Style PC Pin	Coil Type	Non Latching
Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 28VDC - Nom Turn On Voltage (Max) 13.5 VDC Turn Off Voltage (Min) 1.5 VDC Operate Time 4ms Release Time 6ms Features Sealed - Hermetically Mounting Type Through Hole Termination Style PC Pin	Coil Current	19.62mA
Contact Rating (Current) Switching Voltage 28VDC - Nom Turn On Voltage (Max) 13.5 VDC Turn Off Voltage (Min) 1.5 VDC Operate Time 4ms Release Time 6ms Features Sealed - Hermetically Mounting Type Through Hole Termination Style PC Pin	Coil Voltage	26.5VDC
Switching Voltage 28VDC - Nom Turn On Voltage (Max) 13.5 VDC Turn Off Voltage (Min) 1.5 VDC Operate Time 4ms Release Time 6ms Features Sealed - Hermetically Mounting Type Through Hole Termination Style PC Pin	Contact Form	DPDT (2 Form C)
Turn On Voltage (Max) 13.5 VDC Turn Off Voltage (Min) 1.5 VDC Operate Time 4ms Release Time 6ms Features Sealed - Hermetically Mounting Type Through Hole Termination Style PC Pin	Contact Rating (Current)	2A
Turn Off Voltage (Min) Operate Time 4ms Release Time 6ms Features Sealed - Hermetically Mounting Type Through Hole Termination Style PC Pin	Switching Voltage	28VDC - Nom
Operate Time 4ms Release Time 6ms Features Sealed - Hermetically Mounting Type Through Hole Termination Style PC Pin	Turn On Voltage (Max)	13.5 VDC
Release Time 6ms Features Sealed - Hermetically Mounting Type Through Hole Termination Style PC Pin	Turn Off Voltage (Min)	1.5 VDC
Features Sealed - Hermetically Mounting Type Through Hole Termination Style PC Pin	Operate Time	4ms
Mounting Type Through Hole Termination Style PC Pin	Release Time	6ms
Termination Style PC Pin	Features	Sealed - Hermetically
•	Mounting Type	Through Hole
Report errors?	Termination Style	PC Pin
		Report errors?

3SBC2091A2 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

3SBC2091A2 Payment Methods





















3SBC2091A2 Shipping Methods













If you have any question about 3SBC2091A2, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com