



### 3SBC5131K1 Information

Heisener.com

Part Number 3SBC5131K1

Manufacturer TE Connectivity Aerospace, Defense and Marine

Category Relays

Signal Relays, Up to 2 Amps

**Description** RELAY GEN PURPOSE DPDT 2A 26.5V

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# 3SBC5131K1 Specifications

Manufacturer Part Number3SBC5131K1ManufacturerTE Connectivity Aerospace, Defense and MarineCategoryRelaysBackage-Series3SBC, CIIRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current19.62mACoil Voltage26.5VDCContact FormDPDT (2 Form C)Contact Rating (Current)2ASwitching Voltage115VAC, 28VDC - MaxTurn On Voltage (Max)-Turn Off Voltage (Min)-Operate Time4msRelease Time4msFeaturesSealed - HermeticallyMounting TypeChassis Mount		
CategoryRelaysPackage-Series3SBC, CIIRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current19.62mACoil Voltage26.5VDCContact FormDPDT (2 Form C)Contact Rating (Current)2ASwitching Voltage115VAC, 28VDC - MaxTurn On Voltage (Max)-Turn Off Voltage (Min)-Operate Time4msRelease Time4msFeaturesSealed - Hermetically	Manufacturer Part Number	3SBC5131K1
Package - Series 3SBC, CII Relay Type General Purpose Coil Type Non Latching Coil Current 19.62mA Coil Voltage 26.5VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 115VAC, 28VDC - Max Turn On Voltage (Max) - Turn Off Voltage (Min) - Operate Time 4ms Release Time 4ms Features Sealed - Hermetically	Manufacturer	TE Connectivity Aerospace, Defense and Marine
Package-Series3SBC, CIIRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current19.62mACoil Voltage26.5VDCContact FormDPDT (2 Form C)Contact Rating (Current)2ASwitching Voltage115VAC, 28VDC - MaxTurn On Voltage (Max)-Turn Off Voltage (Min)-Operate Time4msRelease Time4msFeaturesSealed - Hermetically	Category	Relays
Series 3SBC, CII Relay Type General Purpose Coil Type Non Latching Coil Current 19.62mA Coil Voltage 26.5 VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 115 VAC, 28 VDC - Max Turn On Voltage (Max) - Turn Off Voltage (Min) - Operate Time 4ms Release Time 4ms Features Sealed - Hermetically		Signal Relays, Up to 2 Amps
Relay TypeGeneral PurposeCoil TypeNon LatchingCoil Current19.62mACoil Voltage26.5VDCContact FormDPDT (2 Form C)Contact Rating (Current)2ASwitching Voltage115VAC, 28VDC - MaxTurn On Voltage (Max)-Turn Off Voltage (Min)-Operate Time4msRelease Time4msFeaturesSealed - Hermetically	Package	-
Coil Type Non Latching Coil Current 19.62mA Coil Voltage 26.5VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 115VAC, 28VDC - Max Turn On Voltage (Max) - Turn Off Voltage (Min) - Operate Time 4ms Release Time 4ms Features Sealed - Hermetically	Series	3SBC, CII
Coil Current19.62mACoil Voltage26.5VDCContact FormDPDT (2 Form C)Contact Rating (Current)2ASwitching Voltage115VAC, 28VDC - MaxTurn On Voltage (Max)-Turn Off Voltage (Min)-Operate Time4msRelease Time4msFeaturesSealed - Hermetically	Relay Type	General Purpose
Coil Voltage 26.5VDC  Contact Form DPDT (2 Form C)  Contact Rating (Current) 2A  Switching Voltage 115VAC, 28VDC - Max  Turn On Voltage (Max) -  Turn Off Voltage (Min) -  Operate Time 4ms  Release Time 4ms  Features Sealed - Hermetically	Coil Type	Non Latching
Contact Form DPDT (2 Form C)  Contact Rating (Current) 2A  Switching Voltage 115VAC, 28VDC - Max  Turn On Voltage (Max) -  Turn Off Voltage (Min) -  Operate Time 4ms  Release Time 4ms  Features Sealed - Hermetically	Coil Current	19.62mA
Contact Rating (Current)  Switching Voltage  115VAC, 28VDC - Max  Turn On Voltage (Max)  - Turn Off Voltage (Min)  Operate Time  4ms  Release Time  4ms  Features  Sealed - Hermetically	Coil Voltage	26.5VDC
Switching Voltage 115VAC, 28VDC - Max  Turn On Voltage (Max) -  Turn Off Voltage (Min) -  Operate Time 4ms  Release Time 4ms  Features Sealed - Hermetically	Contact Form	DPDT (2 Form C)
Turn On Voltage (Max)  Turn Off Voltage (Min)  Operate Time  4ms  Release Time  4ms  Features  Sealed - Hermetically	Contact Rating (Current)	2A
Turn Off Voltage (Min)  Operate Time  4ms  Release Time  4ms  Features  Sealed - Hermetically	Switching Voltage	115VAC, 28VDC - Max
Operate Time 4ms Release Time 4ms Features Sealed - Hermetically	Turn On Voltage (Max)	-
Release Time 4ms Features Sealed - Hermetically	Turn Off Voltage (Min)	-
Features Sealed - Hermetically	Operate Time	4ms
·	Release Time	4ms
Mounting Type Chassis Mount	Features	Sealed - Hermetically
	Mounting Type	Chassis Mount
Termination Style Solder Hook	Termination Style	Solder Hook
Report errors?		Report errors?

#### 3SBC5131K1 Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### 3SBC5131K1 Payment Methods



















## 3SBC5131K1 Shipping Methods













If you have any question about 3SBC5131K1, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com