



3SBH5131K2 Information

Heisener.com

Part Number 3SBH5131K2

Manufacturer TE Connectivity Aerospace, Defense and Marine

Category Relays

Signal Relays, Up to 2 Amps

Description RELAY GEN PURPOSE 4PDT 2A 26.5V


Package


For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com





Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









3SBH5131K2 Specifications

Manufacturer Part Number Manufacturer TE Connectivity Aerospace, Defense and Marine Relays Signal Relays, Up to 2 Amps Package - Series 3SBH, CII Relay Type General Purpose Coil Type Non Latching Coil Current 36.8mA Coil Voltage 26.5VDC Contact Form 4PDT (4 Form C) Contact Rating (Current) 2A Switching Voltage 115VAC, 28VDC - Max Turn On Voltage (Max) 1.5 VDC Turn Off Voltage (Min) 1.5 VDC Operate Time Release Time - Features Sealed - Hermetically Mounting Type Chassis Mount Fermination Style Termination Style TE Connectivity Aerospace, Defense and Marine TE Connectivity Aerospace, Defense and Marine Tel Connectivity Aerospace, Defense and Marine 10		
CategoryRelaysSignal Relays, Up to 2 AmpsPackage-Series3SBH, CIIRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current36.8mACoil Voltage26.5VDCContact Form4PDT (4 Form C)Contact Rating (Current)2ASwitching Voltage115VAC, 28VDC - MaxTurn On Voltage (Max)13.5 VDCTurn Off Voltage (Min)1.5 VDCOperate Time-Release Time-FeaturesSealed - HermeticallyMounting TypeChassis MountTermination StyleSolder Hook	Manufacturer Part Number	3SBH5131K2
Package - Series 3SBH, CII Relay Type General Purpose Coil Type Non Latching Coil Current 36.8mA Coil Voltage 26.5VDC Contact Form 4PDT (4 Form C) Contact Rating (Current) 2A Switching Voltage 115VAC, 28VDC - Max Turn On Voltage (Max) 13.5 VDC Turn Off Voltage (Min) 1.5 VDC Operate Time - Release Time - Features Sealed - Hermetically Mounting Type Chassis Mount Termination Style Solder Hook	Manufacturer	TE Connectivity Aerospace, Defense and Marine
Package - Series 3SBH, CII Relay Type General Purpose Coil Type Non Latching Coil Current 36.8mA Coil Voltage 26.5VDC Contact Form 4PDT (4 Form C) Contact Rating (Current) 2A Switching Voltage 115VAC, 28VDC - Max Turn On Voltage (Max) 13.5 VDC Turn Off Voltage (Min) 1.5 VDC Operate Time - Release Time - Features Sealed - Hermetically Mounting Type Chassis Mount Termination Style Solder Hook	Category	Relays
Series3SBH, CIIRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current36.8mACoil Voltage26.5VDCContact Form4PDT (4 Form C)Contact Rating (Current)2ASwitching Voltage115VAC, 28VDC - MaxTurn On Voltage (Max)13.5 VDCTurn Off Voltage (Min)1.5 VDCOperate Time-Release Time-FeaturesSealed - HermeticallyMounting TypeChassis MountTermination StyleSolder Hook		Signal Relays, Up to 2 Amps
Relay TypeGeneral PurposeCoil TypeNon LatchingCoil Current36.8mACoil Voltage26.5VDCContact Form4PDT (4 Form C)Contact Rating (Current)2ASwitching Voltage115VAC, 28VDC - MaxTurn On Voltage (Max)13.5 VDCTurn Off Voltage (Min)1.5 VDCOperate Time-Release Time-FeaturesSealed - HermeticallyMounting TypeChassis MountTermination StyleSolder Hook	Package	-
Coil TypeNon LatchingCoil Current36.8mACoil Voltage26.5VDCContact Form4PDT (4 Form C)Contact Rating (Current)2ASwitching Voltage115VAC, 28VDC - MaxTurn On Voltage (Max)13.5 VDCTurn Off Voltage (Min)1.5 VDCOperate Time-Release Time-FeaturesSealed - HermeticallyMounting TypeChassis MountTermination StyleSolder Hook	Series	3SBH, CII
Coil Current36.8mACoil Voltage26.5VDCContact Form4PDT (4 Form C)Contact Rating (Current)2ASwitching Voltage115VAC, 28VDC - MaxTurn On Voltage (Max)13.5 VDCTurn Off Voltage (Min)1.5 VDCOperate Time-Release Time-FeaturesSealed - HermeticallyMounting TypeChassis MountTermination StyleSolder Hook	Relay Type	General Purpose
Coil Voltage 26.5VDC Contact Form 4PDT (4 Form C) Contact Rating (Current) 2A Switching Voltage 115VAC, 28VDC - Max Turn On Voltage (Max) 13.5 VDC Turn Off Voltage (Min) 1.5 VDC Operate Time - Release Time - Features Sealed - Hermetically Mounting Type Chassis Mount Termination Style Solder Hook	Coil Type	Non Latching
Contact Form 4PDT (4 Form C) Contact Rating (Current) 2A Switching Voltage 115VAC, 28VDC - Max Turn On Voltage (Max) 13.5 VDC Turn Off Voltage (Min) 1.5 VDC Operate Time - Release Time - Features Sealed - Hermetically Mounting Type Chassis Mount Termination Style Solder Hook	Coil Current	36.8mA
Contact Rating (Current) Switching Voltage 115VAC, 28VDC - Max Turn On Voltage (Max) 13.5 VDC Turn Off Voltage (Min) 1.5 VDC Operate Time - Release Time - Features Sealed - Hermetically Mounting Type Chassis Mount Termination Style Solder Hook	Coil Voltage	26.5VDC
Switching Voltage 115VAC, 28VDC - Max Turn On Voltage (Max) 13.5 VDC Turn Off Voltage (Min) 1.5 VDC Operate Time - Release Time - Features Sealed - Hermetically Mounting Type Chassis Mount Termination Style Solder Hook	Contact Form	4PDT (4 Form C)
Turn On Voltage (Max) 13.5 VDC Turn Off Voltage (Min) 1.5 VDC Operate Time - Release Time - Features Sealed - Hermetically Mounting Type Chassis Mount Termination Style Solder Hook	Contact Rating (Current)	2A
Turn Off Voltage (Min) Operate Time - Release Time - Features Sealed - Hermetically Mounting Type Chassis Mount Termination Style Solder Hook	Switching Voltage	115VAC, 28VDC - Max
Operate Time - Release Time - Features Sealed - Hermetically Mounting Type Chassis Mount Termination Style Solder Hook	Turn On Voltage (Max)	13.5 VDC
Release Time - Features Sealed - Hermetically Mounting Type Chassis Mount Termination Style Solder Hook	Turn Off Voltage (Min)	1.5 VDC
Features Sealed - Hermetically Mounting Type Chassis Mount Termination Style Solder Hook	Operate Time	-
Mounting Type Chassis Mount Termination Style Solder Hook	Release Time	-
Termination Style Solder Hook	Features	Sealed - Hermetically
•	Mounting Type	Chassis Mount
Report errors?	Termination Style	Solder Hook
Ł.		Report errors?

3SBH5131K2 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

3SBH5131K2 Payment Methods



















3SBH5131K2 Shipping Methods













If you have any question about 3SBH5131K2, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com