

4-1571920-1 Information

Heisener.com

Part Number 4-1571920-1

Manufacturer TE Connectivity ALCOSWITCH Switches

Category Switches

Toggle Switches

Description SWITCH TOGGLE DP3T 6A 125V

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









4-1571920-1 Specifications

Manufacturer Part Number Manufacturer TE Connectivity ALCOSWITCH Switches Category Switches Toggle Switches Package - Series MTA Green Circuit DP3T Switch Function On-On-On Current Rating 6A (AC), 4A (DC) Voltage Rating - AC Voltage Rating - DC Actuator Type Standard Round Actuator Length Illumination Illumination Non-Illuminated Illumination Type, Color Illumination Voltage (Nominal) Mounting Type Panel Mount Termination Style Panel Cutout Dimensions Bushing Thread Ingress Protection Features Jumper needed to achieve triple throw Report errors?		
CategorySwitchesPackage-SeriesMTA GreenCircuitDP3TSwitch FunctionOn-On-OnCurrent Rating6A (AC), 4A (DC)Voltage Rating - AC125VVoltage Rating - DC28VActuator TypeStandard RoundActuator Length10.49mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 6.40mm DiaBushing Thread1/4-40Ingress Protection-FeaturesJumper needed to achieve triple throw	Manufacturer Part Number	4-1571920-1
Package - Series MTA Green Circuit DP3T Switch Function On-On-On Current Rating 6A (AC), 4A (DC) Voltage Rating - AC 125V Voltage Rating - DC 28V Actuator Type Standard Round Actuator Length 10.49mm Illumination Type, Color - Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 6.40mm Dia Bushing Thread 1/4-40 Ingress Protection - Features MTA (DC) MTA Green MTA Green ATTA Green ATT	Manufacturer	TE Connectivity ALCOSWITCH Switches
Package-SeriesMTA GreenCircuitDP3TSwitch FunctionOn-On-OnCurrent Rating6A (AC), 4A (DC)Voltage Rating - AC125VVoltage Rating - DC28VActuator TypeStandard RoundActuator Length10.49mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 6.40mm DiaBushing Thread1/4-40Ingress Protection-FeaturesJumper needed to achieve triple throw	Category	Switches
SeriesMTA GreenCircuitDP3TSwitch FunctionOn-On-OnCurrent Rating6A (AC), 4A (DC)Voltage Rating - AC125VVoltage Rating - DC28VActuator TypeStandard RoundActuator Length10.49mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 6.40mm DiaBushing Thread1/4-40Ingress Protection-FeaturesJumper needed to achieve triple throw		Toggle Switches
CircuitDP3TSwitch FunctionOn-On-OnCurrent Rating6A (AC), 4A (DC)Voltage Rating - AC125VVoltage Rating - DC28VActuator TypeStandard RoundActuator Length10.49mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 6.40mm DiaBushing Thread1/4-40Ingress Protection-FeaturesJumper needed to achieve triple throw	Package	-
Switch Function On-On-On Current Rating 6A (AC), 4A (DC) Voltage Rating - AC 125V Voltage Rating - DC 28V Actuator Type Standard Round Actuator Length 10.49mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 6.40mm Dia Bushing Thread 1/4-40 Ingress Protection - Features Jumper needed to achieve triple throw	Series	MTA Green
Current Rating 6A (AC), 4A (DC) Voltage Rating - AC 125V Voltage Rating - DC 28V Actuator Type Standard Round Actuator Length 10.49mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 6.40mm Dia Bushing Thread 1/4-40 Ingress Protection - Features Jumper needed to achieve triple throw	Circuit	DP3T
Voltage Rating - AC Voltage Rating - DC 28V Actuator Type Standard Round Actuator Length 10.49mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) Mounting Type Panel Mount Termination Style Panel Cutout Dimensions Circular - 6.40mm Dia Bushing Thread 1/4-40 Ingress Protection - Features 1ush Actuator Length Standard Round Non-Illumination Non-Illuminated 10.49mm Non-Illuminated 10.49mm Circular - 6.40mm Dia 1/4-40 Jumper needed to achieve triple throw	Switch Function	On-On-On
Voltage Rating - DC Actuator Type Standard Round Actuator Length 10.49mm Illumination Non-Illuminated Illumination Type, Color Illumination Voltage (Nominal) Mounting Type Panel Mount Termination Style Panel Cutout Dimensions Circular - 6.40mm Dia Bushing Thread Ingress Protection Features Jumper needed to achieve triple throw	Current Rating	6A (AC), 4A (DC)
Actuator Type Standard Round 10.49mm Illumination Non-Illuminated Illumination Type, Color Illumination Voltage (Nominal) Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 6.40mm Dia Bushing Thread 1/4-40 Ingress Protection - Features Jumper needed to achieve triple throw	Voltage Rating - AC	125V
Actuator Length 10.49mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 6.40mm Dia Bushing Thread 1/4-40 Ingress Protection - Features Jumper needed to achieve triple throw	Voltage Rating - DC	28V
Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 6.40mm Dia Bushing Thread 1/4-40 Ingress Protection - Features Jumper needed to achieve triple throw	Actuator Type	Standard Round
Illumination Type, Color Illumination Voltage (Nominal) Mounting Type Panel Mount Termination Style Panel Cutout Dimensions Circular - 6.40mm Dia Bushing Thread 1/4-40 Ingress Protection Features Jumper needed to achieve triple throw	Actuator Length	10.49mm
Illumination Voltage (Nominal) Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 6.40mm Dia Bushing Thread 1/4-40 Ingress Protection - Features Jumper needed to achieve triple throw	Illumination	Non-Illuminated
Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 6.40mm Dia Bushing Thread 1/4-40 Ingress Protection - Features Jumper needed to achieve triple throw	Illumination Type, Color	-
Termination Style Solder Lug Panel Cutout Dimensions Circular - 6.40mm Dia Bushing Thread 1/4-40 Ingress Protection - Features Jumper needed to achieve triple throw	Illumination Voltage (Nominal)	-
Panel Cutout Dimensions Circular - 6.40mm Dia Bushing Thread 1/4-40 Ingress Protection Features Jumper needed to achieve triple throw	Mounting Type	Panel Mount
Bushing Thread 1/4-40 Ingress Protection - Features Jumper needed to achieve triple throw	Termination Style	Solder Lug
Ingress Protection - Features Jumper needed to achieve triple throw	Panel Cutout Dimensions	Circular - 6.40mm Dia
Features Jumper needed to achieve triple throw	Bushing Thread	1/4-40
	Ingress Protection	-
Report errors?	Features	Jumper needed to achieve triple throw
		Report errors?

4-1571920-1 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

4-1571920-1 Payment Methods



















4-1571920-1 Shipping Methods













If you have any question about 4-1571920-1, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com