

4-1825142-7 Information

Heisener.com

Part Number 4-1825142-7

Manufacturer TE Connectivity ALCOSWITCH Switches

Category Switches

Toggle Switches

Description SWITCH TOGGLE SPDT 5A 120V

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









4-1825142-7 Specifications

Manufacturer Part Number 4-1825142-7 Manufacturer TE Connectivity ALCOSWITCH Switches Category Switches Package - Series Gemini AE Circuit SPDT Switch Function On-Mom Current Rating 5A (AC/DC) Voltage Rating - AC 120V Voltage Rating - DC 28V Actuator Type Standard Round Actuator Length 7.62mm Illumination Non-Illuminated Illumination Voltage (Nominal) - Mounting Type Through Hole, Right Angle Termination Style PC Pin Panel Cutout Dimensions - Bushing Thread Unthreaded Ingress Protection IP67 - Dust Tight, Waterproof Features Process Sealed		
CategorySwitchesPackage-SeriesGemini AECircuitSPDTSwitch FunctionOn-MomCurrent Rating5A (AC/DC)Voltage Rating - AC120VVoltage Rating - DC28VActuator TypeStandard RoundActuator Length7.62mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypeThrough Hole, Right AngleTermination StylePC PinPanel Cutout Dimensions-Bushing ThreadUnthreadedIngress ProtectionIP67 - Dust Tight, WaterproofFeaturesProcess Sealed	Manufacturer Part Number	4-1825142-7
Package - Series Gemini AE Circuit SPDT Switch Function On-Mom Current Rating 5A (AC/DC) Voltage Rating - AC 120V Voltage Rating - DC 28V Actuator Type Standard Round Actuator Length 7.62mm Illumination Type, Color - Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Through Hole, Right Angle Termination Style PC Pin Panel Cutout Dimensions - Bushing Thread Unthreaded Ingress Protection IP67 - Dust Tight, Waterproof Features Process Sealed	Manufacturer	TE Connectivity ALCOSWITCH Switches
Package - Series Gemini AE Circuit SPDT Switch Function On-Mom Current Rating 5A (AC/DC) Voltage Rating - AC 120V Voltage Rating - DC 28V Actuator Type Standard Round Actuator Length 7.62mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Through Hole, Right Angle Termination Style PC Pin Panel Cutout Dimensions - Bushing Thread Unthreaded Ingress Protection IP67 - Dust Tight, Waterproof Features Process Sealed	Category	Switches
Series Gemini AE Circuit SPDT Switch Function On-Mom Current Rating 5A (AC/DC) Voltage Rating - AC 120V Voltage Rating - DC 28V Actuator Type Standard Round Actuator Length 7.62mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Through Hole, Right Angle Termination Style PC Pin Panel Cutout Dimensions - Bushing Thread Unthreaded Ingress Protection IP67 - Dust Tight, Waterproof Features Process Sealed		Toggle Switches
Circuit SPDT Switch Function On-Mom Current Rating 5A (AC/DC) Voltage Rating - AC 120V Voltage Rating - DC 28V Actuator Type Standard Round Actuator Length 7.62mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Through Hole, Right Angle Termination Style PC Pin Panel Cutout Dimensions - Bushing Thread Unthreaded Ingress Protection IP67 - Dust Tight, Waterproof Features Process Sealed	Package	-
Switch FunctionOn-MomCurrent Rating5A (AC/DC)Voltage Rating - AC120VVoltage Rating - DC28VActuator TypeStandard RoundActuator Length7.62mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypeThrough Hole, Right AngleTermination StylePC PinPanel Cutout Dimensions-Bushing ThreadUnthreadedIngress ProtectionIP67 - Dust Tight, WaterproofFeaturesProcess Sealed	Series	Gemini AE
Current Rating5A (AC/DC)Voltage Rating - AC120VVoltage Rating - DC28VActuator TypeStandard RoundActuator Length7.62mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypeThrough Hole, Right AngleTermination StylePC PinPanel Cutout Dimensions-Bushing ThreadUnthreadedIngress ProtectionIP67 - Dust Tight, WaterproofFeaturesProcess Sealed	Circuit	SPDT
Voltage Rating - AC Voltage Rating - DC 28V Actuator Type Standard Round Actuator Length 7.62mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Through Hole, Right Angle Termination Style PC Pin Panel Cutout Dimensions - Bushing Thread Ingress Protection Features 120V 28V Actuator Length 1020 1030 1040 1050	Switch Function	On-Mom
Voltage Rating - DC Actuator Type Standard Round 7.62mm Illumination Non-Illuminated Illumination Type, Color Illumination Voltage (Nominal) Mounting Type Through Hole, Right Angle Termination Style PC Pin Panel Cutout Dimensions - Bushing Thread Unthreaded Ingress Protection Features Process Sealed	Current Rating	5A (AC/DC)
Actuator Type Standard Round 7.62mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Through Hole, Right Angle Termination Style PC Pin Panel Cutout Dimensions - Bushing Thread Unthreaded Ingress Protection IP67 - Dust Tight, Waterproof Features Process Sealed	Voltage Rating - AC	120V
Actuator Length 7.62mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) Mounting Type Through Hole, Right Angle Termination Style PC Pin Panel Cutout Dimensions - Bushing Thread Unthreaded Ingress Protection IP67 - Dust Tight, Waterproof Features Process Sealed	Voltage Rating - DC	28V
Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Through Hole, Right Angle Termination Style PC Pin Panel Cutout Dimensions - Bushing Thread Unthreaded Ingress Protection IP67 - Dust Tight, Waterproof Features Process Sealed	Actuator Type	Standard Round
Illumination Type, Color Illumination Voltage (Nominal)	Actuator Length	7.62mm
Illumination Voltage (Nominal) Mounting Type Through Hole, Right Angle PC Pin Panel Cutout Dimensions - Bushing Thread Unthreaded Ingress Protection IP67 - Dust Tight, Waterproof Features Process Sealed	Illumination	Non-Illuminated
Mounting Type Through Hole, Right Angle Termination Style PC Pin Panel Cutout Dimensions - Bushing Thread Unthreaded Ingress Protection IP67 - Dust Tight, Waterproof Features Process Sealed	Illumination Type, Color	-
Termination Style PC Pin Panel Cutout Dimensions - Bushing Thread Unthreaded Ingress Protection IP67 - Dust Tight, Waterproof Features Process Sealed	Illumination Voltage (Nominal)	-
Panel Cutout Dimensions - Bushing Thread Unthreaded Ingress Protection IP67 - Dust Tight, Waterproof Features Process Sealed	Mounting Type	Through Hole, Right Angle
Bushing Thread Unthreaded Ingress Protection IP67 - Dust Tight, Waterproof Features Process Sealed	Termination Style	PC Pin
Ingress Protection IP67 - Dust Tight, Waterproof Features Process Sealed	Panel Cutout Dimensions	-
Features Process Sealed	Bushing Thread	Unthreaded
	Ingress Protection	IP67 - Dust Tight, Waterproof
Report errors?	Features	Process Sealed
The part of the same of the sa		Report errors's

4-1825142-7 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

4-1825142-7 Payment Methods



















4-1825142-7 Shipping Methods













If you have any question about 4-1825142-7, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com