

4000-51J15K999

4000-51J15K999 Information

Heisener.com	Part Number Manufacturer Category Description Package	4000-51J15K999 TE Connectivity Potter & Brumfield Relays Transformers Power Transformers XFRMR LAMINATED 75VA CHAS MOUNT - For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



4000-51J15K999 Specifications

Manufacturer TE Connectivity Potter & Brumfield Relays Category Transformers Power Transformers Power Transformers Package - Series 4000, Products Unlimited Type Laminated Core Voltage - Primary 380V, 415V Voltage - Secondary (Full Load) 24V Current - Output (Max) - Primary Winding(s) Single Secondary Winding(s) Single Power - Max 75 VA Mounting Type Chassis Mount Termination Style Wire Leads Size / Dinension 101.60mm L x 63.50mm W Height - Seated (Max) - Weight 24 lbs (1.1kg)		
CategoryTransformersPower TransformersPackagePackageSeries4000, Products UnlimitedTypeLaminated CoreVoltage - Primary380V, 415VVoltage - Secondary (Full Load)24VCurrent - Output (Max)-Primary Winding(s)SingleSecondary Winding(s)SingleCenter TapPower - Max75 VAMounting TypeChassis MountSize / DimensionBilde - Seated (Max)-Voltage - IsolationWeightKeight<	Manufacturer Part Number	4000-51J15K999
PackagePower TransformersPackage-Series4000, Products UnlimitedTypeLaminated CoreVoltage - Primary380V, 415VVoltage - Secondary (Full Load)24VCurrent - Output (Max)-Primary Winding(s)SingleSecondary Winding(s)SingleCenter TapNoPower - Max75 VAMounting TypeChassis MountTermination Style101.60mm Lx 63.50mm WSize / Dimension-Viltage - Isolation-Weight2.4 lbs (1.1kg)	Manufacturer	TE Connectivity Potter & Brumfield Relays
Package-Series4000, Products UnlimitedTypeLaminated CoreVoltage - Primary380V, 415VVoltage - Secondary (Full Load)24VCurrent - Output (Max)-Primary Winding(s)SingleSecondary Winding(s)SingleCenter TapNoPower - Max75 VAMounting TypeChasis MountTermination StyleNir LeadsSize / Dimension101.60mm Lx 63.50mm WHeight - Seated (Max)-Woitge - Isolation24.bls (1.1kg)	Category	Transformers
Series4000, Products UnlimitedTypeLaminated CoreVoltage - Primary380V, 415VVoltage - Secondary (Full Load)24VCurrent - Output (Max)-Primary Winding(s)SingleSecondary Winding(s)SingleCenter TapNoPower - Max75 VAMounting TypeChassis MountTermination StyleWire LeadsSize / Dimension101.60mm L x 63.50mm WHeight - Seated (Max)-Weight2.4 lbs (1.1kg)		Power Transformers
TypeLaminated CoreVoltage - Primary380V, 415VVoltage - Secondary (Full Load)24VCurrent - Output (Max)-Primary Winding(s)SingleSecondary Winding(s)SingleSecondary Winding(s)NoPower - Max75 VAMounting TypeChassis MountTermination Style101.60mm L x 63.50mm WSize / Dimension-Height - Seated (Max)-Weight2.4 lbs (1.1kg)	Package	-
Voltage - Primary380V, 415VVoltage - Secondary (Full Load)24VCurrent - Output (Max)-Primary Winding(s)SingleSecondary Winding(s)SingleCenter TapNoPower - Max75 VAMounting TypeChassis MountTermination StyleWire LeadsSize / Dimension101.60mm L x 63.50mm WHeight - Seated (Max)-Weight2.4 lbs (1.1kg)	Series	4000, Products Unlimited
Voltage - Secondary (Full Load)24VCurrent - Output (Max)-Primary Winding(s)SingleSecondary Winding(s)SingleCenter TapNoPower - Max75 VAMounting TypeChassis MountTermination StyleWire LeadsSize / Dimension101.60mm L x 63.50mm WHeight - Seated (Max)-Voltage - Isolation2.4 lbs (1.1kg)	Туре	Laminated Core
Current - Output (Max)-Primary Winding(s)SingleSecondary Winding(s)SingleCenter TapNoPower - Max75 VAMounting TypeChassis MountTermination StyleWire LeadsSize / Dimension101.60mm L x 63.50mm WHeight - Seated (Max)-Voltage - Isolation2.4 lbs (1.1kg)	Voltage - Primary	380V, 415V
Primary Winding(s)SingleSecondary Winding(s)SingleCenter TapNoPower - Max75 VAMounting TypeChassis MountTermination StyleWire LeadsSize / Dimension101.60mm L x 63.50mm WHeight - Seated (Max)-Voltage - Isolation2.4 lbs (1.1kg)	Voltage - Secondary (Full Load)	24V
Secondary Winding(s)SingleCenter TapNoPower - Max75 VAMounting TypeChassis MountTermination StyleWire LeadsSize / Dimension101.60mm L x 63.50mm WHeight - Seated (Max)-Voltage - Isolation2.4 lbs (1.1kg)	Current - Output (Max)	-
Center TapNoPower - Max75 VAMounting TypeChassis MountTermination StyleWire LeadsSize / Dimension101.60mm L x 63.50mm WHeight - Seated (Max)-Voltage - Isolation-Weight2.4 lbs (1.1kg)	Primary Winding(s)	Single
Power - Max75 VAMounting TypeChassis MountTermination StyleWire LeadsSize / Dimension101.60mm L x 63.50mm WHeight - Seated (Max)-Voltage - Isolation-Weight2.4 lbs (1.1kg)	Secondary Winding(s)	Single
Nounting TypeChassis MountMounting TypeChassis MountTermination StyleWire LeadsSize / Dimension101.60mm L x 63.50mm WHeight - Seated (Max)-Voltage - Isolation-Weight2.4 lbs (1.1kg)	Center Tap	No
Termination StyleWire LeadsSize / Dimension101.60mm L x 63.50mm WHeight - Seated (Max)-Voltage - Isolation-Weight2.4 lbs (1.1kg)	Power - Max	75 VA
Size / Dimension101.60mm L x 63.50mm WHeight - Seated (Max)-Voltage - Isolation-Weight2.4 lbs (1.1kg)	Mounting Type	Chassis Mount
Height - Seated (Max)-Voltage - Isolation-Weight2.4 lbs (1.1kg)	Termination Style	Wire Leads
Voltage - Isolation-Weight2.4 lbs (1.1kg)	Size / Dimension	101.60mm L x 63.50mm W
Weight 2.4 lbs (1.1kg)	Height - Seated (Max)	-
	Voltage - Isolation	-
Report errors?	Weight	2.4 lbs (1.1kg)
		Report errors?

4000-51J15K999 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

4000-51J15K999 Payment Methods





If you have any question about 4000-51J15K999, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com