

400E2C5.5 Information

Heisener.com

Part Number Manufacturer Littelfuse Inc. Category Circuit Protection

Electrical, Specialty Fuses

Description FUSE CRTRDGE 400A 5.5KVAC NONSTD

Package Cartridge, Non-Standard

400E2C5.5

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

For Reference Only

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









400E2C5.5 Specifications

Manufacturer Part Number 400E2C5.5 Manufacturer Littelfuse Inc. Category Circuit Protection Beckage Cartridge, Non-Standard Series POWR-GARD? Fuse Type Cartridge Current Rating 400A Voltage Rating - AC 5500V (5.5kV) Voltage Rating - DC - Response Time - Applications Transformer Protection Features Indicating Class E Approvals - Operating Temperature - Breaking Capacity @ Rated Voltage 80kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 15.875" L x 3.000" W x 6.380" H (403.23mm x 76.20mm x 162.05mm) Report errors?		
Category Circuit Protection Flactrical, Specialty Fuses Package Cartridge, Non-Standard Series POWR-GARD? Fuse Type Cartridge Current Rating 400A Voltage Rating - AC 5500V (5.5kV) Voltage Rating - DC - Response Time - Applications Transformer Protection Features Indicating Class E Approvals - Operating Temperature - Breaking Capacity @ Rated Voltage 80kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 15.875" L x 3.000" W x 6.380" H (403.23mm x 76.20mm x 162.05mm)	Manufacturer Part Number	400E2C5.5
PackageElectrical, Specialty FusesPackageCartridge, Non-StandardSeriesPOWR-GARD?Fuse TypeCartridgeCurrent Rating400AVoltage Rating - AC5500V (5.5kV)Voltage Rating - DC-Response Time-ApplicationsTransformer ProtectionFeaturesIndicatingClassEApprovals-Operating Temperature-Breaking Capacity @ Rated Voltage80kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension15.875" L x 3.000" W x 6.380" H (403.23mm x 76.20mm x 162.05mm)	Manufacturer	Littelfuse Inc.
Package Cartridge, Non-Standard Series POWR-GARD? Fuse Type Cartridge Current Rating 400A Voltage Rating - AC 5500V (5.5kV) Voltage Rating - DC - Response Time - Applications Transformer Protection Features Indicating Class E Approvals - Operating Temperature - Breaking Capacity @ Rated Voltage 80kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 15.875" L x 3.000" W x 6.380" H (403.23mm x 76.20mm x 162.05mm)	Category	Circuit Protection
SeriesPOWR-GARD?Fuse TypeCartridgeCurrent Rating400AVoltage Rating - AC5500V (5.5kV)Voltage Rating - DC-Response Time-ApplicationsTransformer ProtectionFeaturesIndicatingClassEApprovals-Operating Temperature-Breaking Capacity @ Rated Voltage80kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension15.875" L x 3.000" W x 6.380" H (403.23mm x 76.20mm x 162.05mm)		Electrical, Specialty Fuses
Fuse Type Cartridge Current Rating 400A Voltage Rating - AC 5500V (5.5kV) Voltage Rating - DC - Response Time - Applications Transformer Protection Features Indicating Class E Approvals - Operating Temperature - Breaking Capacity @ Rated Voltage 80kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 15.875" L x 3.000" W x 6.380" H (403.23mm x 76.20mm x 162.05mm)	Package	Cartridge, Non-Standard
Current Rating 400A Voltage Rating - AC 5500V (5.5kV) Voltage Rating - DC - Response Time - Applications Transformer Protection Features Indicating Class E Approvals - Operating Temperature - Breaking Capacity @ Rated Voltage 80kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 15.875" L x 3.000" W x 6.380" H (403.23mm x 76.20mm x 162.05mm)	Series	POWR-GARD?
Voltage Rating - AC Voltage Rating - DC Response Time - Applications Features Indicating Class E Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 5500V (5.5kV) 5500V (5.5kV) - Class - Characteristics Indicating Features Features Breaking Capacity @ Rated Voltage BokA Cartridge, Non-Standard 15.875" L x 3.000" W x 6.380" H (403.23mm x 76.20mm x 162.05mm)	Fuse Type	Cartridge
Voltage Rating - DC Response Time - Applications Transformer Protection Features Indicating Class E Approvals - Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension - Class - Cartridge, Non-Standard Size / Dimension	Current Rating	400A
Response Time	Voltage Rating - AC	5500V (5.5kV)
Applications Transformer Protection Features Indicating Class E Approvals - Operating Temperature - Breaking Capacity @ Rated Voltage 80kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 15.875" L x 3.000" W x 6.380" H (403.23mm x 76.20mm x 162.05mm)	Voltage Rating - DC	-
Features Indicating Class E Approvals - Operating Temperature - Breaking Capacity @ Rated Voltage 80kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 15.875" L x 3.000" W x 6.380" H (403.23mm x 76.20mm x 162.05mm)	Response Time	-
Class E Approvals - Operating Temperature - Breaking Capacity @ Rated Voltage 80kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 15.875" L x 3.000" W x 6.380" H (403.23mm x 76.20mm x 162.05mm)	Applications	Transformer Protection
Approvals Operating Temperature Breaking Capacity @ Rated Voltage 80kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 15.875" L x 3.000" W x 6.380" H (403.23mm x 76.20mm x 162.05mm)	Features	Indicating
Operating Temperature Breaking Capacity @ Rated Voltage 80kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 15.875" L x 3.000" W x 6.380" H (403.23mm x 76.20mm x 162.05mm)	Class	E
Breaking Capacity @ Rated Voltage 80kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 15.875" L x 3.000" W x 6.380" H (403.23mm x 76.20mm x 162.05mm)	Approvals	-
Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 15.875" L x 3.000" W x 6.380" H (403.23mm x 76.20mm x 162.05mm)	Operating Temperature	-
Package / Case Cartridge, Non-Standard Size / Dimension 15.875" L x 3.000" W x 6.380" H (403.23mm x 76.20mm x 162.05mm)	Breaking Capacity @ Rated Voltage	80kA
Size / Dimension 15.875" L x 3.000" W x 6.380" H (403.23mm x 76.20mm x 162.05mm)	Mounting Type	Holder
·	Package / Case	Cartridge, Non-Standard
Report errors?	Size / Dimension	15.875" L x 3.000" W x 6.380" H (403.23mm x 76.20mm x 162.05mm)
		Report errors?

400E2C5.5 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

400E2C5.5 Payment Methods



















400E2C5.5 Shipping Methods













If you have any question about 400E2C5.5, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com