



402F25012IDR Information



For Reference Only

Part Number 402F25012IDR

Manufacturer CTS-Frequency Controls

Category Crystals, Oscillators, Resonators

Crystals

Description CRYSTAL 25.0000MHZ 18PF SMD

Package 4-SMD, No Lead

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









402F25012IDR Specifications

Manufacturer Part Number 402F25012IDR Manufacturer CTS-Frequency Controls Category Crystals, Oscillators, Resonators Package 4-SMD, No Lead Series 402 Type MHz Crystal Frequency 25MHz Frequency Stability ±20ppm Frequency Tolerance ±10ppm Load Capacitance 18pF ESR (Equivalent Series Resistance) 100 Ohm Operating Mode Fundamental Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.079" L x 0.063" W (2.00mm x 1.60mm) Height - Seated (Max) 0.022" (0.55mm)	*	
Category Crystals, Oscillators, Resonators Package 4-SMD, No Lead Series 402 Type MHz Crystal Frequency 25MHz Frequency Stability ±20ppm Frequency Tolerance ±10ppm Load Capacitance 18pF ESR (Equivalent Series Resistance) 100 Ohm Operating Mode Fundamental Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.079" L x 0.063" W (2.00mm x 1.60mm) Height - Seated (Max) 0.022" (0.55mm)	Manufacturer Part Number	402F25012IDR
Package 4-SMD, No Lead Series 402 Type MHz Crystal Frequency 25MHz Frequency Stability ±20ppm Frequency Tolerance ±10ppm Load Capacitance 18pF ESR (Equivalent Series Resistance) 100 Ohm Operating Mode Fundamental Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.079" L x 0.063" W (2.00mm x 1.60mm) Height - Seated (Max) 0.022" (0.55mm)	Manufacturer	CTS-Frequency Controls
Package 4-SMD, No Lead Series 402 Type MHz Crystal Frequency 25MHz Frequency Stability ±20ppm Frequency Tolerance ±10ppm Load Capacitance 18pF ESR (Equivalent Series Resistance) 100 Ohm Operating Mode Fundamental Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.079" L x 0.063" W (2.00mm x 1.60mm) Height - Seated (Max) 0.022" (0.55mm)	Category	Crystals, Oscillators, Resonators
Series 402 Type MHz Crystal Frequency 25MHz Frequency Stability ±20ppm Frequency Tolerance ±10ppm Load Capacitance 18pF ESR (Equivalent Series Resistance) 100 Ohm Operating Mode Fundamental Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.079" L x 0.063" W (2.00mm x 1.60mm) Height - Seated (Max) 0.022" (0.55mm)		Crystals
Type MHz Crystal Frequency 25MHz Frequency Stability ±20ppm Frequency Tolerance ±10ppm Load Capacitance 18pF ESR (Equivalent Series Resistance) 100 Ohm Operating Mode Fundamental Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.079" L x 0.063" W (2.00mm x 1.60mm) Height - Seated (Max) 0.022" (0.55mm)	Package	4-SMD, No Lead
Frequency Stability ±20ppm Frequency Tolerance ±10ppm Load Capacitance 18pF ESR (Equivalent Series Resistance) 100 Ohm Operating Mode Fundamental Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.079" L x 0.063" W (2.00mm x 1.60mm) Height - Seated (Max) 0.022" (0.55mm)	Series	402
Frequency Stability ±20ppm Frequency Tolerance ±10ppm Load Capacitance 18pF ESR (Equivalent Series Resistance) 100 Ohm Operating Mode Fundamental Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.079" L x 0.063" W (2.00mm x 1.60mm) Height - Seated (Max) 0.022" (0.55mm)	Туре	MHz Crystal
Frequency Tolerance ±10ppm Load Capacitance 18pF ESR (Equivalent Series Resistance) 100 Ohm Operating Mode Fundamental Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.079" L x 0.063" W (2.00mm x 1.60mm) Height - Seated (Max) 0.022" (0.55mm)	Frequency	25MHz
Load Capacitance 18pF ESR (Equivalent Series Resistance) 100 Ohm Operating Mode Fundamental Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.079" L x 0.063" W (2.00mm x 1.60mm) Height - Seated (Max) 0.022" (0.55mm)	Frequency Stability	±20ppm
ESR (Equivalent Series Resistance) Operating Mode Fundamental Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.079" L x 0.063" W (2.00mm x 1.60mm) Height - Seated (Max)	Frequency Tolerance	±10ppm
Operating Mode Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.079" L x 0.063" W (2.00mm x 1.60mm) Height - Seated (Max) 0.022" (0.55mm)	Load Capacitance	18pF
Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.079" L x 0.063" W (2.00mm x 1.60mm) Height - Seated (Max) 0.022" (0.55mm)	ESR (Equivalent Series Resistance)	100 Ohm
Ratings Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.079" L x 0.063" W (2.00mm x 1.60mm) Height - Seated (Max) 0.022" (0.55mm)	Operating Mode	Fundamental
Mounting TypeSurface MountPackage / Case4-SMD, No LeadSize / Dimension0.079" L x 0.063" W (2.00mm x 1.60mm)Height - Seated (Max)0.022" (0.55mm)	Operating Temperature	-40°C ~ 85°C
Package / Case 4-SMD, No Lead Size / Dimension 0.079" L x 0.063" W (2.00mm x 1.60mm) Height - Seated (Max) 0.022" (0.55mm)	Ratings	-
Size / Dimension 0.079" L x 0.063" W (2.00mm x 1.60mm) Height - Seated (Max) 0.022" (0.55mm)	Mounting Type	Surface Mount
Height - Seated (Max) 0.022" (0.55mm)	Package / Case	4-SMD, No Lead
	Size / Dimension	0.079" L x 0.063" W (2.00mm x 1.60mm)
Report errors?	Height - Seated (Max)	0.022" (0.55mm)
		Report errors?

402F25012IDR Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

402F25012IDR Payment Methods



















402F25012IDR Shipping Methods













If you have any question about 402F25012IDR, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com