



402F26022IJR Information

www.medicale.mo

For Reference Only

Part Number 402F26022IJR

Manufacturer CTS-Frequency Controls

Category Crystals, Oscillators, Resonators

Crystals

Description CRYSTAL 26.0000MHZ 9PF SMD

Package 4-SMD, No Lead

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









402F26022IJR Specifications

Manufacturer Part Number 402F26022IJR Manufacturer CTS-Frequency Controls Category Crystals, Oscillators, Resonators Package 4-SMD, No Lead Series 402 Type MHz Crystal Frequency 26MHz Frequency Stability ±20ppm Frequency Tolerance ±20ppm Load Capacitance 9pF ESR (Equivalent Series Resistance) 100 Ohm Operating Mode Fundamental Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.079" L x 0.063" W (2.00mm x 1.60mm) Height - Seated (Max) 0.022" (0.55mm)	*	
Category Crystals, Oscillators, Resonators Package 4-SMD, No Lead Series 402 Type MHz Crystal Frequency 26MHz Frequency Stability ±20ppm Frequency Tolerance ±20ppm Load Capacitance 9pF ESR (Equivalent Series Resistance) 100 Ohm Operating Mode Fundamental Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.079" L x 0.063" W (2.00mm x 1.60mm) Height - Seated (Max) 0.022" (0.55mm)	Manufacturer Part Number	402F26022IJR
Package 4-SMD, No Lead Series 402 Type MHz Crystal Frequency 26MHz Frequency Stability ±20ppm Frequency Tolerance ±20ppm Load Capacitance 9pF ESR (Equivalent Series Resistance) 100 Ohm Operating Mode Fundamental Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.079" L x 0.063" W (2.00mm x 1.60mm) Height - Seated (Max) 0.022" (0.55mm)	Manufacturer	CTS-Frequency Controls
Package4-SMD, No LeadSeries402TypeMHz CrystalFrequency26MHzFrequency Stability±20ppmFrequency Tolerance±20ppmLoad Capacitance9pFESR (Equivalent Series Resistance)100 OhmOperating ModeFundamentalOperating Temperature-40°C ~ 85°CRatings-Mounting TypeSurface MountPackage / Case4-SMD, No LeadSize / Dimension0.079" L x 0.063" W (2.00mm x 1.60mm)Height - Seated (Max)0.022" (0.55mm)	Category	Crystals, Oscillators, Resonators
Series 402 Type MHz Crystal Frequency 26MHz Frequency Stability ±20ppm Frequency Tolerance ±20ppm Load Capacitance 9pF ESR (Equivalent Series Resistance) 100 Ohm Operating Mode Fundamental Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.079" L x 0.063" W (2.00mm x 1.60mm) Height - Seated (Max) 0.022" (0.55mm)		Crystals
Type MHz Crystal Frequency 26MHz Frequency Stability ±20ppm Frequency Tolerance ±20ppm Load Capacitance 9pF ESR (Equivalent Series Resistance) 100 Ohm Operating Mode Fundamental Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.079" L x 0.063" W (2.00mm x 1.60mm) Height - Seated (Max) 0.022" (0.55mm)	Package	4-SMD, No Lead
Frequency Stability ±20ppm Frequency Tolerance ±20ppm Load Capacitance 9pF ESR (Equivalent Series Resistance) 100 Ohm Operating Mode Fundamental Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.079" L x 0.063" W (2.00mm x 1.60mm) Height - Seated (Max) 0.022" (0.55mm)	Series	402
Frequency Stability ±20ppm Frequency Tolerance ±20ppm Load Capacitance 9pF ESR (Equivalent Series Resistance) 100 Ohm Operating Mode Fundamental Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.079" L x 0.063" W (2.00mm x 1.60mm) Height - Seated (Max) 0.022" (0.55mm)	Туре	MHz Crystal
Frequency Tolerance ±20ppm Load Capacitance 9pF ESR (Equivalent Series Resistance) 100 Ohm Operating Mode Fundamental Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.079" L x 0.063" W (2.00mm x 1.60mm) Height - Seated (Max) 0.022" (0.55mm)	Frequency	26MHz
Load Capacitance9pFESR (Equivalent Series Resistance)100 OhmOperating ModeFundamentalOperating Temperature-40°C ~ 85°CRatings-Mounting TypeSurface MountPackage / Case4-SMD, No LeadSize / Dimension0.079" L x 0.063" W (2.00mm x 1.60mm)Height - Seated (Max)0.022" (0.55mm)	Frequency Stability	±20ppm
ESR (Equivalent Series Resistance) Operating Mode Fundamental Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.079" L x 0.063" W (2.00mm x 1.60mm) Height - Seated (Max) 0.022" (0.55mm)	Frequency Tolerance	±20ppm
Operating ModeFundamentalOperating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Ratings-Mounting TypeSurface MountPackage / Case 4-SMD , No LeadSize / Dimension $0.079^{\circ}\text{L} \times 0.063^{\circ}\text{W} (2.00\text{mm} \times 1.60\text{mm})$ Height - Seated (Max) $0.022^{\circ}\text{(0.55\text{mm})}$	Load Capacitance	9pF
Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.079" L x 0.063" W (2.00mm x 1.60mm) Height - Seated (Max) 0.022" (0.55mm)	ESR (Equivalent Series Resistance)	100 Ohm
Ratings Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.079" L x 0.063" W (2.00mm x 1.60mm) Height - Seated (Max) 0.022" (0.55mm)	Operating Mode	Fundamental
Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.079" L x 0.063" W (2.00mm x 1.60mm) Height - Seated (Max) 0.022" (0.55mm)	Operating Temperature	-40°C ~ 85°C
Package / Case 4-SMD, No Lead Size / Dimension 0.079" L x 0.063" W (2.00mm x 1.60mm) Height - Seated (Max) 0.022" (0.55mm)	Ratings	-
Size / Dimension 0.079" L x 0.063" W (2.00mm x 1.60mm) Height - Seated (Max) 0.022" (0.55mm)	Mounting Type	Surface Mount
Height - Seated (Max) 0.022" (0.55mm)	Package / Case	4-SMD, No Lead
	Size / Dimension	0.079" L x 0.063" W (2.00mm x 1.60mm)
Report errors?	Height - Seated (Max)	0.022" (0.55mm)
		Report errors?

402F26022IJR Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

402F26022IJR Payment Methods





















402F26022IJR Shipping Methods













If you have any question about 402F26022IJR, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com