



402F3001XIAT Information



For Reference Only

Part Number 402F3001XIAT

Manufacturer CTS-Frequency Controls

Category Crystals, Oscillators, Resonators

Crystals

Description CRYSTAL 30.0000MHZ 10PF SMD

Package 4-SMD, No Lead

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









402F3001XIAT Specifications

Manufacturer Part Number 402F3001XIAT Manufacturer CTS-Frequency Controls Category Crystals, Oscillators, Resonators Package 4-SMD, No Lead Series 402 Type MHz Crystal Frequency 30MHz Frequency Stability ±15ppm Frequency Tolerance ±10ppm Load Capacitance 10pF ESR (Equivalent Series Resistance) 80 Ohm Operating Mode Fundamental Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.079" L x 0.063" W (2.00mm x 1.60mm)	*	
Category Crystals, Oscillators, Resonators Crystals Package 4-SMD, No Lead Series 402 Type MHz Crystal Frequency 30MHz Frequency Stability Frequency Tolerance ±15ppm Frequency Tolerance ±10ppm Load Capacitance 10pF ESR (Equivalent Series Resistance) 80 Ohm Operating Mode Fundamental Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead	Manufacturer Part Number	402F3001XIAT
Crystals Package 4-SMD, No Lead Series 402 Type MHz Crystal Frequency 30MHz Frequency Stability ±15ppm Frequency Tolerance ±10ppm Load Capacitance 10pF ESR (Equivalent Series Resistance) 80 Ohm Operating Mode Fundamental Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead	Manufacturer	CTS-Frequency Controls
Package 4-SMD, No Lead Series 402 Type MHz Crystal Frequency 30MHz Frequency Stability ±15ppm Frequency Tolerance ±10ppm Load Capacitance 10pF ESR (Equivalent Series Resistance) 80 Ohm Operating Mode Fundamental Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead	Category	Crystals, Oscillators, Resonators
Series 402 Type MHz Crystal Frequency 30MHz Frequency Stability ±15ppm Frequency Tolerance ±10ppm Load Capacitance 10pF ESR (Equivalent Series Resistance) 80 Ohm Operating Mode Fundamental Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead		Crystals
Type MHz Crystal Frequency 30MHz Frequency Stability ±15ppm Frequency Tolerance ±10ppm Load Capacitance 10pF ESR (Equivalent Series Resistance) 80 Ohm Operating Mode Fundamental Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead	Package	4-SMD, No Lead
Frequency Stability ±15ppm Frequency Tolerance ±10ppm Load Capacitance 10pF ESR (Equivalent Series Resistance) 80 Ohm Operating Mode Fundamental Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead	Series	402
Frequency Stability ±15ppm Frequency Tolerance ±10ppm Load Capacitance 10pF ESR (Equivalent Series Resistance) 80 Ohm Operating Mode Fundamental Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead	Туре	MHz Crystal
Frequency Tolerance ±10ppm Load Capacitance 10pF ESR (Equivalent Series Resistance) 80 Ohm Operating Mode Fundamental Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead	Frequency	30MHz
Load Capacitance 10pF ESR (Equivalent Series Resistance) 80 Ohm Operating Mode Fundamental Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead	Frequency Stability	±15ppm
ESR (Equivalent Series Resistance) Operating Mode Fundamental Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead	Frequency Tolerance	±10ppm
Operating Mode Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead	Load Capacitance	10pF
Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead	ESR (Equivalent Series Resistance)	80 Ohm
Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead	Operating Mode	Fundamental
Mounting Type Surface Mount Package / Case 4-SMD, No Lead	Operating Temperature	-40°C ~ 85°C
Package / Case 4-SMD, No Lead	Ratings	-
	Mounting Type	Surface Mount
Size / Dimension 0.079" L x 0.063" W (2.00mm x 1.60mm)	Package / Case	4-SMD, No Lead
	Size / Dimension	0.079" L x 0.063" W (2.00mm x 1.60mm)
Height - Seated (Max) 0.022" (0.55mm)	Height - Seated (Max)	0.022" (0.55mm)
Report errors?		Report errors?

402F3001XIAT Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

402F3001XIAT Payment Methods



















402F3001XIAT Shipping Methods













If you have any question about 402F3001XIAT, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com