



402F320XXCJT Information



For Reference Only

Part Number 402F320XXCJT

Manufacturer CTS-Frequency Controls

Category Crystals, Oscillators, Resonators

Crystals

Description CRYSTAL 32.0000MHZ 9PF SMD

Package 4-SMD, No Lead

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









402F320XXCJT Specifications

Manufacturer Part Number402F320XXCITManufacturerCTS-Frequency ControlsCategoryCrystals, Oscillators, ResonatorsPackage4-SMD, No LeadSeries402TypeMHz CrystalFrequency32MHzFrequency Stability±15ppmFrequency Tolerance±15ppmLoad Capacitance9pFESR (Equivalent Series Resistance)80 OhmOperating ModeFundamentalOperating Temperature-20°C ~ 70°CRatings-Mounting TypeSurface Mount	*	
Category Crystals, Oscillators, Resonators Crystals Package 4-SMD, No Lead Series 402 Type MHz Crystal Frequency 32MHz Frequency Stability ±15ppm Frequency Tolerance ±15ppm Load Capacitance 9pF ESR (Equivalent Series Resistance) 0perating Mode Fundamental Operating Temperature Ratings - Mounting Type Surface Mount	Manufacturer Part Number	402F320XXCJT
Package 4-SMD, No Lead Series 402 Type MHz Crystal Frequency Stability ±15ppm Frequency Tolerance ±15ppm Load Capacitance 9pF ESR (Equivalent Series Resistance) 80 Ohm Operating Mode Fundamental Operating Temperature -20°C ~ 70°C Ratings - Mounting Type Surface Mount	Manufacturer	CTS-Frequency Controls
Package 4-SMD, No Lead Series 402 Type MHz Crystal Frequency 32MHz Frequency Stability ±15ppm Frequency Tolerance ±15ppm Load Capacitance 9pF ESR (Equivalent Series Resistance) 80 Ohm Operating Mode Fundamental Operating Temperature -20°C ~ 70°C Ratings - Mounting Type Surface Mount	Category	Crystals, Oscillators, Resonators
Series Type MHz Crystal Frequency 32MHz Frequency Stability Frequency Tolerance ±15ppm Load Capacitance 9pF ESR (Equivalent Series Resistance) Operating Mode Fundamental Operating Temperature -20°C ~ 70°C Ratings Mounting Type 402 MHz Crystal 402 MHz Crystal 402 MHz Crystal 402 MHz Crystal 402 402 MHz Crystal 402 402 402 MHz Crystal 402 402 402 402 402 402 402 40		Crystals
Type MHz Crystal Frequency 32MHz Frequency Stability ±15ppm Frequency Tolerance ±15ppm Load Capacitance 9pF ESR (Equivalent Series Resistance) 80 Ohm Operating Mode Fundamental Operating Temperature -20°C ~ 70°C Ratings - Mounting Type Surface Mount	Package	4-SMD, No Lead
Frequency Stability ±15ppm Frequency Tolerance ±15ppm Load Capacitance 9pF ESR (Equivalent Series Resistance) 80 Ohm Operating Mode Fundamental Operating Temperature -20°C ~ 70°C Ratings - Mounting Type Surface Mount	Series	402
Frequency Stability ±15ppm Frequency Tolerance ±15ppm Load Capacitance 9pF ESR (Equivalent Series Resistance) 80 Ohm Operating Mode Fundamental Operating Temperature -20°C ~ 70°C Ratings - Mounting Type Surface Mount	Type	MHz Crystal
Frequency Tolerance ±15ppm Load Capacitance 9pF ESR (Equivalent Series Resistance) 80 Ohm Operating Mode Fundamental Operating Temperature -20°C ~ 70°C Ratings - Mounting Type Surface Mount	Frequency	32MHz
Load Capacitance9pFESR (Equivalent Series Resistance)80 OhmOperating ModeFundamentalOperating Temperature-20°C ~ 70°CRatings-Mounting TypeSurface Mount	Frequency Stability	±15ppm
ESR (Equivalent Series Resistance) Operating Mode Fundamental Operating Temperature -20°C ~ 70°C Ratings - Mounting Type Surface Mount	Frequency Tolerance	±15ppm
Operating ModeFundamentalOperating Temperature $-20^{\circ}\text{C} \sim 70^{\circ}\text{C}$ Ratings-Mounting TypeSurface Mount	Load Capacitance	9pF
Operating Temperature $-20^{\circ}\text{C} \sim 70^{\circ}\text{C}$ Ratings $-$ Mounting Type Surface Mount	ESR (Equivalent Series Resistance)	80 Ohm
Ratings - Mounting Type Surface Mount	Operating Mode	Fundamental
Mounting Type Surface Mount	Operating Temperature	-20°C ~ 70°C
	Ratings	-
	Mounting Type	Surface Mount
Package / Case 4-SMD, No Lead	Package / Case	4-SMD, No Lead
Size / Dimension 0.079" L x 0.063" W (2.00mm x 1.60mm)	Size / Dimension	0.079" L x 0.063" W (2.00mm x 1.60mm)
Height - Seated (Max) 0.022" (0.55mm)	Height - Seated (Max)	0.022" (0.55mm)
Report errors?		Report errors?

402F320XXCJT Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

402F320XXCJT Payment Methods





















402F320XXCJT Shipping Methods













If you have any question about 402F320XXCJT, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com