

4061580000 Information



For Reference Only

Part Number 4061580000 Manufacturer Weidmuller Category Relays

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE SPDT 6A 5V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









4061580000 Specifications

Manufacturer Part Number Manufacturer Weidmuller Relays Power Relays, Over 2 Amps Package - Series Relay Type General Purpose Coil Type Non Latching Coil Current 33.3mA Coil Voltage SyDC Contact Form SPDT (1 Form C) Contact Rating (Current) 6A Switching Voltage 250VAC - Max Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time Release Time Features Mounting Type Through Hole Fermination Style Weidmuller Relays Relays Relays Relays Relays Relays Relays Relays Relays Power Relays, Over 2 Amps August Features - Mounting Type Through Hole Fermination Style		
CategoryRelaysPower Relays, Over 2 AmpsPackage-Series-Relay TypeGeneral PurposeCoil TypeNon LatchingCoil Current33.3mACoil Voltage5VDCContact FormSPDT (1 Form C)Contact Rating (Current)6ASwitching Voltage250VAC - MaxTurn On Voltage (Max)3.3 VDCTurn Off Voltage (Min)1 VDCOperate Time8msRelease Time4msFeatures-Mounting TypeThrough HoleTermination StylePC Pin	Manufacturer Part Number	4061580000
Package - Series - Relays, Over 2 Amps Fackage - General Purpose Coil Type General Purpose Coil Current 33.3mA Coil Voltage 5VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 6A Switching Voltage 250VAC - Max Turn On Voltage (Max) 3.3 VDC Turn Off Voltage (Min) 1 VDC Operate Time 8ms Release Time 4ms Features - Mounting Type Through Hole Termination Style Purpose - Mounting Type Termination Style PC Pin	Manufacturer	Weidmuller
Package-Series-Relay TypeGeneral PurposeCoil TypeNon LatchingCoil Current33.3mACoil Voltage5VDCContact FormSPDT (1 Form C)Contact Rating (Current)6ASwitching Voltage250VAC - MaxTurn On Voltage (Max)3.3 VDCTurn Off Voltage (Min)1 VDCOperate Time8msRelease Time4msFeatures-Mounting TypeThrough HoleTermination StylePC Pin	Category	Relays
Series-Relay TypeGeneral PurposeCoil TypeNon LatchingCoil Current33.3mACoil Voltage5VDCContact FormSPDT (1 Form C)Contact Rating (Current)6ASwitching Voltage250VAC - MaxTurn On Voltage (Max)3.3 VDCTurn Off Voltage (Min)1 VDCOperate Time8msRelease Time4msFeatures-Mounting TypeThrough HoleTermination StylePC Pin		Power Relays, Over 2 Amps
Relay TypeGeneral PurposeCoil TypeNon LatchingCoil Current33.3mACoil Voltage5VDCContact FormSPDT (1 Form C)Contact Rating (Current)6ASwitching Voltage250VAC - MaxTurn On Voltage (Max)3.3 VDCTurn Off Voltage (Min)1 VDCOperate Time8msRelease Time4msFeatures-Mounting TypeThrough HoleTermination StylePC Pin	Package	-
Coil TypeNon LatchingCoil Current33.3mACoil Voltage5VDCContact FormSPDT (1 Form C)Contact Rating (Current)6ASwitching Voltage250VAC - MaxTurn On Voltage (Max)3.3 VDCTurn Off Voltage (Min)1 VDCOperate Time8msRelease Time4msFeatures-Mounting TypeThrough HoleTermination StylePC Pin	Series	-
Coil Current 33.3mA Coil Voltage 5VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 6A Switching Voltage 250VAC - Max Turn On Voltage (Max) 3.3 VDC Turn Off Voltage (Min) 1 VDC Operate Time 8ms Release Time 4ms Features Mounting Type Through Hole Termination Style PC Pin	Relay Type	General Purpose
Coil Voltage 5VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 6A Switching Voltage 250VAC - Max Turn On Voltage (Max) 3.3 VDC Turn Off Voltage (Min) 1 VDC Operate Time 8ms Release Time 4ms Features - Mounting Type Through Hole Termination Style PC Pin	Coil Type	Non Latching
Contact Form SPDT (1 Form C) Contact Rating (Current) 6A Switching Voltage 250VAC - Max Turn On Voltage (Max) 3.3 VDC Turn Off Voltage (Min) 1 VDC Operate Time 8ms Release Time 4ms Features - Mounting Type Through Hole Termination Style PC Pin	Coil Current	33.3mA
Contact Rating (Current) Switching Voltage 250VAC - Max Turn On Voltage (Max) 3.3 VDC Turn Off Voltage (Min) 1 VDC Operate Time 8ms Release Time 4ms Features - Mounting Type Through Hole Termination Style	Coil Voltage	5VDC
Switching Voltage 250VAC - Max Turn On Voltage (Max) 3.3 VDC Turn Off Voltage (Min) 1 VDC Operate Time 8ms Release Time 4ms Features - Mounting Type Through Hole Termination Style PC Pin	Contact Form	SPDT (1 Form C)
Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time 8ms Release Time 4ms Features - Mounting Type Through Hole Termination Style 3.3 VDC 4 WDC 5 WDC 6 WDC 7 WDC 8 WDC 9 WDC 8 WDC 8 WDC 9 W	Contact Rating (Current)	6A
Turn Off Voltage (Min) Operate Time 8ms Release Time 4ms Features - Mounting Type Through Hole Termination Style 1 VDC 8ms 4ms Features - Through Hole PC Pin	Switching Voltage	250VAC - Max
Operate Time 8ms Release Time 4ms Features - Mounting Type Through Hole Termination Style PC Pin	Turn On Voltage (Max)	3.3 VDC
Release Time 4ms Features - Mounting Type Through Hole Termination Style PC Pin	Turn Off Voltage (Min)	1 VDC
Features - Mounting Type Through Hole Termination Style PC Pin	Operate Time	8ms
Mounting Type Through Hole Termination Style PC Pin	Release Time	4ms
Termination Style PC Pin	Features	-
	Mounting Type	Through Hole
Report errors?	Termination Style	PC Pin
Topon on one		Report errors?

4061580000 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

4061580000 Payment Methods



















4061580000 Shipping Methods













If you have any question about 4061580000, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com