

4061620000 Information



For Reference Only

Part Number 4061620000 Manufacturer Weidmuller Category Relays

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE SPDT 6A 48V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









4061620000 Specifications

Manufacturer Part Number 4061620000 Manufacturer Weidmuller Category Relays Power Relays, Over 2 Amps Package - Series - Relay Type General Purpose Coil Type Non Latching Coil Current 4.6mA Coil Voltage 48VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 6A Switching Voltage 250VAC - Max Turn On Voltage (Max) 33.6 VDC Turn Off Voltage (Min) 4.8 VDC Operate Time 8ms Release Time 4ms Features -		
Category Relays Power Relays, Over 2 Amps Package - Series - Relay Type General Purpose Coil Type Non Latching Coil Current 4.6mA Coil Voltage 48VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 6A Switching Voltage 250VAC - Max Turn On Voltage (Max) 33.6 VDC Turn Off Voltage (Min) 4.8 VDC Operate Time 8ms Release Time 4ms	Manufacturer Part Number	4061620000
Package - Series - Relay Type General Purpose Coil Type Non Latching Coil Current 4.6mA Coil Voltage 48VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 6A Switching Voltage 250VAC - Max Turn On Voltage (Max) 33.6 VDC Turn Off Voltage (Min) 4.8 VDC Operate Time 8ms Release Time 4-6	Manufacturer	Weidmuller
Package - Series - Relay Type General Purpose Coil Type Non Latching Coil Current 4.6mA Coil Voltage 48VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 6A Switching Voltage 250VAC - Max Turn On Voltage (Max) 33.6 VDC Turn Off Voltage (Min) 4.8 VDC Operate Time 8ms Release Time 4ms	Category	Relays
Series - Relay Type General Purpose Coil Type Non Latching Coil Current 4.6mA Coil Voltage 48VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 6A Switching Voltage 250VAC - Max Turn On Voltage (Max) 33.6 VDC Turn Off Voltage (Min) 4.8 VDC Operate Time 8ms Release Time 4ms		Power Relays, Over 2 Amps
Relay Type Coil Type Non Latching Coil Current 4.6mA Coil Voltage 48VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 6A Switching Voltage 250VAC - Max Turn On Voltage (Max) 33.6 VDC Turn Off Voltage (Min) Operate Time 8ms Release Time 4ms	Package	-
Coil TypeNon LatchingCoil Current4.6mACoil Voltage48VDCContact FormSPDT (1 Form C)Contact Rating (Current)6ASwitching Voltage250VAC - MaxTurn On Voltage (Max)33.6 VDCTurn Off Voltage (Min)4.8 VDCOperate Time8msRelease Time4ms	Series	-
Coil Current 4.6mA Coil Voltage 48VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 6A Switching Voltage 250VAC - Max Turn On Voltage (Max) 33.6 VDC Turn Off Voltage (Min) 4.8 VDC Operate Time 8ms Release Time 4ms	Relay Type	General Purpose
Coil Voltage 48VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 6A Switching Voltage 250VAC - Max Turn On Voltage (Max) 33.6 VDC Turn Off Voltage (Min) 4.8 VDC Operate Time 8ms Release Time 4ms	Coil Type	Non Latching
Contact Form SPDT (1 Form C) Contact Rating (Current) 6A Switching Voltage 250VAC - Max Turn On Voltage (Max) 33.6 VDC Turn Off Voltage (Min) 4.8 VDC Operate Time 8ms Release Time 4ms	Coil Current	4.6mA
Contact Rating (Current) Switching Voltage 250VAC - Max Turn On Voltage (Max) 33.6 VDC Turn Off Voltage (Min) 4.8 VDC Operate Time 8ms Release Time 4ms	Coil Voltage	48VDC
Switching Voltage 250VAC - Max Turn On Voltage (Max) 33.6 VDC Turn Off Voltage (Min) 4.8 VDC Operate Time 8ms Release Time 4ms	Contact Form	SPDT (1 Form C)
Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time Release Time 4ms 33.6 VDC 4.8 VDC 4ms	Contact Rating (Current)	6A
Turn Off Voltage (Min) Operate Time Release Time 4.8 VDC 8ms 4ms	Switching Voltage	250VAC - Max
Operate Time 8ms Release Time 4ms	Turn On Voltage (Max)	33.6 VDC
Release Time 4ms	Turn Off Voltage (Min)	4.8 VDC
	Operate Time	8ms
Features -	Release Time	4ms
	Features	-
Mounting Type Through Hole	Mounting Type	Through Hole
Termination Style PC Pin	Termination Style	PC Pin
Report errors?		Report errors?

4061620000 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

4061620000 Payment Methods





















4061620000 Shipping Methods













If you have any question about 4061620000, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com