

40ET Information

www.heisener.com

Part Number 40ET Manufacturer Eaton

Category Circuit Protection

Electrical, Specialty Fuses

Description FUSE CARTRIDGE 40A 690VAC/500VDC

Package Cylindrical, Blade Terminal (Bolt)

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









40ET Specifications

Manufacturer Part Number 40ET Manufacturer Eaton Category Circuit Protection Package Cylindrical, Specialty Fuses Package Cylindrical, Blade Terminal (Bolt) Series ET Fuse Type Cartridge Current Rating 40A Voltage Rating - AC 690V Voltage Rating - DC 500V Response Time - Applications Electrical, Industrial Features - Class - Approvals CE, UR Operating Temperature - Breaking Capacity @ Rated Voltage 200kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.673" Dia x 1.890" L (17.10mm x 48.00mm)		
CategoryCircuit ProtectionPackageCylindrical, Specialty FusesSeriesETFuse TypeCartridgeCurrent Rating40AVoltage Rating - AC690VVoltage Rating - DC500VResponse Time-ApplicationsElectrical, IndustrialFeatures-Class-ApprovalsCE, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension0.673" Dia x 1.890" L (17.10mm x 48.00mm)	Manufacturer Part Number	40ET
Electrical, Specialty Fuses Package Cylindrical, Blade Terminal (Bolt) Series ET Fuse Type Cartridge Current Rating 40A Voltage Rating - AC Voltage Rating - DC So0V Response Time -Applications Electrical, Industrial Features -Class -CLass -CLass -CLass -CLass -CB, UR Operating Temperature Breaking Capacity @ Rated Voltage Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Electrical, Industrial Features -CE, UR COperating Temperature -CE, UR COPERATION TO THE MAN AND AND AND AND AND AND AND AND AND A	Manufacturer	Eaton
Package Cylindrical, Blade Terminal (Bolt) Series ET Fuse Type Cartridge Current Rating 40A Voltage Rating - AC 690V Voltage Rating - DC 500V Response Time - Applications Electrical, Industrial Features - Class - Approvals CE, UR Operating Temperature - Breaking Capacity @ Rated Voltage 200kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.673" Dia x 1.890" L (17.10mm x 48.00mm)	Category	Circuit Protection
SeriesETFuse TypeCartridgeCurrent Rating40AVoltage Rating - AC690VVoltage Rating - DC500VResponse Time-ApplicationsElectrical, IndustrialFeatures-Class-ApprovalsCE, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension0.673" Dia x 1.890" L (17.10mm x 48.00mm)		Electrical, Specialty Fuses
Fuse Type Current Rating 40A Voltage Rating - AC 690V Voltage Rating - DC 500V Response Time - Applications Electrical, Industrial Features - Class - Approvals CE, UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Cartridge 690V Converting Capacity @ Rated Voltage CE, UR Colindrical, Blade Terminal (Bolt) Size / Dimension Cartridge 690V Collindrical, Blade Terminal (Bolt) Capacity @ Rated Voltage Collindrical, Blade Terminal (Bolt)	Package	Cylindrical, Blade Terminal (Bolt)
Current Rating Voltage Rating - AC 690V Voltage Rating - DC 500V Response Time - Applications Electrical, Industrial Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Size / Dimension 40A 40A 40A 40A 40A 40A 40A 40	Series	ET
Voltage Rating - AC Voltage Rating - DC SooV Response Time Applications Electrical, Industrial Features - Class - Approvals CE, UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 690V 690V	Fuse Type	Cartridge
Voltage Rating - DC Response Time - Applications Electrical, Industrial Features - Class - Approvals CE, UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Size / Dimension 500V 500V 500V 500V 500V 600V 600	Current Rating	40A
Response Time - Applications Electrical, Industrial - Class - Class - CE, UR Approvals CE, UR Operating Temperature - Streaking Capacity @ Rated Voltage 200kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.673" Dia x 1.890" L (17.10mm x 48.00mm)	Voltage Rating - AC	690V
Applications Electrical, Industrial Features - Class - Approvals CE, UR Operating Temperature - Breaking Capacity @ Rated Voltage 200kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.673" Dia x 1.890" L (17.10mm x 48.00mm)	Voltage Rating - DC	500V
Features - Class - CE, UR Approvals CE, UR Operating Temperature - Ereaking Capacity @ Rated Voltage 200kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.673" Dia x 1.890" L (17.10mm x 48.00mm)	Response Time	-
Class - Approvals CE, UR Operating Temperature - Breaking Capacity @ Rated Voltage 200kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.673" Dia x 1.890" L (17.10mm x 48.00mm)	Applications	Electrical, Industrial
Approvals CE, UR Operating Temperature - Breaking Capacity @ Rated Voltage Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension CE, UR CUR CUR CUR CUR CON CON CON CON CON CON CON CO	Features	-
Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.673" Dia x 1.890" L (17.10mm x 48.00mm)	Class	-
Breaking Capacity @ Rated Voltage 200kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.673" Dia x 1.890" L (17.10mm x 48.00mm)	Approvals	CE, UR
Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.673" Dia x 1.890" L (17.10mm x 48.00mm)	Operating Temperature	-
Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.673" Dia x 1.890" L (17.10mm x 48.00mm)	Breaking Capacity @ Rated Voltage	200kA
Size / Dimension 0.673" Dia x 1.890" L (17.10mm x 48.00mm)	Mounting Type	Bolt Mount
	Package / Case	Cylindrical, Blade Terminal (Bolt)
Report errors?	Size / Dimension	0.673" Dia x 1.890" L (17.10mm x 48.00mm)
		Report errors?

40ET Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

40ET Payment Methods



















40ET Shipping Methods













If you have any question about 40ET, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com