

4114R-2-683 Information



For Reference Only

Part Number 4114R-2-683 Manufacturer Bourns Inc. Category Resistors

Resistor Networks, Arrays

Description RES ARRAY 13 RES 68K OHM 14DIP

Package 14-DIP (0.300", 7.62mm)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









4114R-2-683 Specifications

Manufacturer Part Number 4114R-2-683 Manufacturer Bourns Inc. Category Resistors Package 14-DIP (0.300", 7.62mm) Series 4100R Circuit Type Bussed Resistance (Ohms) 68k Tolerance ±2% Number of Resistors 13 Number of Pins 14 Power Per Element 125mW Temperature Coefficient ±100ppm/°C Operating Temperature -55°C ~ 125°C Applications - Mounting Type Through Hole Package / Case 14-DIP (0.300", 7.62mm) Supplier Device Package 14-DIP Size / Dimension 0.765" L x 0.300" W (19.43mm x 7.62mm) Height - Seated (Max) 0.185" (4.69mm)		
Category Resistors Package 14-DIP (0.300", 7.62mm) Series 4100R Circuit Type Bussed Resistance (Ohms) 68k Tolerance ±2% Number of Resistors 13 Number of Pins 14 Power Per Element 125mW Temperature Coefficient ±100ppm/°C Operating Temperature -55°C ~ 125°C Applications - Mounting Type Through Hole Package / Case 14-DIP (0.300", 7.62mm) Supplier Device Package 14-DIP Size / Dimension 0.765" L x 0.300" W (19.43mm x 7.62mm) Height - Seated (Max) 0.185" (4.69mm)	Manufacturer Part Number	4114R-2-683
Resistor Networks, Arrays Package 14-DIP (0.300", 7.62mm) Series 4100R Circuit Type Bussed Resistance (Ohms) 68k Tolerance ±2% Number of Resistors 13 Number of Pins 14 Power Per Element 125mW Temperature Coefficient ±100ppm/°C Operating Temperature -55°C ~ 125°C Applications - Mounting Type Through Hole Package / Case 14-DIP (0.300", 7.62mm) Supplier Device Package 14-DIP Size / Dimension 0.765" L x 0.300" W (19.43mm x 7.62mm) Height - Seated (Max) 0.185" (4.69mm)	Manufacturer	Bourns Inc.
Package 14-DIP (0.300", 7.62mm) Series 4100R Circuit Type Bussed Resistance (Ohms) 68k Tolerance ±2% Number of Resistors 13 Number of Pins 14 Power Per Element 125mW Temperature Coefficient ±100ppm/°C Operating Temperature -55°C ~ 125°C Applications - Mounting Type Through Hole Package / Case 14-DIP (0.300", 7.62mm) Supplier Device Package 14-DIP Size / Dimension 0.765" L x 0.300" W (19.43mm x 7.62mm) Height - Seated (Max) 0.185" (4.69mm)	Category	Resistors
Series 4100R Circuit Type Bussed Resistance (Ohms) 68k Tolerance ±2% Number of Resistors 13 Number of Pins 14 Power Per Element 125mW Temperature Coefficient ±100ppm/°C Operating Temperature -55°C ~ 125°C Applications - Mounting Type Through Hole Package / Case 14-DIP (0.300", 7.62mm) Supplier Device Package 14-DIP Size / Dimension 0.765" L x 0.300" W (19.43mm x 7.62mm) Height - Seated (Max) 0.185" (4.69mm)		Resistor Networks, Arrays
Circuit Type Bussed Resistance (Ohms) 68k Tolerance ±2% Number of Resistors 13 Number of Pins 14 Power Per Element 125mW Temperature Coefficient ±100ppm/°C Operating Temperature -55°C ~ 125°C Applications - Mounting Type Through Hole Package / Case 14-DIP (0.300", 7.62mm) Supplier Device Package 14-DIP Size / Dimension 0.765" L x 0.300" W (19.43mm x 7.62mm) Height - Seated (Max) 0.185" (4.69mm)	Package	14-DIP (0.300", 7.62mm)
Resistance (Ohms) 68k Tolerance ±2% Number of Resistors 13 Number of Pins 14 Power Per Element 125mW Temperature Coefficient ±100ppm/°C Operating Temperature -55°C ~ 125°C Applications - Mounting Type Through Hole Package / Case 14-DIP (0.300", 7.62mm) Supplier Device Package 14-DIP Size / Dimension 0.765" L x 0.300" W (19.43mm x 7.62mm) Height - Seated (Max) 0.185" (4.69mm)	Series	4100R
Tolerance ±2% Number of Resistors 13 Number of Pins 14 Power Per Element 125mW Temperature Coefficient ±100ppm/°C Operating Temperature -55°C ~ 125°C Applications - Mounting Type Through Hole Package / Case 14-DIP (0.300", 7.62mm) Supplier Device Package 14-DIP Size / Dimension 0.765" L x 0.300" W (19.43mm x 7.62mm) Height - Seated (Max) 0.185" (4.69mm)	Circuit Type	Bussed
Number of Resistors13Number of Pins14Power Per Element125mWTemperature Coefficient±100ppm/°COperating Temperature-55°C ~ 125°CApplications-Mounting TypeThrough HolePackage / Case14-DIP (0.300", 7.62mm)Supplier Device Package14-DIPSize / Dimension0.765" L x 0.300" W (19.43mm x 7.62mm)Height - Seated (Max)0.185" (4.69mm)	Resistance (Ohms)	68k
Number of Pins Power Per Element 125mW Temperature Coefficient ±100ppm/°C Operating Temperature -55°C ~ 125°C Applications - Mounting Type Through Hole Package / Case 14-DIP (0.300", 7.62mm) Supplier Device Package Size / Dimension 0.765" L x 0.300" W (19.43mm x 7.62mm) Height - Seated (Max) 0.185" (4.69mm)	Tolerance	±2%
Power Per Element Temperature Coefficient ±100ppm/°C Operating Temperature -55°C ~ 125°C Applications - Mounting Type Through Hole Package / Case 14-DIP (0.300", 7.62mm) Supplier Device Package 14-DIP Size / Dimension 0.765" L x 0.300" W (19.43mm x 7.62mm) Height - Seated (Max) 0.185" (4.69mm)	Number of Resistors	13
Temperature Coefficient $\pm 100 \text{ppm/}^{\circ}\text{C}$ Operating Temperature $-55^{\circ}\text{C} \sim 125^{\circ}\text{C}$ Applications $-$ Mounting Type Through Hole Package / Case $14\text{-DIP} (0.300^{\circ}, 7.62 \text{mm})$ Supplier Device Package 14-DIP Size / Dimension $0.765^{\circ}\text{L} \times 0.300^{\circ}\text{W} (19.43 \text{mm} \times 7.62 \text{mm})$ Height - Seated (Max) $0.185^{\circ}\text{W} (4.69 \text{mm})$	Number of Pins	14
Operating Temperature -55°C ~ 125°C Applications - Mounting Type Through Hole Package / Case 14-DIP (0.300", 7.62mm) Supplier Device Package 14-DIP Size / Dimension 0.765" L x 0.300" W (19.43mm x 7.62mm) Height - Seated (Max) 0.185" (4.69mm)	Power Per Element	125mW
Applications - Mounting Type Through Hole Package / Case 14-DIP (0.300", 7.62mm) Supplier Device Package 14-DIP Size / Dimension 0.765" L x 0.300" W (19.43mm x 7.62mm) Height - Seated (Max) 0.185" (4.69mm)	Temperature Coefficient	±100ppm/°C
Mounting Type Through Hole Package / Case 14-DIP (0.300", 7.62mm) Supplier Device Package 14-DIP Size / Dimension 0.765" L x 0.300" W (19.43mm x 7.62mm) Height - Seated (Max) 0.185" (4.69mm)	Operating Temperature	-55°C ~ 125°C
Package / Case 14-DIP (0.300", 7.62mm) Supplier Device Package 14-DIP Size / Dimension 0.765" L x 0.300" W (19.43mm x 7.62mm) Height - Seated (Max) 0.185" (4.69mm)	Applications	-
Supplier Device Package 14-DIP Size / Dimension 0.765" L x 0.300" W (19.43mm x 7.62mm) Height - Seated (Max) 0.185" (4.69mm)	Mounting Type	Through Hole
Size / Dimension 0.765" L x 0.300" W (19.43mm x 7.62mm) Height - Seated (Max) 0.185" (4.69mm)	Package / Case	14-DIP (0.300", 7.62mm)
Height - Seated (Max) 0.185" (4.69mm)	Supplier Device Package	14-DIP
	Size / Dimension	0.765" L x 0.300" W (19.43mm x 7.62mm)
Report errors?	Height - Seated (Max)	0.185" (4.69mm)
K.		Report errors?

4114R-2-683 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

4114R-2-683 Payment Methods



















4114R-2-683 Shipping Methods













If you have any question about 4114R-2-683, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com