

4116R-1-104 Information



For Reference Only

Part Number 4116R-1-104 Manufacturer Bourns Inc. Category Resistors

Resistor Networks, Arrays

Description RES ARRAY 8 RES 100K OHM 16DIP

Package 16-DIP (0.300", 7.62mm)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









4116R-1-104 Specifications

Manufacturer Part Number 4116R-1-104 Manufacturer Bourns Inc. Category Resistors Resistor Networks, Arrays Package 16-DIP (0.300", 7.62mm) Series 4100R Circuit Type Isolated Resistance (Ohms) 100k Tolerance ±2% Number of Resistors 8 Number of Pins 16 Power Per Element 250mW Temperature Coefficient ±100ppm/°C Operating Temperature -55°C ~ 125°C Applications - Mounting Type Through Hole Package / Case 16-DIP (0.300", 7.62mm) Supplier Device Package 16-DIP Size / Dimension 0.865" L x 0.300" W (21.97mm x 7.62mm) Height - Seated (Max) 0.185" (4.69mm)		
Category Resistors Package 16-DIP (0.300", 7.62mm) Series 4100R Circuit Type Isolated Resistance (Ohms) 100k Tolerance ±2% Number of Resistors 8 Number of Pins 16 Power Per Element 250mW Temperature Coefficient ±100ppm/°C Operating Temperature -55°C ~ 125°C Applications - Mounting Type Through Hole Package / Case 16-DIP (0.300", 7.62mm) Supplier Device Package 16-DIP Size / Dimension 0.865" L x 0.300" W (21.97mm x 7.62mm) Height - Seated (Max) 0.185" (4.69mm)	Manufacturer Part Number	4116R-1-104
Resistor Networks, Arrays Package 16-DIP (0.300", 7.62mm) Series 4100R Circuit Type Isolated Resistance (Ohms) 100k Tolerance ±2% Number of Resistors 8 Number of Pins 16 Power Per Element 250mW Temperature Coefficient ±100ppm/°C Operating Temperature -55°C ~ 125°C Applications - Mounting Type Through Hole Package / Case 16-DIP (0.300", 7.62mm) Supplier Device Package 16-DIP Size / Dimension 0.865" L x 0.300" W (21.97mm x 7.62mm) Height - Seated (Max) 0.185" (4.69mm)	Manufacturer	Bourns Inc.
Package 16-DIP (0.300", 7.62mm) Series 4100R Circuit Type Isolated Resistance (Ohms) 100k Tolerance ±2% Number of Resistors 8 Number of Pins 16 Power Per Element 250mW Temperature Coefficient ±100ppm/°C Operating Temperature -55°C ~ 125°C Applications - Mounting Type Through Hole Package / Case 16-DIP (0.300", 7.62mm) Supplier Device Package 16-DIP Size / Dimension 0.865" L x 0.300" W (21.97mm x 7.62mm) Height - Seated (Max) 0.185" (4.69mm)	Category	Resistors
Series 4100R Circuit Type Isolated Resistance (Ohms) 100k Tolerance ±2% Number of Resistors 8 Number of Pins 16 Power Per Element 250mW Temperature Coefficient ±100ppm/°C Operating Temperature -55°C ~ 125°C Applications - Mounting Type Through Hole Package / Case 16-DIP (0.300", 7.62mm) Supplier Device Package 16-DIP Size / Dimension 0.865" L x 0.300" W (21.97mm x 7.62mm) Height - Seated (Max) 0.185" (4.69mm)		Resistor Networks, Arrays
Circuit Type Isolated Resistance (Ohms) 100k Tolerance ±2% Number of Resistors 8 Number of Pins 16 Power Per Element 250mW Temperature Coefficient ±100ppm/°C Operating Temperature -55°C ~ 125°C Applications - Mounting Type Through Hole Package / Case 16-DIP (0.300", 7.62mm) Supplier Device Package 16-DIP Size / Dimension 0.865" L x 0.300" W (21.97mm x 7.62mm) Height - Seated (Max) 0.185" (4.69mm)	Package	16-DIP (0.300", 7.62mm)
Resistance (Ohms) 100k Tolerance ±2% Number of Resistors 8 Number of Pins 16 Power Per Element 250mW Temperature Coefficient ±100ppm/°C Operating Temperature -55°C ~ 125°C Applications - Mounting Type Through Hole Package / Case 16-DIP (0.300", 7.62mm) Supplier Device Package 16-DIP Size / Dimension 0.865" L x 0.300" W (21.97mm x 7.62mm) Height - Seated (Max) 0.185" (4.69mm)	Series	4100R
Tolerance ±2% Number of Resistors 8 Number of Pins 16 Power Per Element 250mW Temperature Coefficient ±100ppm/°C Operating Temperature -55°C ~ 125°C Applications - Mounting Type Through Hole Package / Case 16-DIP (0.300", 7.62mm) Supplier Device Package 16-DIP Size / Dimension 0.865" L x 0.300" W (21.97mm x 7.62mm) Height - Seated (Max) 0.185" (4.69mm)	Circuit Type	Isolated
Number of Resistors 8 Number of Pins 16 Power Per Element 250mW Temperature Coefficient ±100ppm/°C Operating Temperature -55°C ~ 125°C Applications - Mounting Type Through Hole Package / Case 16-DIP (0.300", 7.62mm) Supplier Device Package 16-DIP Size / Dimension 0.865" L x 0.300" W (21.97mm x 7.62mm) Height - Seated (Max) 0.185" (4.69mm)	Resistance (Ohms)	100k
Number of Pins Power Per Element 250mW Temperature Coefficient ±100ppm/°C Operating Temperature -55°C ~ 125°C Applications - Mounting Type Through Hole Package / Case 16-DIP (0.300", 7.62mm) Supplier Device Package Size / Dimension 0.865" L x 0.300" W (21.97mm x 7.62mm) Height - Seated (Max) 0.185" (4.69mm)	Tolerance	±2%
Power Per Element 250mW Temperature Coefficient ±100ppm/°C Operating Temperature -55°C ~ 125°C Applications - Mounting Type Through Hole Package / Case 16-DIP (0.300", 7.62mm) Supplier Device Package 16-DIP Size / Dimension 0.865" L x 0.300" W (21.97mm x 7.62mm) Height - Seated (Max) 0.185" (4.69mm)	Number of Resistors	8
Temperature Coefficient $\pm 100 \text{ppm/}^{\circ}\text{C}$ Operating Temperature $-55^{\circ}\text{C} \sim 125^{\circ}\text{C}$ Applications $-$ Mounting Type Through Hole Package / Case $16\text{-DIP} (0.300^{\circ}, 7.62 \text{mm})$ Supplier Device Package 16-DIP Size / Dimension $0.865^{\circ}\text{L} \times 0.300^{\circ}\text{W} (21.97 \text{mm} \times 7.62 \text{mm})$ Height - Seated (Max) $0.185^{\circ}\text{M} (4.69 \text{mm})$	Number of Pins	16
Operating Temperature -55°C ~ 125°C Applications - Mounting Type Through Hole Package / Case 16-DIP (0.300", 7.62mm) Supplier Device Package 16-DIP Size / Dimension 0.865" L x 0.300" W (21.97mm x 7.62mm) Height - Seated (Max) 0.185" (4.69mm)	Power Per Element	250mW
Applications - Mounting Type Through Hole Package / Case 16-DIP (0.300", 7.62mm) Supplier Device Package 16-DIP Size / Dimension 0.865" L x 0.300" W (21.97mm x 7.62mm) Height - Seated (Max) 0.185" (4.69mm)	Temperature Coefficient	±100ppm/°C
Mounting Type Through Hole Package / Case 16-DIP (0.300", 7.62mm) Supplier Device Package 16-DIP Size / Dimension 0.865" L x 0.300" W (21.97mm x 7.62mm) Height - Seated (Max) 0.185" (4.69mm)	Operating Temperature	-55°C ~ 125°C
Package / Case 16-DIP (0.300", 7.62mm) Supplier Device Package 16-DIP Size / Dimension 0.865" L x 0.300" W (21.97mm x 7.62mm) Height - Seated (Max) 0.185" (4.69mm)	Applications	-
Supplier Device Package 16-DIP Size / Dimension 0.865" L x 0.300" W (21.97mm x 7.62mm) Height - Seated (Max) 0.185" (4.69mm)	Mounting Type	Through Hole
Size / Dimension 0.865" L x 0.300" W (21.97mm x 7.62mm) Height - Seated (Max) 0.185" (4.69mm)	Package / Case	16-DIP (0.300", 7.62mm)
Height - Seated (Max) 0.185" (4.69mm)	Supplier Device Package	16-DIP
	Size / Dimension	0.865" L x 0.300" W (21.97mm x 7.62mm)
Report errors?	Height - Seated (Max)	0.185" (4.69mm)
		Report errors?

4116R-1-104 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

4116R-1-104 Payment Methods





















4116R-1-104 Shipping Methods













If you have any question about 4116R-1-104, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com