

4116R-2-153 Information



For Reference Only

Part Number4116R-2-153ManufacturerBourns Inc.CategoryResistors

Resistor Networks, Arrays

Description RES ARRAY 15 RES 15K OHM 16DIP

Package 16-DIP (0.300", 7.62mm)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









4116R-2-153 Specifications

Manufacturer Part Number 4116R-2-153 Manufacturer Bourns Inc. Category Resistors Package 16-DIP (0.300", 7.62mm) Series 4100R Circuit Type Bussed Resistance (Ohms) 15k Tolerance ±2% Number of Resistors 15 Number of Pins 16 Power Per Element 125mW Temperature Coefficient ±100ppm/°C Operating Temperature -55°C ~ 125°C Applications - Mounting Type Through Hole Package / Case 16-DIP (0.300", 7.62mm) Supplier Device Package 16-DIP Size / Dimension 0.865" L x 0.300" W (21.97mm x 7.62mm) Height - Seated (Max) 0.185" (4.69mm)	-	
Category Resistors Package 16-DIP (0.300", 7.62mm) Series 4100R Circuit Type Bussed Resistance (Ohms) 15k Tolerance ±2% Number of Resistors 15 Number of Pins 16 Power Per Element 125mW Temperature Coefficient ±100ppm/°C Operating Temperature -55°C ~ 125°C Applications - Mounting Type Through Hole Package / Case 16-DIP (0.300", 7.62mm) Supplier Device Package 16-DIP (0.300" W (21.97mm x 7.62mm) Size / Dimension 0.865" L x 0.300" W (21.97mm x 7.62mm) Height - Seated (Max) 0.185" (4.69mm)	Manufacturer Part Number	4116R-2-153
Resistor Networks, Arrays Package 16-DIP (0.300", 7.62mm) Series 4100R Circuit Type Bussed Resistance (Ohms) 15k Tolerance ±2% Number of Resistors 15 Number of Pins 16 Power Per Element 125mW Temperature Coefficient ±100ppm/°C Operating Temperature -55°C ~ 125°C Applications - Mounting Type Through Hole Package / Case 16-DIP (0.300", 7.62mm) Supplier Device Package 16-DIP Size / Dimension 0.865" L x 0.300" W (21.97mm x 7.62mm) Height - Seated (Max) 0.185" (4.69mm)	Manufacturer	Bourns Inc.
Package 16-DIP (0.300", 7.62mm) Series 4100R Circuit Type Bussed Resistance (Ohms) 15k Tolerance ±2% Number of Resistors 15 Number of Pins 16 Power Per Element 125mW Temperature Coefficient ±100ppm/°C Operating Temperature -55°C ~ 125°C Applications - Mounting Type Through Hole Package / Case 16-DIP (0.300", 7.62mm) Supplier Device Package 16-DIP Size / Dimension 0.865" L x 0.300" W (21.97mm x 7.62mm) Height - Seated (Max) 0.185" (4.69mm)	Category	Resistors
Series 4100R Circuit Type Bussed Resistance (Ohms) 15k Tolerance ±2% Number of Resistors 15 Number of Pins 16 Power Per Element 125mW Temperature Coefficient ±100ppm/°C Operating Temperature -55°C ~ 125°C Applications - Mounting Type Through Hole Package / Case 16-DIP (0.300", 7.62mm) Supplier Device Package 16-DIP Size / Dimension 0.865" L x 0.300" W (21.97mm x 7.62mm) Height - Seated (Max) 0.185" (4.69mm)		Resistor Networks, Arrays
Circuit TypeBussedResistance (Ohms)15kTolerance±2%Number of Resistors15Number of Pins16Power Per Element125mWTemperature Coefficient±100ppm/°COperating Temperature-55°C ~ 125°CApplications-Mounting TypeThrough HolePackage / Case16-DIP (0.300", 7.62mm)Size / Dimension0.865" L x 0.300" W (21.97mm x 7.62mm)Height - Seated (Max)0.185" (4.69mm)	Package	16-DIP (0.300", 7.62mm)
Resistance (Ohms) 15k Tolerance ±2% Number of Resistors 15 Number of Pins 16 Power Per Element 125mW Temperature Coefficient ±100ppm/°C Operating Temperature -55°C ~ 125°C Applications - Mounting Type Through Hole Package / Case 16-DIP (0.300", 7.62mm) Supplier Device Package 16-DIP Size / Dimension 0.865" L x 0.300" W (21.97mm x 7.62mm) Height - Seated (Max) 0.185" (4.69mm)	Series	4100R
Tolerance ±2% Number of Resistors 15 Number of Pins 16 Power Per Element 125mW Temperature Coefficient ±100ppm/°C Operating Temperature -55°C ~ 125°C Applications - Mounting Type Through Hole Package / Case 16-DIP (0.300", 7.62mm) Supplier Device Package 16-DIP Size / Dimension 0.865" L x 0.300" W (21.97mm x 7.62mm) Height - Seated (Max) 0.185" (4.69mm)	Circuit Type	Bussed
Number of Resistors 15 Number of Pins 16 Power Per Element 125mW Temperature Coefficient 2100ppm/°C Operating Temperature -55°C ~ 125°C Applications - Mounting Type Through Hole Package / Case 16-DIP (0.300", 7.62mm) Supplier Device Package 16-DIP Size / Dimension 0.865" L x 0.300" W (21.97mm x 7.62mm) Height - Seated (Max) 0.185" (4.69mm)	Resistance (Ohms)	15k
Number of Pins 16 Power Per Element 125mW Temperature Coefficient ±100ppm/°C Operating Temperature -55°C ~ 125°C Applications - Mounting Type Through Hole Package / Case 16-DIP (0.300", 7.62mm) Supplier Device Package 16-DIP Size / Dimension 0.865" L x 0.300" W (21.97mm x 7.62mm) Height - Seated (Max) 0.185" (4.69mm)	Tolerance	±2%
Power Per Element 125mW Temperature Coefficient $\pm 100 \text{ppm/}^{\circ}\text{C}$ Operating Temperature $-55^{\circ}\text{C} \sim 125^{\circ}\text{C}$ Applications - Mounting Type Through Hole Package / Case 16-DIP $(0.300^{\circ}, 7.62 \text{mm})$ Supplier Device Package 16-DIP Size / Dimension $0.865^{\circ}\text{L} \times 0.300^{\circ} \text{W} (21.97 \text{mm} \times 7.62 \text{mm})$ Height - Seated (Max) $0.185^{\circ} (4.69 \text{mm})$	Number of Resistors	15
Temperature Coefficient $\pm 100 \text{ppm/}^{\circ}\text{C}$ Operating Temperature $-55^{\circ}\text{C} \sim 125^{\circ}\text{C}$ Applications $-$ Mounting Type Through Hole Package / Case $16\text{-DIP} (0.300^{\circ}, 7.62 \text{mm})$ Supplier Device Package 16-DIP Size / Dimension $0.865^{\circ}\text{L} \times 0.300^{\circ}\text{W} (21.97 \text{mm} \times 7.62 \text{mm})$ Height - Seated (Max) $0.185^{\circ}\text{M} (4.69 \text{mm})$	Number of Pins	16
$ \begin{array}{llllllllllllllllllllllllllllllllllll$	Power Per Element	125mW
Applications - Mounting Type Through Hole Package / Case 16-DIP (0.300", 7.62mm) Supplier Device Package 16-DIP Size / Dimension 0.865" L x 0.300" W (21.97mm x 7.62mm) Height - Seated (Max) 0.185" (4.69mm)	Temperature Coefficient	±100ppm/°C
Mounting Type Through Hole Package / Case 16-DIP (0.300", 7.62mm) Supplier Device Package 16-DIP Size / Dimension 0.865" L x 0.300" W (21.97mm x 7.62mm) Height - Seated (Max) 0.185" (4.69mm)	Operating Temperature	-55°C ~ 125°C
Package / Case 16-DIP (0.300", 7.62mm) Supplier Device Package 16-DIP Size / Dimension 0.865" L x 0.300" W (21.97mm x 7.62mm) Height - Seated (Max) 0.185" (4.69mm)	Applications	-
Supplier Device Package 16-DIP Size / Dimension 0.865" L x 0.300" W (21.97mm x 7.62mm) Height - Seated (Max) 0.185" (4.69mm)	Mounting Type	Through Hole
Size / Dimension 0.865" L x 0.300" W (21.97mm x 7.62mm) Height - Seated (Max) 0.185" (4.69mm)	Package / Case	16-DIP (0.300", 7.62mm)
Height - Seated (Max) 0.185" (4.69mm)	Supplier Device Package	16-DIP
	Size / Dimension	0.865" L x 0.300" W (21.97mm x 7.62mm)
Panort arrors?	Height - Seated (Max)	0.185" (4.69mm)
Report errors:		Report errors?

4116R-2-153 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

4116R-2-153 Payment Methods





















4116R-2-153 Shipping Methods













If you have any question about 4116R-2-153, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com