



### 4116R-3-181/391LF Information



For Reference Only

**Part Number** 4116R-3-181/391LF

Manufacturer Bourns Inc.
Category Resistors

Resistor Networks, Arrays

**Description** RES NTWRK 28 RES MULT OHM 16DIP

**Package** 16-DIP (0.300", 7.62mm)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **4116R-3-181/391LF Specifications**

Manufacturer Part Number         4116R-3-181/391LF           Manufacturer         Bourns Inc.           Category         Resistors           Package         16-DIP (0.300", 7.62mm)           Series         4100R           Circuit Type         Dual Terminator           Resistance (Ohms)         180, 390           Tolerance         ±2%           Number of Resistors         28           Number of Pins         16           Power Per Element         125mW           Temperature Coefficient         ±100ppm/°C           Operating Temperature         -55°C ~ 125°C           Applications         -           Mounting Type         Through Hole           Package / Case         16-DIP (0.300", 7.62mm)           Supplier Device Package         16-DIP           Size / Dimension         0.865" L x 0.300" W (21.97mm x 7.62mm)           Height - Seated (Max)         0.185" (4.69mm)		
Category         Resistors           Package         16-DIP (0.300", 7.62mm)           Series         4100R           Circuit Type         Dual Terminator           Resistance (Ohms)         180, 390           Tolerance         ±2%           Number of Resistors         28           Number of Pins         16           Power Per Element         125mW           Temperature Coefficient         ±100ppm/°C           Operating Temperature         -55°C ~ 125°C           Applications         -           Mounting Type         Through Hole           Package / Case         16-DIP (0.300", 7.62mm)           Supplier Device Package         16-DIP (0.300" W (21.97mm x 7.62mm)           Size / Dimension         0.865" L x 0.300" W (21.97mm x 7.62mm)           Height - Seated (Max)         0.185" (4.69mm)	Manufacturer Part Number	4116R-3-181/391LF
Resistor Networks, Arrays           Package         16-DIP (0.300", 7.62mm)           Series         4100R           Circuit Type         Dual Terminator           Resistance (Ohms)         180, 390           Tolerance         ±2%           Number of Resistors         28           Number of Pins         16           Power Per Element         125mW           Temperature Coefficient         ±100ppm/°C           Operating Temperature         -55°C ~ 125°C           Applications         -           Mounting Type         Through Hole           Package / Case         16-DIP (0.300", 7.62mm)           Supplier Device Package         16-DIP           Size / Dimension         0.865" L x 0.300" W (21.97mm x 7.62mm)           Height - Seated (Max)         0.185" (4.69mm)	Manufacturer	Bourns Inc.
Package         16-DIP (0.300", 7.62mm)           Series         4100R           Circuit Type         Dual Terminator           Resistance (Ohms)         180, 390           Tolerance         ±2%           Number of Resistors         28           Number of Pins         16           Power Per Element         125mW           Temperature Coefficient         ±100ppm/°C           Operating Temperature         -55°C ~ 125°C           Applications         -           Mounting Type         Through Hole           Package / Case         16-DIP (0.300", 7.62mm)           Supplier Device Package         16-DIP           Size / Dimension         0.865" L x 0.300" W (21.97mm x 7.62mm)           Height - Seated (Max)         0.185" (4.69mm)	Category	Resistors
Series         4100R           Circuit Type         Dual Terminator           Resistance (Ohms)         180, 390           Tolerance         ±2%           Number of Resistors         28           Number of Pins         16           Power Per Element         125mW           Temperature Coefficient         ±100ppm/°C           Operating Temperature         -55°C ~ 125°C           Applications         -           Mounting Type         Through Hole           Package / Case         16-DIP (0.300", 7.62mm)           Supplier Device Package         16-DIP           Size / Dimension         0.865" L x 0.300" W (21.97mm x 7.62mm)           Height - Seated (Max)         0.185" (4.69mm)		Resistor Networks, Arrays
Circuit TypeDual TerminatorResistance (Ohms)180, 390Tolerance±2%Number of Resistors28Number of Pins16Power Per Element125mWTemperature Coefficient±100ppm/°COperating Temperature-55°C ~ 125°CApplications-Mounting TypeThrough HolePackage / Case16-DIP (0.300", 7.62mm)Size / Dimension0.865" L x 0.300" W (21.97mm x 7.62mm)Height - Seated (Max)0.185" (4.69mm)	Package	16-DIP (0.300", 7.62mm)
Resistance (Ohms)       180, 390         Tolerance       ±2%         Number of Resistors       28         Number of Pins       16         Power Per Element       125mW         Temperature Coefficient       ±100ppm/°C         Operating Temperature       -55°C ~ 125°C         Applications       -         Mounting Type       Through Hole         Package / Case       16-DIP (0.300", 7.62mm)         Supplier Device Package       16-DIP         Size / Dimension       0.865" L x 0.300" W (21.97mm x 7.62mm)         Height - Seated (Max)       0.185" (4.69mm)	Series	4100R
Tolerance       ±2%         Number of Resistors       28         Number of Pins       16         Power Per Element       125mW         Temperature Coefficient       ±100ppm/°C         Operating Temperature       -55°C ~ 125°C         Applications       -         Mounting Type       Through Hole         Package / Case       16-DIP (0.300", 7.62mm)         Supplier Device Package       16-DIP         Size / Dimension       0.865" L x 0.300" W (21.97mm x 7.62mm)         Height - Seated (Max)       0.185" (4.69mm)	Circuit Type	Dual Terminator
Number of Resistors28Number of Pins16Power Per Element125mWTemperature Coefficient±100ppm/°COperating Temperature-55°C ~ 125°CApplications-Mounting TypeThrough HolePackage / Case16-DIP (0.300", 7.62mm)Supplier Device Package16-DIPSize / Dimension0.865" L x 0.300" W (21.97mm x 7.62mm)Height - Seated (Max)0.185" (4.69mm)	Resistance (Ohms)	180, 390
Number of Pins  16  Power Per Element  125mW  Temperature Coefficient  ±100ppm/°C  Operating Temperature  -55°C ~ 125°C  Applications  -  Mounting Type  Through Hole  Package / Case  16-DIP (0.300", 7.62mm)  Supplier Device Package  16-DIP  Size / Dimension  0.865" L x 0.300" W (21.97mm x 7.62mm)  Height - Seated (Max)  0.185" (4.69mm)	Tolerance	±2%
Power Per Element  125mW  Temperature Coefficient  ±100ppm/°C  Operating Temperature  -55°C ~ 125°C  Applications  -  Mounting Type  Through Hole  Package / Case  16-DIP (0.300", 7.62mm)  Supplier Device Package  16-DIP  Size / Dimension  0.865" L x 0.300" W (21.97mm x 7.62mm)  Height - Seated (Max)  0.185" (4.69mm)	Number of Resistors	28
Temperature Coefficient ±100ppm/°C  Operating Temperature -55°C ~ 125°C  Applications -  Mounting Type Through Hole  Package / Case 16-DIP (0.300", 7.62mm)  Supplier Device Package 16-DIP  Size / Dimension 0.865" L x 0.300" W (21.97mm x 7.62mm)  Height - Seated (Max) 0.185" (4.69mm)	Number of Pins	16
Operating Temperature  -55°C ~ 125°C  Applications  -  Mounting Type  Through Hole  Package / Case  16-DIP (0.300", 7.62mm)  Supplier Device Package  16-DIP  Size / Dimension  0.865" L x 0.300" W (21.97mm x 7.62mm)  Height - Seated (Max)  0.185" (4.69mm)	Power Per Element	125mW
Applications - Mounting Type Through Hole  Package / Case 16-DIP (0.300", 7.62mm)  Supplier Device Package 16-DIP  Size / Dimension 0.865" L x 0.300" W (21.97mm x 7.62mm)  Height - Seated (Max) 0.185" (4.69mm)	Temperature Coefficient	±100ppm/°C
Mounting Type Through Hole Package / Case 16-DIP (0.300", 7.62mm) Supplier Device Package 16-DIP Size / Dimension 0.865" L x 0.300" W (21.97mm x 7.62mm) Height - Seated (Max) 0.185" (4.69mm)	Operating Temperature	-55°C ~ 125°C
Package / Case       16-DIP (0.300", 7.62mm)         Supplier Device Package       16-DIP         Size / Dimension       0.865" L x 0.300" W (21.97mm x 7.62mm)         Height - Seated (Max)       0.185" (4.69mm)	Applications	-
Supplier Device Package 16-DIP Size / Dimension 0.865" L x 0.300" W (21.97mm x 7.62mm) Height - Seated (Max) 0.185" (4.69mm)	Mounting Type	Through Hole
Size / Dimension       0.865" L x 0.300" W (21.97mm x 7.62mm)         Height - Seated (Max)       0.185" (4.69mm)	Package / Case	16-DIP (0.300", 7.62mm)
Height - Seated (Max) 0.185" (4.69mm)	Supplier Device Package	16-DIP
	Size / Dimension	0.865" L x 0.300" W (21.97mm x 7.62mm)
Report errors?	Height - Seated (Max)	0.185" (4.69mm)
-		Report errors?

#### 4116R-3-181/391LF Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **4116R-3-181/391LF Payment Methods**



















## 4116R-3-181/391LF Shipping Methods













If you have any question about 4116R-3-181/391LF, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com