



416F26023CSR Information



For Reference Only

Part Number 416F26023CSR

Manufacturer CTS-Frequency Controls

Category Crystals, Oscillators, Resonators

Crystals

Description CRYSTAL 26.000 MHZ SERIES SMT

Package 4-SMD, No Lead

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









416F26023CSR Specifications

Manufacturer Part Number416F26023CSRManufacturerCTS-Frequency ControlsCategoryCrystals, Oscillators, ResonatorsPackage4-SMD, No LeadSeries416TypeMHz CrystalFrequency26MHzFrequency Stability±30ppmFrequency Tolerance±20ppmLoad CapacitanceSeriesESR (Equivalent Series Resistance)200 OhmOperating ModeFundamentalOperating Temperature-20°C ~ 70°CRatings-Mounting TypeSurface MountPackage / Case4-SMD, No LeadSize / Dimension0.063" L x 0.047" W (1.60mm x 1.20mm)	*	
Category Crystals, Oscillators, Resonators Crystals Package 4-SMD, No Lead Series 416 Type MHz Crystal Frequency 26MHz Frequency Stability ±30ppm Frequency Tolerance ±20ppm Load Capacitance ESR (Equivalent Series Resistance) Operating Mode Operating Temperature Coperating Temperature Ratings Mounting Type Surface Mount Package / Case Size / Dimension Crystals, Oscillators, Resonators Crystals Crystals Crystals Crystals Assonited Series 100 MHz Crystal 4-SMD, No Lead Size / Dimension Copystals Crystals, Oscillators, Resonators Crystals Crystals Crystals Crystals Crystals Crystals Assonited Series 100 Copystals Crystals 4-SMD, No Lead Size / Dimension Copystals Crystals Alsonited Crystals Assonited Crystals Crystals Assonited Crystals Crystals Assonited Crystals Assonited Crystals Assonited Crystals Assonited Crystals Assonited Crystals Assonited Copystals Co	Manufacturer Part Number	416F26023CSR
Package 4-SMD, No Lead Series 416 Type MHz Crystal Frequency 26MHz Frequency Stability ±30ppm Frequency Tolerance ±20ppm Load Capacitance Series ESR (Equivalent Series Resistance) 200 Ohm Operating Mode Fundamental Operating Temperature -20°C ~ 70°C Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.063" L x 0.047" W (1.60mm x 1.20mm)	Manufacturer	CTS-Frequency Controls
Package 4-SMD, No Lead Series 416 Type MHz Crystal Frequency 26MHz Frequency Stability ±30ppm Frequency Tolerance ±20ppm Load Capacitance Series ESR (Equivalent Series Resistance) 200 Ohm Operating Mode Fundamental Operating Temperature -20°C ~ 70°C Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.063" L x 0.047" W (1.60mm x 1.20mm)	Category	Crystals, Oscillators, Resonators
Series 416 Type MHz Crystal Frequency 26MHz Frequency Stability ±30ppm Frequency Tolerance ±20ppm Load Capacitance Series ESR (Equivalent Series Resistance) 200 Ohm Operating Mode Fundamental Operating Temperature -20°C ~70°C Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.063" L x 0.047" W (1.60mm x 1.20mm)		Crystals
Type MHz Crystal Frequency 26MHz Frequency Stability ±30ppm Frequency Tolerance ±20ppm Load Capacitance Series ESR (Equivalent Series Resistance) 200 Ohm Operating Mode Fundamental Operating Temperature -20°C ~ 70°C Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.063" L x 0.047" W (1.60mm x 1.20mm)	Package	4-SMD, No Lead
Frequency Stability ±30ppm Frequency Tolerance ±20ppm Load Capacitance Series ESR (Equivalent Series Resistance) 200 Ohm Operating Mode Fundamental Operating Temperature -20°C ~ 70°C Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.063" L x 0.047" W (1.60mm x 1.20mm)	Series	416
Frequency Stability ±30ppm Frequency Tolerance ±20ppm Load Capacitance Series ESR (Equivalent Series Resistance) 200 Ohm Operating Mode Fundamental Operating Temperature -20°C ~ 70°C Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.063" L x 0.047" W (1.60mm x 1.20mm)	Туре	MHz Crystal
Frequency Tolerance ±20ppm Load Capacitance Series ESR (Equivalent Series Resistance) 200 Ohm Operating Mode Fundamental Operating Temperature -20°C ~ 70°C Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.063" L x 0.047" W (1.60mm x 1.20mm)	Frequency	26MHz
Load CapacitanceSeriesESR (Equivalent Series Resistance)200 OhmOperating ModeFundamentalOperating Temperature-20°C ~ 70°CRatings-Mounting TypeSurface MountPackage / Case4-SMD, No LeadSize / Dimension0.063" L x 0.047" W (1.60mm x 1.20mm)	Frequency Stability	±30ppm
ESR (Equivalent Series Resistance) Operating Mode Fundamental Operating Temperature -20°C ~ 70°C Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 200 Ohm Fundamental -20°C ~ 70°C Surface Mount 0.063" L x 0.047" W (1.60mm x 1.20mm)	Frequency Tolerance	±20ppm
Operating Mode Operating Temperature -20°C ~ 70°C Ratings Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension O.063" L x 0.047" W (1.60mm x 1.20mm)	Load Capacitance	Series
Operating Temperature -20°C ~ 70°C Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.063" L x 0.047" W (1.60mm x 1.20mm)	ESR (Equivalent Series Resistance)	200 Ohm
Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.063" L x 0.047" W (1.60mm x 1.20mm)	Operating Mode	Fundamental
Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.063" L x 0.047" W (1.60mm x 1.20mm)	Operating Temperature	-20°C ~ 70°C
Package / Case 4-SMD, No Lead Size / Dimension 0.063" L x 0.047" W (1.60mm x 1.20mm)	Ratings	-
Size / Dimension 0.063" L x 0.047" W (1.60mm x 1.20mm)	Mounting Type	Surface Mount
	Package / Case	4-SMD, No Lead
	Size / Dimension	0.063" L x 0.047" W (1.60mm x 1.20mm)
Height - Seated (Max) 0.018" (0.45mm)	Height - Seated (Max)	0.018" (0.45mm)
Report errors?		Report errors?

416F26023CSR Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

416F26023CSR Payment Methods



















416F26023CSR Shipping Methods













If you have any question about 416F26023CSR, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com