



416F37412ATT Information

www.medicale.m

For Reference Only

Part Number 416F37412ATT

Manufacturer CTS-Frequency Controls

Category Crystals, Oscillators, Resonators

Crystals

Description CRYSTAL 37.400 MHZ 6PF SMT

Package 4-SMD, No Lead

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









416F37412ATT Specifications

Manufacturer Part Number Manufacturer CTS-Frequency Controls Crystals, Oscillators, Resonators Crystals Package 4-SMD, No Lead Series 416 Type MHz Crystal Frequency Stability Frequency Stability Frequency Tolerance Load Capacitance ESR (Equivalent Series Resistance) Operating Mode Operating Temperature Package / Case Mounting Type Surface Mount Package / Case Size / Dimension Wand CTystal 4-SMD, No Lead Size / Dimension U.063" L x 0.047" W (1.60mm x 1.20mm)		
Category Crystals, Oscillators, Resonators Crystals Package 4-SMD, No Lead Series 416 Type MHz Crystal Frequency 37.4MHz Frequency Stability ±20ppm Frequency Tolerance ±10ppm Load Capacitance 6pF ESR (Equivalent Series Resistance) 200 Ohm Operating Mode Fundamental Operating Temperature -10°C ~ 60°C Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.063" L x 0.047" W (1.60mm x 1.20mm)	Manufacturer Part Number	416F37412ATT
Crystals Package 4-SMD, No Lead Series 416 Type MHz Crystal Frequency 37.4MHz Frequency Stability ±20ppm Frequency Tolerance ±10ppm Load Capacitance 6pF ESR (Equivalent Series Resistance) 200 Ohm Operating Mode Fundamental Operating Temperature -10°C ~ 60°C Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.063" L x 0.047" W (1.60mm x 1.20mm)	Manufacturer	CTS-Frequency Controls
Package 4-SMD, No Lead Series 416 Type MHz Crystal Frequency 37.4MHz Frequency Stability ±20ppm Frequency Tolerance ±10ppm Load Capacitance 6pF ESR (Equivalent Series Resistance) 200 Ohm Operating Mode Fundamental Operating Temperature -10°C ~ 60°C Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.063" L x 0.047" W (1.60mm x 1.20mm)	Category	Crystals, Oscillators, Resonators
Series 416 Type MHz Crystal Frequency 37.4MHz Frequency Stability ±20ppm Frequency Tolerance ±10ppm Load Capacitance 6pF ESR (Equivalent Series Resistance) 200 Ohm Operating Mode Fundamental Operating Temperature -10°C ~ 60°C Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.063" L x 0.047" W (1.60mm x 1.20mm)		Crystals
Type MHz Crystal Frequency 37.4MHz Frequency Stability ±20ppm Frequency Tolerance ±10ppm Load Capacitance 6pF ESR (Equivalent Series Resistance) 200 Ohm Operating Mode Fundamental Operating Temperature -10°C ~ 60°C Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.063" L x 0.047" W (1.60mm x 1.20mm)	Package	4-SMD, No Lead
Frequency Stability $\pm 20 \mathrm{ppm}$ Frequency Tolerance $\pm 10 \mathrm{ppm}$ Load Capacitance $6 \mathrm{pF}$ ESR (Equivalent Series Resistance) $200 \mathrm{Ohm}$ Operating Mode Fundamental Operating Temperature $-10^{\circ}\mathrm{C} \sim 60^{\circ}\mathrm{C}$ Ratings $-$ Mounting Type Surface Mount Package / Case $4-\mathrm{SMD}$, No Lead Size / Dimension $0.063^{\circ}\mathrm{L} \times 0.047^{\circ}\mathrm{W} (1.60 \mathrm{mm} \times 1.20 \mathrm{mm})$	Series	416
Frequency Stability ±20ppm Frequency Tolerance ±10ppm Load Capacitance 6pF ESR (Equivalent Series Resistance) 200 Ohm Operating Mode Fundamental Operating Temperature -10°C ~ 60°C Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.063" L x 0.047" W (1.60mm x 1.20mm)	Type	MHz Crystal
Frequency Tolerance $\pm 10 \mathrm{ppm}$ Load Capacitance $6 \mathrm{pF}$ ESR (Equivalent Series Resistance) $200 \mathrm{~Ohm}$ Operating Mode Fundamental Operating Temperature $-10^{\circ}\mathrm{C} \sim 60^{\circ}\mathrm{C}$ Ratings $-$ Mounting Type Surface Mount Package / Case 4-SMD , No Lead Size / Dimension $0.063'' \mathrm{L} \times 0.047'' \mathrm{W} (1.60 \mathrm{mm} \times 1.20 \mathrm{mm})$	Frequency	37.4MHz
Load Capacitance 6pF ESR (Equivalent Series Resistance) 200 Ohm Operating Mode Fundamental Operating Temperature -10°C ~ 60°C Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.063" L x 0.047" W (1.60mm x 1.20mm)	Frequency Stability	±20ppm
ESR (Equivalent Series Resistance) Operating Mode Fundamental Operating Temperature -10°C ~ 60°C Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.063" L x 0.047" W (1.60mm x 1.20mm)	Frequency Tolerance	± 10 ppm
Operating ModeFundamentalOperating Temperature $-10^{\circ}\text{C} \sim 60^{\circ}\text{C}$ Ratings-Mounting TypeSurface MountPackage / Case4-SMD, No LeadSize / Dimension 0.063 " L x 0.047 " W $(1.60\text{mm x } 1.20\text{mm})$	Load Capacitance	6pF
$ \begin{array}{cccccccccccccccccccccccccccccccccccc$	ESR (Equivalent Series Resistance)	200 Ohm
Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.063" L x 0.047" W (1.60mm x 1.20mm)	Operating Mode	Fundamental
Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.063" L x 0.047" W (1.60mm x 1.20mm)	Operating Temperature	-10°C ~ 60°C
Package / Case 4-SMD, No Lead Size / Dimension 0.063" L x 0.047" W (1.60mm x 1.20mm)	Ratings	-
Size / Dimension 0.063" L x 0.047" W (1.60mm x 1.20mm)	Mounting Type	Surface Mount
	Package / Case	4-SMD, No Lead
Height Costed (May)	Size / Dimension	0.063" L x 0.047" W (1.60mm x 1.20mm)
neight - Scaled (Max) 0.018 (0.43fillit)	Height - Seated (Max)	0.018" (0.45mm)
Report errors?		Report errors?

416F37412ATT Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

416F37412ATT Payment Methods





















416F37412ATT Shipping Methods













If you have any question about 416F37412ATT, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com